
Gamma Ray
Resistivity
Density
Neutron
Caliper
Bit Size
Delta Rho
PE
Photoelectric Factor
Mud Weight
Viscosity
Chlorides
Fluid Loss
pH
Rm @ Meas. Temp
Rmf @ Meas. Temp
Rmc @ Meas. Temp
Source of Rmf and Rmc
Rm @ BHT
Mud Type
Time Since Circulation
Time on Bottom
Max Recorded Temp
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Logged Interval
Type Fluid in Hole
Salinity
Density / Viscosity
Fluid Loss
Source of Sample
Rm @ Meas. Temp
Rmf @ Meas. Temp
Rmc @ Meas. Temp
Source of Rmf and Rmc
Rm @ BHT
Drill Collar Size
Drill Collar Length
Drill Pipe Size
Drill Pipe Length



9	Collar Locator	-1	0	Amplitude (mV)	100	200	Variable Density	1200
0	GR (GAPI)	150	800	Travel Time (usec)	200			

Database File: hrmu1113.db
Dataset Pathname: pass7
Presentation Format: cbldig
Dataset Creation: Wed Sep 24 17:07:44 2014 by Log Std Casedhole 10071
Charted by: Depth in Feet scaled 1:240

9	Collar Locator	-1	0	Amplitude (mV)	100	200	Variable Density	1200
0	GR (GAPI)	150	800	Travel Time (usec)	200			



9	Collar Locator	-1	0	Amplitude (mV)	100	200	Variable Density	1200
0	GR (GAPI)	150	800	Travel Time (usec)	200			

Calibration Report

Database File: hrmu1113.db
Dataset Pathname: pass1
Dataset Creation: Wed Sep 24 16:24:30 2014 by Log Std Casedhole 10071

Gamma Ray Calibration Report

Serial Number:	061120GR	
Tool Model:	PROBE	
Performed:	Tue Jul 08 12:29:35 2014	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	5.5dig040201		
Tool Model:	Probe275Digital		
Performed:	Wed Sep 24 16:12:22 2014		
Depth:	87.75	ft	
Casing Diameter:	5.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.25	0	mV
Calibrated Amplitude:	71.921	71.921	mV
Reading at Signal Zero:	0.0121094	0.0164795	V
Reading in Free Pipe:	2.33103	1.54458	V
Gain:	30.907	47.0656	
Offset:	-0.124265	-0.775618	