

Generated

Ancient volcanic eruptions in T. ophiu. Found on Ancient Rocks Rocks. Geologic

Ancient volcanic eruptions in T. ophiu. Found on Ancient Rocks Rocks. Geologic

Drilling Contractor: Atlas Drilling
Rig Name: Rig 7
Rig Type: Jack-up
Vessel Name: Atlas Explorer
Company Man: Robert Chen
Toolpusher: Mike Sullivan
Geologist: Sarah Williams
Mud Engineer: David Lee
Mud Logger: Jennifer Brown
Date: 15 March 2024
Time: 08:00
Depth: 1,250 m
Weight on Bit: 25 klbs
Rotary Speed: 120 rpm
Flow Rate: 500 gpm
Standpipe Pressure: 2,500 psi
Mud Weight: 10.5 ppg
Viscosity: 45 sec/qt
Fluid Loss: 5 cc/30 min
pH: 9.5
Chlorides: 20,000 mg/L
Calcium: 400 mg/L
Solids: 8%
Oil: 2%
Water: 90%
Sand: 1%
Gas: 0.5%
Cuttings Description: Shale, gray, soft, fissile
Lithology: Shale 80%, Sandstone 15%, Limestone 5%
Gas Ratios: C1/C2 = 10, C1/C3 = 20, C1/nC4 = 30
Gas Data: Total Gas = 500 units, Background Gas = 200 units, Connection Gas = 1,000 units, Trip Gas = 1,500 units
Drilling Parameters: ROP = 50 ft/hr, WOB = 25 klbs, RPM = 120, Torque = 10,000 ft-lbs
Drilling Fluids Data: Mud Weight = 10.5 ppg, Viscosity = 45 sec/qt, Fluid Loss = 5 cc/30 min, pH = 9.5, Chlorides = 20,000 mg/L, Calcium = 400 mg/L, Solids = 8%, Oil = 2%, Water = 90%, Sand = 1%, Gas = 0.5%
Mud Properties: Mud Weight = 10.5 ppg, Viscosity = 45 sec/qt, Fluid Loss = 5 cc/30 min, pH = 9.5, Chlorides = 20,000 mg/L, Calcium = 400 mg/L, Solids = 8%, Oil = 2%, Water = 90%, Sand = 1%, Gas = 0.5%
Mud Gas Data: Total Gas = 500 units, Background Gas = 200 units, Connection Gas = 1,000 units, Trip Gas = 1,500 units
Gas Chromatography: C1 = 80%, C2 = 8%, C3 = 4%, nC4 = 2%, iC4 = 1%, nC5 = 0.5%, iC5 = 0.5%, C6+ = 4%
Gas Trap Data: Efficiency = 90%, Pressure = 2,500 psi, Temperature = 120°F, Flow = 500 gpm, Volume = 1,000 cf, Duration = 10 min, Frequency = 1 Hz, Amplitude = 100 units, Phase = 0°, Quality = 95%, Signal = 90%, Noise = 10%, Baseline = 200 units, Drift = 5 units/hr, Calibration = 100%, Validation = 100%, Verification = 100%, Certification = 100%, Accreditation = 100%, Compliance = 100%, Regulation = 100%, Standard = 100%, Specification = 100%, Requirement = 100%, Procedure = 100%, Method = 100%, Technique = 100%, Equipment = 100%, Instrument = 100%, Device = 100%, Sensor = 100%, Detector = 100%, Analyzer = 100%, Chromatograph = 100%, Mass Spectrometer = 100%, Spectrometer = 100%, Ionization Mass Spectrometer = 100%, Desorption Ionization Mass Spectrometer = 100%, Ambient Ionization Mass Spectrometer = 100%, Vacuum Ionization Mass Spectrometer = 100%, Atmospheric Pressure Ionization Mass Spectrometer = 100%, Negative Ion Chemical Ionization Mass Spectrometer = 100%, Positive Ion Chemical Ionization Mass Spectrometer = 100%, Electron Ionization Mass Spectrometer = 100%, Chemical Ionization Mass Spectrometer = 100%, Proton Transfer Reaction Mass Spectrometer = 100%, Selected Ion Flow Tube Mass Spectrometer = 100%, Flowing Afterglow Ionization Mass Spectrometer = 100%, Dielectric Barrier Discharge Ionization Mass Spectrometer = 100%, Low Temperature Plasma Ionization Mass Spectrometer = 100%, Direct Analysis in Real Time Mass Spectrometer = 100%, Desorption Electrospray Ionization Mass Spectrometer = 100%, Surface Assisted Laser Desorption Ionization Mass Spectrometer = 100%, Surface Enhanced Laser Desorption Ionization Mass Spectrometer = 100%, Laser Desorption Mass Spectrometer = 100%, Laser Ablation Mass Spectrometer = 100%, Resonance Enhanced Multiphoton Ionization Mass Spectrometer = 100%, Plasma Desorption Mass Spectrometer = 100%, Liquid Secondary Ion Mass Spectrometer = 100%, Secondary Ion Mass Spectrometer = 100%, Fast Atom Bombardment Mass Spectrometer = 100%, Field Desorption Mass Spectrometer = 100%, Field Ionization Mass Spectrometer = 100%, Thermal Ionization Mass Spectrometer = 100%, Glow Discharge Ionization Mass Spectrometer = 100%, Inductively Coupled Plasma Ionization Mass Spectrometer = 100%, Atmospheric Pressure Photoionization Mass Spectrometer = 100%, Atmospheric Pressure Chemical Ionization Mass Spectrometer = 100%, Matrix Assisted Laser Desorption Ionization Mass Spectrometer = 100%, Electrospray Ionization Mass Spectrometer = 100%, Fourier Transform Mass Spectrometer = 100%, Ion Cyclotron Resonance Mass Spectrometer = 100%, Orbitrap Mass Spectrometer = 100%, Ion Trap Mass Spectrometer = 100%, Quadrupole Mass Spectrometer = 100%, Time of Flight Mass Spectrometer = 100%, Linear Time of Flight Mass Spectrometer = 100%, Reflectron Time of Flight Mass Spectrometer = 100%, Double Focusing Mass Spectrometer = 100%, Electrostatic Sector Mass Spectrometer = 100%, Magnetic Sector Mass Spectrometer = 100%, Fourier Transform Ion Cyclotron Resonance Mass Spectrometer = 100%, Hybrid Mass Spectrometer = 100%, Multiple Mass Spectrometer = 100%, Tandem Mass Spectrometer = 100%, Linear Time of Flight Mass Spectrometer = 100%, Reflectron Time of Flight Mass Spectrometer = 100%, Double Focusing Mass Spectrometer = 100%, Electrostatic Sector Mass Spectrometer = 100%, Magnetic Sector Mass Spectrometer = 100%, Fourier Transform Ion Cyclotron Resonance Mass Spectrometer = 100%, Hybrid Mass Spectrometer = 100%, Multiple Mass Spectrometer = 100%, Tandem Mass Spectrometer = 100%










Ch 1 Trace
Ch 2 Trace
Ch 3 Trace
Ch 4 Trace
Math Trace
Ref Trace



Calibration Report

Database File: 13663.db
Dataset Pathname: pass2
Dataset Creation: Tue Aug 26 06:12:28 2014 by Log 0

Dual Induction Calibration Report

Serial-Model: 1011-PSI
Surface Cal Performed:

Loop:	Readings Air	Readings Loop	References Air	References Loop		Results m	Results b
Deep	0.000	1.000	0.000	1.000	mmho/m	0.510	-28.000
Medium	0.000	1.000	0.000	1.000	mmho/m	0.440	-28.000

Compensated Density Calibration Report

Serial-Model: 128-PSI
Source / Verifier: 4400 / PSI
Master Calibration Performed: Wed Jul 02 08:14:00 2014
Before Survey Verification Performed:
After Survey Verification Performed:

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.750	g/cc	6051.14	2934.47	cps
Aluminum	2.690	g/cc	1088.83	1765.21	cps

Spine Angle = 73.49 Density/Spine Ratio = 0.525

	Size		Reading	
Small Ring	4.50	in	1.18	
Large Ring	13.50	in	1.03	

Compensated Neutron Calibration Report

Serial Number: 826
Tool Model: PSI

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.9000
Long Space	1.00	cps	1.00	cps	2.0900

Gamma Ray Calibration Report

Serial Number: 923
Tool Model: PSI
Performed: Fri Aug 22 23:09:02 2014

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.6000 GAPI/cps

Log Variables

Database:C:\Warrior\Data\13663.db
Dataset: field/well/run1/pass4

Top - 4270.00 ft

SZCOR	NPORSEL	FLUIDDEN	MATRXDEN	SPSHIFT	SNDERRM	SNDERR	SRFTEMP
		g/cc	g/cc	m/v	mmho/m	mmho/m	degF
Off	Limestone	1	2.71	0	0	0	0

CASEOD	PERFS	TDEPTH	BOTTEMP	BOREID
in		ft	degF	in
5.5	0	0	190	7.875

4270.00 ft - 4760.00 ft

NPORSEL	MATRXDEN
	g/cc
Sandstone	2.68

4760.00 ft - 7620.00 ft

NPORSEL	MATRXDEN
	g/cc
Limestone	2.71

7620.00 ft - 7860.00 ft

NPORSEL	MATRXDEN
	g/cc
Sandstone	2.68

7860.00 ft - Bottom

NPORSEL	MATRXDEN
	g/cc
Limestone	2.71