

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
Document Number: 400701318			
Date Received: 10/03/2014			

SUNDRY NOTICE

Submit a signed original. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full in Comments or provide as an attachment. Identify Well by API Number; identify Oil and Gas Location by Location ID Number; identify other Facility by Facility ID Number.

OGCC Operator Number: 47120 Contact Name Cheryl Light
 Name of Operator: KERR MCGEE OIL & GAS ONSHORE LP Phone: (720) 929-6461
 Address: P O BOX 173779 Fax: (720) 929-7461
 City: DENVER State: CO Zip: 80217-3779 Email: cheryl.light@anadarko.com

Complete the Attachment
Checklist

OP OGCC

API Number : 05- 123 24601 00 OGCC Facility ID Number: 288520
 Well/Facility Name: HERRMAN Well/Facility Number: 21-10
 Location QtrQtr: NWNE Section: 10 Township: 3N Range: 66W Meridian: 6
 County: WELD Field Name: WATTENBERG
 Federal, Indian or State Lease Number: _____

Survey Plat		
Directional Survey		
Srvc Eqpmt Diagram		
Technical Info Page		
Other		

CHANGE OF LOCATION OR AS BUILT GPS REPORT

- Change of Location * As-Built GPS Location Report As-Built GPS Location Report with Survey

* Well location change requires new plat. A substantive surface location change may require new Form 2A.

SURFACE LOCATION GPS DATA Data must be provided for Change of Surface Location and As Built Reports.

Latitude _____ PDOP Reading _____ Date of Measurement _____
 Longitude _____ GPS Instrument Operator's Name _____

LOCATION CHANGE (all measurements in Feet)

Well will be: _____ (Vertical, Directional, Horizontal)

Change of **Surface** Footage **From** Exterior Section Lines:

	FNL/FSL		FEL/FWL
	704	FNL	1980
	FNL	FEL	FEL

Change of **Surface** Footage **To** Exterior Section Lines:

--	--	--	--

Current **Surface** Location **From** QtrQtr NWNE Sec 10

Twp	<u>3N</u>	Range	<u>66W</u>	Meridian	<u>6</u>
-----	-----------	-------	------------	----------	----------

New **Surface** Location **To** QtrQtr _____ Sec _____

Twp	_____	Range	_____	Meridian	_____
-----	-------	-------	-------	----------	-------

Change of **Top of Productive Zone** Footage **From** Exterior Section Lines:

	1250	FNL	2610	FEL
--	------	-----	------	-----

Change of **Top of Productive Zone** Footage **To** Exterior Section Lines:

				**
--	--	--	--	----

Current **Top of Productive Zone** Location **From** Sec 10

Twp	<u>3N</u>	Range	<u>66W</u>
-----	-----------	-------	------------

New **Top of Productive Zone** Location **To** Sec _____

Twp	_____	Range	_____
-----	-------	-------	-------

Change of **Bottomhole** Footage **From** Exterior Section Lines:

	1261	FNL	2624	FEL
--	------	-----	------	-----

Change of **Bottomhole** Footage **To** Exterior Section Lines:

				**
--	--	--	--	----

Current **Bottomhole** Location Sec 10 Twp 3N Range 66W

** attach deviated drilling plan

New **Bottomhole** Location Sec _____ Twp _____ Range _____

Is location in High Density Area? _____

Distance, in feet, to nearest building _____, public road: _____, above ground utility: _____, railroad: _____,
 _____ property line: _____, lease line: _____, well in same formation: _____

Ground Elevation _____ feet Surface owner consultation date _____

Comments:

ENGINEERING AND ENVIRONMENTAL WORK

NOTICE OF CONTINUED TEMPORARILY ABANDONED STATUS

Indicate why the well is temporarily abandoned and describe future plans for utilization in the COMMENTS box below or provide as an attachment, as required by Rule 319.b.(3).

Date well temporarily abandoned _____ Has Production Equipment been removed from site? _____

Mechanical Integrity Test (MIT) required if shut in longer than 2 years. Date of last MIT _____

SPUD DATE: _____

TECHNICAL ENGINEERING AND ENVIRONMENTAL WORK

Details of work must be described in full in the COMMENTS below or provided as an attachment.

NOTICE OF INTENT Approximate Start Date 10/17/2014

REPORT OF WORK DONE Date Work Completed _____

<input type="checkbox"/> Intent to Recomplete (Form 2 also required)	<input type="checkbox"/> Request to Vent or Flare	<input type="checkbox"/> E&P Waste Mangement Plan
<input type="checkbox"/> Change Drilling Plan	<input checked="" type="checkbox"/> Repair Well	<input type="checkbox"/> Beneficial Reuse of E&P Waste
<input type="checkbox"/> Gross Interval Change	<input type="checkbox"/> Rule 502 variance requested. Must provide detailed info regarding request.	
<input type="checkbox"/> Other _____	<input type="checkbox"/> Status Update/Change of Remediation Plans for Spills and Releases	

COMMENTS:

- 1 A directional survey of this well has already been completed.
- 2 Last record of casing pressure test was to 6000 psi on 4/25/2007.
- 3 Call Wattenberg IOC (970-506-5980) at least 24 hrs prior to rig move. If not already completed, request that they catch and remove plunger, isolate production equipment and remove any automation equipment prior to the rig showing up. Install perimeter fence as needed.
- 4 MIRU Slick line. Fish plunger if necessary and tag PBMD (Should be 8051').
- 5 Prepare location for base beam rig.
- 6 Spot 25 jts of 2-3/8" 4.7# J-55 8RD EUE tbg.
- 7 Spot 57 jts of 1-1/4" 2.33# J-55 IJ tbg.
- 8 Notify mud company to have 10.0 ppg drilling mud on standby.
- 9 Check wellhead for flanged-style connections and 5,000 psi rating. If wellhead is not rated to 5,000 psi or does not have flanged-style connections, install one that does prior to completing the job.
- 10 MIRU WO rig. Kill well with fresh water with biocide. ND wellhead, NU BOP.
- 11 Run two 2" lines from starting head to return tanks.
- 12 PU 8-10' landing joint with TIW safety valve on top and screw into the tbg hanger. Back out the lock down pins and pull up on the tbg string to break any possible sand bridges. Do not exceed 80% of tubing tensile strength, or 57,384-lb.
- 13 Unseat tbg hanger and LD tbg hanger and landing joint. Install rubber wiper in stripping head.
- 14 MIRU EMI equipment. TOOH with 2-3/8" tbg. EMI tbg while TOOH. Lay down joints with wall loss or penetrations >35%. Replace joints as necessary. Keep yellow and blue band tubing. Note joint number and depth of tubing leak(s) on production equipment failure report in OpenWells. Clearly mark all junk (red band) tubing sent to yard.
- 15 PU and TIH with 233 jts of 2-3/8" 4.7# J-55 tbg with 4.5" RBP (4.5" 11.6# I-80). Set RBP at +/- 7000' (Collars at 6980' and 7026'). Spot 2 sx sand on top of RBP. TOOH. SB tbg.
- 16 Pressure test RBP to 2,000 psi for 15 minutes. (Pressure test to make sure plug is set correctly)
- 17 ND BOP, un-land 4-1/2" csg, RU dual-entry flange, NU BOP.
- 18 PU and TIH with 57 jts 1-1/4" 2.33# IJ tbg to 1700'.
- 19 Circulate 120 bbls with rig pump (Circulate at least 1.5x annular volume from 1700') with 10.0 ppg mud sweep at the end.
- 20 TOOH 7 jts 1-1/4" tbg to +/- 1500'.
- 21 ND BOP, MIRU cement company.
- 22 Commence pumping cement job consisting of 5 bbls fresh water, 20 bbls sodium metasilicate, 5 bbls fresh water and 57 bbl (240 sx) of Type III with 1/4 lb/sk cello-flake mixed at 14.8 ppg and 1.33 cuft/sk blended for a 3 hr pump time (Cement from 1500' to 484').
- 23 Break lines, clean up with fresh water, RMDO cement company.
- 24 ND BOP, ND dual entry flange, re-land 4-1/2" csg and NU BOP. Leave well shut in minimum of 24 hours.
- 25 MIRU wire line and run CCL-GR-CBL-VDL from 1600' to 0'. If Fox Hill plug is not above 488', contact engineering for further instructions. Email logs to engineering and DJVendors@anadarko.com. RDMO wire line.
- 26 PU and TIH with 2-3/8" notched collar, 2-3/8" XN, 2-3/8" 4.7# J-55 tbg. Land 2-3/8" tbg @ +/- 7868' (1 jt above top J Sand perf).
- 27 ND BOP, NU master valve.
- 28 Install 7 1/16" x 5,000 psi tubing head adaptor with new 5,000 psi master valve threaded 2 3/8" connection. Make sure all wellhead valves are rated to 5,000 psi.
- 29 Install 2 3/8" pup joint above the master valve. Pressure test the tubing head from below the tubing head through the master valve to 5,000 psi with hydro tester. NU 5k wellhead.
- 30 RMDO WO rig. Return well to production team.
- 31 Clean location and swab well back to production. Notify field foreman/field coordinator of finished work and turn well back over to production team.

CASING AND CEMENTING CHANGES

Casing Type	Size	Of /	Hole	Size	Of /	Casing	Wt/Ft	Csg/LinTop	Setting Depth	Sacks of Cement	Cement Bottom	Cement Top

H2S REPORTING

Data Fields in this section are intended to document Sample and Location Data associated with the collection of a Gas Sample that is submitted for Laboratory Analysis.

Gas Analysis Report must be attached.

H2S Concentration: _____ in ppm (parts per million) Date of Measurement or Sample Collection _____

Description of Sample Point:

Absolute Open Flow Potential _____ in CFPD (cubic feet per day)

Description of Release Potential and Duration (If flow is not open to the atmosphere, identify the duration in which the container or pipeline would likely be opened for servicing operations.):

--

Distance to nearest occupied residence, school, church, park, school bus stop, place of business, or other areas where the public could reasonably be expected to frequent: _____

Distance to nearest Federal, State, County, or municipal road or highway owned and principally maintained for public use: _____

COMMENTS:

--

Best Management Practices

No BMP/COA Type

Description

No BMP/COA Type	Description

Operator Comments:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Cheryl Light
Title: Sr. Regulatory Analyst Email: DJRegulatory@anadarko.com Date: 10/3/2014

Based on the information provided herein, this Sundry Notice (Form 4) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: SCHLAGENHAUF, MARK Date: 10/13/2014

CONDITIONS OF APPROVAL, IF ANY:

COA Type

Description

COA Type	Description
	The additional cement referenced shall be placed as indicated and comply with Rule 317.i. The placed cement shall be verified with a CBL and documented with a Form 5 Drilling Completion Report.

General Comments

User Group

Comment

Comment Date

User Group	Comment	Comment Date

Total: 0 comment(s)

Attachment Check List

Att Doc Num

Name

400701318	FORM 4 SUBMITTED
400701320	OTHER

Total Attach: 2 Files