HIGH RESOLUTION INDUCTION

PIONEER
Pioneer Energy Services

Company Bonanza Creek Energy Operating Co. LLC
Well Antelope B11-V41-33HNC
Field Wattenberg
County Weld
State Colorado

Company Bonanza Creek Energy Operating Co. LLC
Well Antelope B11-V41-33HNC
Field Wattenberg
County Weld State Colorado

Location: API #: 05123390650000
SHL: 1471' FNL & 350' FWL
SW NW
SEC 33 TWP 5N RGE 62W

Other Services
Density
Neutron

Permanent Datum	GL
Log Measured From	KB
Drilling Measured From	KB

Elevation 4579

Elevation
K.B. 4595
D.F. 4594
G.L. 4579

Date	May 9, 2014		
Run Number	1		
Depth Driller	5830		
Depth Logger	5841		
Bottom Logged Interval	5841		
Top Log Interval	Casing		
Casing Driller	467		
Casing Logger	467		
Bit Size	8-3/4"		
Type Fluid in Hole	Chem Gel		
Density / Viscosity	9.2 / 42		
pH / Fluid Loss	8.5 / --		
Source of Sample	Flowline		
Rm @ Meas. Temp	2.97 @ 68 F		
Rmf @ Meas. Temp	2.38 @ 68 F		
Rmc @ Meas. Temp	3.56 @ 68 F		
Source of Rmf / Rmc	Calc / Calc		
Rm @ BHT	1.19 @ 170 F		
Time Circulation Stopped	1100		
Time Logger on Bottom	1745		
Maximum Recorded Temperature	170 F		
Equipment Number	49		
Location	Brighton, CO		
Recorded By	Matt Gill		
Witnessed By	John Bradley		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Pioneer Wireline Services, LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Pioneer Wireline Services, LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

Annular volume calculated for 7" casing
Cade Drilling Rig 26
Thank you for using Pioneer Energy Services.



Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CHD (~0)	2.00	3.50	30.00
GR	0.00		GR-PSI (939)	2.92	3.50	40.00
CNLSC CNSSC	-3.67 -4.17		CNT-PSI (826)	5.00	3.50	70.00
DCAL LSD SSD	-11.84 -12.67 -13.17		CDL-PSI (128)	8.50	5.00	285.00
RLL3 CILD CILM SP	-17.52 -24.97 -28.42 -32.42		DIL-PSI (1024)	18.25	3.75	175.00

Dataset: 13550.db: field/well/run1/final
Total Length: 36.67 ft
Total Weight: 600.00 lb
O.D. 5.00 in

Database File: 13550.db
Dataset Pathname: final
Presentation Format: dilin5
Dataset Creation: Fri May 09 18:25:49 2014
Charted by: Depth in Feet scaled 1:600

0 SP (mV) 200	0 Deep Resistivity (Ohm-m) 50	1000 CILD (mmho/m) 0
6 Caliper (in) 16	0 Shallow Resistivity (Ohm-m) 50	
0 Gamma Ray (GAPI) 200	50 RILD (Ohm-m) 500	
TBHV (ft3) ABHV (ft3)	50 RLL3 (Ohm-m) 500	

0 SP (mV) 200	0 Deep Resistivity (Ohm-m) 50	1000 CILD (mmho/m) 0
6 Caliper (in) 16	0 Shallow Resistivity (Ohm-m) 50	
0 Gamma Ray (GAPI) 200	50 RILD (Ohm-m) 500	
TBHV (ft3) ABHV (ft3)	50 RLL3 (Ohm-m) 500	

Database File: 13550.db
Dataset Pathname: final
Presentation Format: dil
Dataset Creation: Fri May 09 18:25:49 2014
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (GAPI) 200	0.2 Deep Resistivity (Ohm-m) 2000
0 SP (mV) 200	0.2 Shallow Resistivity (Ohm-m) 2000
6 Caliper (in) 16	0.2 Medium Resistivity (Ohm-m) 2000
TBHV (ft3) ABHV (ft3)	0.2 Rt (Ohm-m) 2000



1690
596
1669
588
1800
1649
581
1628
574
1900
1608
566
1587
559
2000
1566
552
1545
544
2100
1524
536
1503
529
2200
1482
521
1461
514
2300
1441
507
1420
499
2400
1399
492
1378
484
2500
1357
477
1337
469
2600
1316
462
1295
454
2700
1274
447
1253
439
2800
1232
431
1211
424
2900
1190
416
1169
409
3000
1148
401
1127
394
3100
1106
386
1085
378
3200
1064
371
1044
364
3300
1023
356
1002
349
3400
981
341
960
334
3500
939
326
918
318
3600
897
311
876
303
3700
855
295
834
287
3800
813
279
791
272
3900
770
264
749
256
4000
728
248
707
241
4100
686
233
665
226
4200
645
218
624
211
4300
603
203
582
196
4400
562
189
541
182
4500
521
174
500
167
4600
479
160
459
153
4700
438
145
418
138
4800
397
131
377
124
4900
356
117
335
109
5000
314
102
294
95
5100
273
87
253
80
5200
232
73
212
66
5300
191
59
172
53
5400
153
47
134
42
5500
115
36
96
30
5600
76
24
57
18
5700



Calibration Report

Database File: 13550.db
Dataset Pathname: pass1
Dataset Creation: Fri May 09 17:14:14 2014 by Log 0

Dual Induction Calibration Report

Serial-Model: 1024-PSI
Surface Cal Performed:

	Readings		References			Results	
Loop:	Air	Loop	Air	Loop		m	b
Deep	0.000	1.000	0.000	1.000	mmho/m	0.580	-45.000
Medium	0.000	1.000	0.000	1.000	mmho/m	0.510	-40.000

Compensated Density Calibration Report

Serial-Model: 128-PSI
Master Calibration Performed: Tue Nov 05 00:36:11 2013

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.750	g/cc	5900.80	3069.93	cps
Aluminum	2.690	g/cc	1074.43	1919.88	cps

	Size		Reading
Small Ring		in	
Medium Ring		in	
Large Ring		in	

Compensated Neutron Calibration Report

Serial Number: 826
Tool Model: PSI

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.9000
Long Space	1.00	cps	1.00	cps	2.0900

Gamma Ray Calibration Report

Serial Number: 939
Tool Model: PSI
Performed: Mon Apr 21 14:34:25 2014

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.6200 GAPI/cps