Wellbore Diagram (Actual)

697-20-37D

Actual Wellbore — Mid-Continent

COMMENTS	EQUIPMENT DESCRIPTION
	1) F-Nipple @ +/- 4,400'
	2 sxs of cement
	CIBP @ 4,550
	Fish @ 5,542'



Perforations

5,259' - 5,500'

5,560' - 5,821'

5,915' - 6,092'

6,202' - 6,500'

PBTD 6,746 MD 6,452 TVD
TD 6,835 MD 6,537 TVD

Last Tag:
Last Workover:

FIELD	Cascade Creek
WELL	697-20-37D
COUNTY	Garfield
API No.	504513953
RKB ELEVATION	6,201
GL ELEVATION	6,183
RKB-GL	18
Lat: 39.502974	Long:-108.239688

DIRECTIONAL DATA

MAX ANGLE	NA	THRU	N/A
KOP	NA	TYPE	S-SHAPED

PRODUCTION DETAIL

	TUBING	CASING
SIZE	2 3/8	4 1/2
WEIGHT	4.7	11.6
GRADE	N-80	P-110
DEPTH	4,432	6,835
THREAD	8rd EUE	BTC
I.D.	1.995	4.000
DRIFT	1.901	3.875
BURST	11200	10,690
COLLAPSE	11,780	7,850
CAPACITY	0.00387	0.0155
# JOINTS		

PRODUCTION ASSEMBLY DETAIL

#	O. D. IN	I. D. IN	LENGTH FT	Description
1		1.810	0.86	F-Nipple
2		3.875		CIBP
3				
4				
5				
6				

CASING DETAIL

#	SIZE	WGHT	GRADE	THREAD	DEPTH
A	9 5/8	36	K-55	LTC	1,024
B	4 1/2	11.6	P-110	BTC	6,835
C					
D					

PRESSURE DATA

HIGHEST ANTICIPATED PRESSURE	3 PSI
Max SICP	
MAXIMUM ALLOWABLE SURFACE PRESS	3000 PSI
Valve & BOP rating	
WELL COMMUNICATION	N

Comments

Prepared by: S.Awosanya — Date: 23-Sep-2014