

FORM  
5ARev  
06/12

## State of Colorado

## Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400753372

Date Received:

## COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 96155  
 2. Name of Operator: WHITING OIL & GAS CORPORATION  
 3. Address: 1700 BROADWAY STE 2300  
 City: DENVER State: CO Zip: 80290  
 4. Contact Name: Pauleen Tobin  
 Phone: (303) 837-1661  
 Fax: (303) 390-4923  
 Email: pollyt@whiting.com

5. API Number 05-123-38339-00  
 6. County: WELD  
 7. Well Name: Razor Federal  
 Well Number: 26L-2302B  
 8. Location: QtrQtr: NWSW Section: 26 Township: 10N Range: 58W Meridian: 6  
 9. Field Name: DJ HORIZONTAL NIOBRARA Field Code: 16950

## Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/15/2014 End Date: 09/22/2014 Date of First Production this formation: 10/16/2014

Perforations Top: 6000 Bottom: 13844 No. Holes: 1440 Hole size: 3/8

Provide a brief summary of the formation treatment:

Open Hole: ☐

40-stage Frac: 79015 bbls ClearStar XL Gel; 20063 bbls Linear Gel; 5703120# 20/40 Wh snd, 134620# 40/70 Wh snd, 572 bbls 15% HCl, 27019 bbls Slickwater.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 126669

Max pressure during treatment (psi): 7664

Total gas used in treatment (mcf): 0

Fluid density at initial fracture (lbs/gal): 8.30

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.80

Total acid used in treatment (bbl): 572

Number of staged intervals: 40

Recycled water used in treatment (bbl): 0

Flowback volume recovered (bbl): 17209

Fresh water used in treatment (bbl): 126669

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 5837740

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

## Test Information:

Date: 11/26/2014 Hours: 24 Bbl oil: 402 Mcf Gas: 105 Bbl H2O: 207

Calculated 24 hour rate: Bbl oil: 402 Mcf Gas: 105 Bbl H2O: 207 GOR: 261

Test Method: Separator Casing PSI: 850 Tubing PSI: 330 Choke Size: 26/64

Gas Disposition: SOLD Gas Type: DRY Btu Gas: 1455 API Gravity Oil: 35

Tubing Size: 2 + 7/8 Tubing Setting Depth: 5702 Tbg setting date: 09/28/2014 Packer Depth: 5702

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Pauleen Tobin

Title: Engineer Tech Date: \_\_\_\_\_ Email pollyt@whiting.com  
:

### Attachment Check List

**Att Doc Num**      **Name**

400753388	WELLBORE DIAGRAM
-----------	------------------

Total Attach: 1 Files

### General Comments

**User Group**      **Comment**      **Comment Date**

--	--	--

Total: 0 comment(s)