



Job Number: SVGJ-100414

Company: Petroleum Development Corporation

Lease/Well: Purvis 10-1

Location: Weld County, CO

Rig Name: PSI Wireline

RKB: 0'

G.L. or M.S.L.: GL

State/Country: Colorado/USA

Declination: 9.03°

Grid: East To True

File name: F:\SURVEY\2010SU~1\PDC\PURV10-1.SVY

Date/Time: 07-Jul-10 / 08:33

Curve Name: Surface - 7190' M.D. (SRG)

WINSERVE SURVEY CALCULATIONS
 Minimum Curvature Method
 Vertical Section Plane .00
 Vertical Section Referenced to Wellhead
 Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
100.00	.16	86.15	100.00	.01	.14	.01	.14	86.15	.16
200.00	.35	35.82	200.00	.27	.46	.27	.53	59.78	.28
300.00	.85	238.63	300.00	.13	.00	.13	.13	1.26	1.18
400.00	.87	222.65	399.98	-.82	-1.14	-.82	1.41	234.50	.24
500.00	.88	216.07	499.97	-2.00	-2.11	-2.00	2.91	226.61	.10
600.00	.70	207.71	599.96	-3.16	-2.85	-3.16	4.25	222.05	.21
700.00	.61	214.37	699.96	-4.14	-3.43	-4.14	5.38	219.68	.12
800.00	.23	283.25	799.95	-4.53	-3.93	-4.53	6.00	220.92	.57
900.00	.68	315.71	899.95	-4.06	-4.54	-4.06	6.09	228.18	.50

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
1000.00	.94	297.02	999.94	-3.26	-5.68	-3.26	6.55	240.14	.37
1100.00	1.06	292.94	1099.93	-2.53	-7.27	-2.53	7.69	250.81	.14
1200.00	.96	264.34	1199.91	-2.25	-8.95	-2.25	9.23	255.88	.51
1300.00	.36	304.69	1299.90	-2.16	-10.04	-2.16	10.27	257.89	.72
1400.00	1.17	281.88	1399.90	-1.77	-11.30	-1.77	11.44	261.12	.85
1500.00	.34	307.93	1499.89	-1.37	-12.53	-1.37	12.61	263.75	.88
1600.00	1.09	276.52	1599.88	-1.08	-13.71	-1.08	13.76	265.48	.82
1700.00	.62	335.24	1699.87	-.48	-14.88	-.48	14.89	268.14	.93
1800.00	.82	271.19	1799.86	.02	-15.83	.02	15.83	270.08	.78
1900.00	.90	319.83	1899.85	.64	-17.05	.64	17.06	272.14	.71
2000.00	.10	268.18	1999.85	1.23	-17.64	1.23	17.69	274.00	.84
2200.00	.44	287.44	2199.84	1.46	-18.55	1.46	18.61	274.50	.17
2400.00	1.02	242.08	2399.83	.86	-20.85	.86	20.87	272.35	.39
2600.00	.70	199.35	2599.81	-1.13	-22.83	-1.13	22.86	267.17	.35
2800.00	1.17	215.82	2799.78	-3.94	-24.43	-3.94	24.75	260.84	.27
3000.00	.55	237.92	2999.76	-6.10	-26.44	-6.10	27.14	257.00	.35
3200.00	1.49	255.08	3199.72	-7.28	-29.77	-7.28	30.64	256.25	.49
3400.00	1.36	281.59	3399.66	-7.48	-34.60	-7.48	35.40	257.81	.33
3600.00	.72	279.89	3599.63	-6.78	-38.17	-6.78	38.77	259.92	.32
3800.00	.96	263.34	3799.61	-6.76	-41.07	-6.76	41.62	260.65	.17
4000.00	1.69	252.79	3999.55	-7.83	-45.55	-7.83	46.22	260.25	.38
4200.00	1.25	245.94	4199.49	-9.59	-50.36	-9.59	51.26	259.22	.24
4400.00	.50	318.57	4399.47	-9.83	-52.93	-9.83	53.83	259.48	.60
4600.00	1.09	338.09	4599.45	-7.41	-54.22	-7.41	54.72	262.22	.32
4800.00	1.14	314.81	4799.41	-4.24	-56.34	-4.24	56.50	265.70	.23
5000.00	.88	312.94	4999.38	-1.79	-58.87	-1.79	58.90	268.26	.13
5200.00	.80	313.31	5199.36	.21	-61.01	.21	61.01	270.20	.04
5400.00	.54	305.13	5399.35	1.71	-62.80	1.71	62.82	271.56	.14
5600.00	.60	104.67	5599.34	1.99	-62.56	1.99	62.59	271.82	.56

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
5800.00	.92	69.11	5799.32	2.30	-60.05	2.30	60.09	272.19	.28
6000.00	.47	285.37	5999.32	3.09	-59.34	3.09	59.42	272.98	.66
6200.00	.35	197.39	6199.31	2.72	-60.31	2.72	60.37	272.58	.29
6400.00	.48	80.09	6399.31	2.28	-59.67	2.28	59.71	272.19	.36
6600.00	.74	332.84	6599.30	3.58	-59.43	3.58	59.54	273.44	.50
6800.00	.51	52.70	6799.30	5.26	-59.31	5.26	59.55	275.07	.41
7000.00	.33	146.79	6999.29	5.32	-58.29	5.32	58.53	275.22	.31
Last Survey Depth Recorded									
7190.00	1.30	198.96	7189.27	2.83	-58.69	2.83	58.76	272.76	.59