

FORM
2A

Rev
08/13

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400708100

0

Date Received:

10/24/2014

Oil and Gas Location Assessment

New Location Refile Amend Existing Location Location#: _____

Submit signed original form. This Oil and Gas Location Assessment is to be submitted to the COGCC for approval prior to any ground disturbance activity associated with oil and gas operations. Approval of this Oil and Gas Location Assessment will allow for the construction of the below specified Location; however, it does not supersede any land use rules applied by the local land use authority. Please see the COGCC website at <http://cogcc.state.co.us/> for all accompanying information pertinent this Oil and Gas Location Assessment.

Location ID:

440510

Expiration Date:

12/19/2017

This location assessment is included as part of a permit application.

CONSULTATION

This location is included in a Comprehensive Drilling Plan. CDP # _____

This location is in a sensitive wildlife habitat area.

This location is in a wildlife restricted surface occupancy area.

This location includes a Rule 306.d.(1)A.ii. variance request.

Operator

Operator Number: 10110

Name: GREAT WESTERN OPERATING COMPANY LLC

Address: 1801 BROADWAY #500

City: DENVER State: CO Zip: 80202

Contact Information

Name: Callie Fiddes

Phone: (303) 398-0550

Fax: ()

email: regulatorypermitting@gwogco.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20090080

Gas Facility Surety ID: _____

Waste Management Surety ID: _____

LOCATION IDENTIFICATION

Name: BURR FD PAD

Number: 23-219HN

County: WELD

Quarter: SESE Section: 24 Township: 6N Range: 67W Meridian: 6 Ground Elevation: 4740

Define a single point as a location reference for the facility location. When the location is to be used as a well site then the point shall be a well location.

Footage at surface: 666 feet FSL from North or South section line

364 feet FEL from East or West section line

Latitude: 40.467243 Longitude: -104.833819

PDOP Reading: 1.2 Date of Measurement: 07/08/2014

Instrument Operator's Name: S. STEWART

DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE

Drilling Fluids Disposal Method: Commercial Disposal

Cutting Disposal: OFFSITE

Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted? No

Reuse Facility ID: _____ or Document Number: _____

Centralized E&P Waste Management Facility ID, if applicable: _____

SURFACE & MINERALS & RIGHT TO CONSTRUCT

Name: WILLIAM R. BURR

Phone: _____

Address: 5477 GULFSTAR COURT

Fax: _____

Address: _____

Email: _____

City: WINDSOR State: CO Zip: 80528

Surface Owner: Fee State Federal Indian

Check all that apply. The Surface Owner: is the mineral owner

is committed to an oil and Gas Lease

has signed the Oil and Gas Lease

is the applicant

The Mineral Owner beneath this Oil and Gas Location is: Fee State Federal Indian

The Minerals beneath this Oil and Gas Location will be developed from or produced to this Oil and Gas Location: Yes

The right to construct this Oil and Gas Location is granted by: Surface Use Agreement

Surface damage assurance if no agreement is in place: _____ Surface Surety ID: _____

Date of Rule 306 surface owner consultation 07/25/2014

CURRENT AND FUTURE LAND USE

Current Land Use (Check all that apply):

Crop Land: Irrigated Dry land Improved Pasture Hay Meadow CRP

Non-Crop Land: Rangeland Timber Recreational Other (describe): _____

Subdivided: Industrial Commercial Residential

Future Land Use (Check all that apply):

Crop Land: Irrigated Dry land Improved Pasture Hay Meadow CRP

Non-Crop Land: Rangeland Timber Recreational Other (describe): _____

Subdivided: Industrial Commercial Residential

CULTURAL DISTANCE INFORMATION

Provide the distance to the nearest cultural feature as measured from Wells or Production Facilities onsite.

	From WELL	From PRODUCTION FACILITY
Building:	379 Feet	585 Feet
Building Unit:	780 Feet	585 Feet
High Occupancy Building Unit:	3825 Feet	5280 Feet
Designated Outside Activity Area:	5280 Feet	5280 Feet
Public Road:	461 Feet	315 Feet
Above Ground Utility:	355 Feet	20 Feet
Railroad:	1352 Feet	1261 Feet
Property Line:	356 Feet	21 Feet

INSTRUCTIONS:

- All measurements shall be provided from center of nearest Well or edge of nearest Production Facility to nearest of each cultural feature as described in Rule 303.b.(3)A.
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.
- For measurement purposes only, Production Facilities should only include those items with an asterisk(*) on the Facilities Tab.

DESIGNATED SETBACK LOCATION INFORMATION

- Check all that apply. This location is within a:
- Buffer Zone
 - Exception Zone
 - Urban Mitigation Area

- Buffer Zone - as described in Rule 604.a.(2), within 1,000' of a Building Unit.
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: _____

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: 08/26/2014

FOR MULTI-WELL PADS AND PRODUCTION FACILITIES WITHIN DESIGNATED SETBACK LOCATIONS ONLY:

Check this box if this Oil and Gas Location has or will have Production Facilities that serve multiple wells (on or offsite) and the Production Facilities are proposed to be located less than 1,000 feet from a Building Unit. *(Pursuant to Rule 604.c.(2)E.i., the operator must evaluate alternative locations for the Production Facilities that are farther from the Building Unit, and determine whether those alternative locations were technically feasible and economically practicable for the same proposed development.)*

By checking this box, I certify that no alternative placements for the Production Facilities, farther from the nearest Building Unit, were available based on the analysis conducted pursuant to Rule 604.c.(2)E.i.

In the space below, explain rationale for siting the multi-well Production Facility(ies) that supports your Rule 604.c.(2)E.i determination. Attach documentation that supports your determination to this Form 2A.

Please see attached SUA Exhibit. Based on the land owners request this is the agreed upon location for Burr FD 23 Pad.

SOIL

List all soil map units that occur within the proposed location. attach the National Resource Conservation Service (NRCS) report showing the "Map Unit Description" report listing the soil typical vertical profile. This data is to be used when segregating topsoil.

The required information can be obtained from the NRCS web site at <http://soildatamart.nrcs.usda.org/> or from the COGCC web site GIS Online map page found at <http://colorado.gov/cogcc>. Instructions are provided within the COGCC web site help section.

NRCS Map Unit Name: AQUOLLS AND AQUEPTS FLOODED #4

NRCS Map Unit Name: KIM LOAM 1 TO 3 PERCENT SLOPES #32

NRCS Map Unit Name: _____

PLANT COMMUNITY:

Complete this section only if any portion of the disturbed area of the location's current land use is on non-crop land.

Are noxious weeds present: Yes No

Plant species from: NRCS or, field observation Date of observation: _____

List individual species: _____

Check all plant communities that exist in the disturbed area.

- Disturbed Grassland (Cactus, Yucca, Cheatgrass, Rye)
- Native Grassland (Bluestem, Grama, Wheatgrass, Buffalograss, Fescue, Oatgrass, Brome)
- Shrub Land (Mahogany, Oak, Sage, Serviceberry, Chokecherry)
- Plains Riparian (Cottonwood, Willow, Aspen, Maple, Poplar, Russian Olive, Tamarisk)
- Mountain Riparian (Cottonwood, Willow, Blue Spruce)
- Forest Land (Spruce, Fir, Ponderosa Pine, Lodgepole Pine, Juniper, Pinyon, Aspen)
- Wetlands Aquatic (Bullrush, Sedge, Cattail, Arrowhead)
- Alpine (above timberline)
- Other (describe): _____

WATER RESOURCES

Is this a sensitive area: No Yes

Distance to nearest

downgradient surface water feature: 261 Feet

water well: 964 Feet

Estimated depth to ground water at Oil and Gas Location 14 Feet

Basis for depth to groundwater and sensitive area determination:

Receipt: 9064880 Permit Number: 58623- -

Is the location in a riparian area: No Yes

Was an Army Corps of Engineers Section 404 permit filed No Yes If yes attach permit.

Is the location within a Rule 317B Surface Water Supply Area buffer No zone:

If the location is within a Rule 317B Surface Water Supply Area buffer have all public water supply systems within 15 miles been notified: _____

GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 318A

DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

RULE 502.b VARIANCE REQUEST

Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number _____

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

OPERATOR COMMENTS AND SUBMITTAL

Comments The manufacturer of the TLVST is Brewer Steel Company.
The size of the TLVST is 40,000 BBLs.
The anticipated time frame the TLVST will be onsite is three weeks.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.
Signed: _____ Date: 10/24/2014 Email: regulatorypermitting@gwogco.com

Print Name: Callie Fiddes Title: Regulatory Tech

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved:  Director of COGCC Date: 12/20/2014

Conditions Of Approval

All representations, stipulations and conditions of approval stated in this Form 2A for this location shall constitute representations, stipulations and conditions of approval for any and all subsequent operations on the location unless this Form 2A is modified by Sundry Notice, Form 4 or an Amended Form 2A.

COA Type

Description

	Operator shall provide notice to COGCC 48 hours prior to commencing construction of this Oil and Gas Location via Form 42.
--	--

Best Management Practices

No BMP/COA Type

Description

1	Planning	Where possible, GWOC shall provide for the development of multiple reservoirs by drilling on existing pads. GWOC strives to utilize multi-well pads wherever technically and economically practicable to minimize potential impacts to neighbors and the environment. Multi-well pads are not always feasible due to numerous possible issues including but not limited to; landowner requirements, topographic constraints, well bore reaches, setback requirements, etc.
2	Traffic control	GWOC works closely with all municipalities as appropriate to develop a mutually acceptable road traffic access plan addressing site specific traffic-related issues. These plans may address issues such as; routes, construction specification of access roads, maintenance, dust control, jake brake limits, traffic controls, enforcement, emergency response, etc. GWOC will work with municipalities, the County's Planning Department and/or Road Department to address complaints related to traffic or dust issues as appropriate. Dust control measures may include surface stabilization, or dust control with appropriate chemical or water applications.
3	General Housekeeping	All surface debris, trash, unusable scrap, or solid waste from the facility will be properly temporarily stored on location in a secure container and ultimately removed and disposed of in a legal manner.
4	General Housekeeping	Within ninety (90) days after a well is plugged and abandoned, the well site shall be cleared of all non-essential equipment, trash, and debris.

5	General Housekeeping	General housekeeping will consist of neat and orderly storage of materials and fluids. Wastes will be temporarily stored in sealed containers and regularly collected and disposed of at offsite, suitable facilities. If spills occur prompt cleanup is required to minimize any commingling of waste materials with storm water runoff. Routine maintenance will be limited to fueling and lubrication of equipment. Drip pans will be used during routine fueling and maintenance to contain spills or leaks. Any waste product from maintenance will be containerized and transported offsite for disposal or recycling. There will be no major equipment overhauls conducted onsite. Equipment will be transported offsite for major overhauls. Cleanup will consist of patrolling the roadways, access areas, and other work areas to pick up trash, scrap debris, other discarded materials, and any contaminated soil. These materials will be disposed of properly and promptly.
6	Storm Water/Erosion Control	Storm Water Management Plans (SWMP) Storm Water Management Plans (SWMP) are in place to address construction, drilling and operations associated with Oil and Gas development throughout the state of Colorado in accordance with Colorado Department of Public Health and Environment (CDPHE). Barriers will be constructed around the perimeter of the site prior to construction. Typically, GWOC utilizes a ditch and berm system of storm water control at its sites. BMP's used are determined just prior to construction by a third-party storm water contractor and may vary according to the location. Storm water controls will remain in place until the pad is stabilized or reaches final reclamation.
7	Material Handling and Spill Prevention	GWOC is utilizing a Closed Loop Drilling System on the subject facility. No open pit storage of water is foreseen for this facility. If open pit storage of fresh water is required, a Form 15 will be submitted and approved prior to use of such pit, and appropriate signage and escape provisions will be provided as required. Cuttings and drilling fluids will be removed from location and properly treated or disposed of according to applicable regulations.
8	Material Handling and Spill Prevention	As applicable, per COGCC Rule 805, GWOC will utilize all reasonable and cost-efficient best practices, including but not limited to those listed in Rule 805, to maximize resource recovery and mitigate releases to the environment. <ul style="list-style-type: none"> • Initial frac and drillout effluent is routed through a sand catcher/trap and a junk/sand tank to remove sand and well frac debris. • Once any hydrocarbons are detected but prior to encountering salable quality combustible gas or significant volumes of liquid hydrocarbons (condensate or oil) (greater than 10 barrels per day average) the effluent is routed through a high-pressure separator and closed-top tanks to minimize emissions to the environment. Hydrocarbon liquids, produced water, and sand are separated utilizing the high-pressure separator. • Any accumulation of liquid hydrocarbons on the surface of a tank, greater than a residual amount (maximum of 20 barrels) will be removed as soon as practicable but within a maximum of 24 hours in all cases. The quality (combustibility) of the gas is typically monitored directly at the high-pressure separator. When salable (combustible) quality gas is measured/detected the gas stream is immediately diverted to the sales pipeline or the well is shut in. • Venting or flaring of combustible gases is not performed except in rare 'upset' type situations for safety reasons. • The separated produced water and hydrocarbon liquids (condensate/oil) are directed to specific tanks for storage until being unloaded and hauled to disposal or sales as appropriate.
9	Material Handling and Spill Prevention	GWOC constructs and operates our facilities to meet state and API codes, as appropriate, including API RP 500 electrical classifications inside bermed areas. Any unused potentially flammable materials are moved a minimum distance of 25-feet from wellhead, tanks, and separator areas. In addition, GWOC implements a Hot Work Permit Program for employees and contractors doing any defined 'Hot Work' activities on GWOC locations.

10	Material Handling and Spill Prevention	<p>Spill Prevention Control and Countermeasures (SPCC) plans in place to address any possible spills associated with Oil and Gas operations throughout the state of Colorado in accordance with CFR 112.</p> <p>In accordance with COGCC Rule 1002.f.(2)A. & B., shall provide a designated storage area for dry bulk chemicals and miscellaneous fluids. The storage area shall be covered to prevent contact of precipitation with chemicals, shall be elevated above storm- or standing water, and shall provide sufficient containment to prevent release of spilled fluids or chemicals from impacting soil, surface water or groundwater and will prevent the co-mingling of spilled fluids or chemicals with other E & P Waste.</p>
11	Construction	<p>GWOC strives to utilize multi-well pads wherever technically and economically practicable to minimize potential impacts to neighbors and the environment. Multi-well pads are not always feasible due to numerous possible issues including but not limited to; landowner requirements, topographic constraints, well bore reaches, setback requirements, etc. This pad will be constructed in such a manner that noise mitigation may be installed and removed without disturbing the site or landscaping. The pad has all weather access roads to allow for operator and emergency response. This pad has been placed as far as possible from building units.</p>
12	Construction	<p>GWOC designs its new facilities to both avoid leaks or releases as well as to help detect them in a time-efficient manner to minimize potential impacts. Oil and produced water storage tanks are in secondary containment areas. A minimum containment capacity of 110% of the single largest storage vessel inside the containment is constructed around any storage area. Tanks and all visible pipelines and valves etc. are inspected informally on a daily basis by company lease operators. In addition, GWOC also conducts formal annual SPCC inspections, and formal site specific and random audits, by third-party consultants to inspect for general site conditions as well as condition of tanks, pipelines, and containment structures. In addition, our company lease operators and Production staff review production records, including volumes and pressures, looking for irregularities that may indicate a problem with a tank or pipeline. If an irregularity is detected that may indicate a potential release the suspect tank and/or pipeline(s) are removed from service, isolated, and either pressure tested or visibly inspected for indications of a potential leak.</p>
13	Construction	<p>A minimum containment capacity of 110% of the single largest storage vessel inside the containment will be constructed around any liquids storage area. For this location, steel containment with sealed liners will be utilized at all storage facilities on this location.</p> <p>Tanks and all visible pipelines and valves etc. will be inspected informally on a daily basis by company lease operators. In addition, GWOC also conducts formal annual SPCC inspections, and formal site specific and random audits, by third-party consultants to inspect for general site conditions as well as condition of tanks, pipelines, and containment structures.</p>
14	Construction	<p>A BOPE with a minimum pressure rating of 3,000 psi will be utilized. At a minimum it will consist of 2 ram preventers and 1 annular preventer. The blind rams will be positioned below the pipe rams. A backup system of pressure control will be onsite consisting of at a minimum 1,000 psi accumulator (backup pressure). Accumulator is tested to 1,000 psi. Operator may use fixed sized pipe rams matching the tubular size. The annular preventer will be pressure tested to 250 psi low and 2,000 psi high for 10 minutes each. The ram preventers will be tested to 250 psi low and 2,500 psi high for 10 minutes each. All remaining well control equipment will be tested to 250 psi low and 2,500 psi high for 10 minutes each. The pressure tests will be conducted when the equipment is first installed and every 30 days thereafter. Pipe rams and blind rams will be function tested before every well service operation. Annual BOP inspections and pressure tests will be performed by the service company and will be charted & retained for 1 year. Backup stabbing valves shall be used on operations that require reverse circulation. Valves will be pressure tested before each well service operation in low pressure and high pressure range. The GWOC onsite representative will be certified in Well Control Operations by a Well-Cap certified training service.</p>
15	Construction	<p>GWOC does not typically utilize pits in any of its operations. If a pit was to be used proper pit Level indicators would be installed to indicate pit levels and compliance with pit volume rules.</p>

16	Construction	Conventional drill stem tests will not be conducted on DJ Basin horizontal wells currently being executed or planned by GWOC. If plans change in the future a well specific drill stem testing plan will be prepared for that particular well. Note that GWOC may elect to use one of several available wireline deployed tools for the purpose of measuring downhole formation pressures and/or collecting downhole fluid samples from the target formation(s) of a particular well.
17	Construction	At a minimum GWOC installs appropriate fencing to restrict access by any unauthorized persons. This fencing may vary depending on site-specific situations. Fencing will be properly noted on facility layout diagrams for both drilling/completion and the production phases of operations.
18	Construction	Load line containment is a necessary part of a complete secondary containment system. All loadlines are capped or bullplugged or locked shut to reduce the likelihood of a release occurring. In addition, GWOC places all load line receivers/valves inside secondary containment areas or in a proper load line containment device or both.
19	Construction	All newly installed or replaced crude oil and condensate storage tanks shall be designed, constructed, and maintained in accordance with National Fire Protection Association (NFPA) Code 30 (2008 version). GWOC shall maintain written records verifying proper design, construction, and maintenance, and shall make these records available for inspection by the Director. Only the 2008 version of NFPA Code 30 applies to this rule.
20	Construction	All access roads are designed, constructed, and maintained such that heavy equipment, including emergency response vehicles, can readily access and exit the location. In addition, GWOC will implement manual mud mitigation measures (eg. tracking control rock aprons) at location exits onto paved roads as necessary and in conjunction with county requirements.
21	Noise mitigation	The subject Great Western Operating Company, L.L.C. (GWOC) location will operate in accordance with maximum permissible noise levels per COGCC Rule 604.c.(2)A. and 802, as applicable. GWOC will utilize reasonable and cost-effective best practices to endeavor to reduce noise levels below these limits in areas where occupied structures occur within a Designated Setback Zone. Where possible, drilling rig and completion equipment engine exhaust will be directed away from occupied buildings to assist with noise mitigation. No noise compliance issues are expected from the production area.
22	Odor mitigation	Where possible, drilling rig and completion equipment engine exhaust will be directed away from occupied buildings to assist in mitigating potential odors. Light sources will be directed downwards, and away from occupied structures where possible. While GWOC does not anticipate any mitigation measures will be necessary for odors, sealed tanks with pressure relief valves and emissions controls will be utilized for the production phase. Once the drilling and completion rigs leave the site, there will be no permanently installed lighting on site.
23	Drilling/Completion Operations	Guy line anchors left buried for future use shall be identified by a brightly colored marker at least 4-feet in height and within 1-foot to the east of the anchor.
24	Drilling/Completion Operations	GWOC shall identify the location of the P&A wellbore with a permanent monument as specified in Rule 319.a.(5). The operator shall also inscribe or imbed the well number and date of plugging upon the permanent monument. P&A wellbores shall be cutoff well below ground surface in agricultural areas to provide for landowners to safely farm the reclaimed well area.
25	Drilling/Completion Operations	Great Western Operating Company certifies that the MLVTs on this location will be designed and implemented consistent with the COGCC Policy on the use of MLVTs in the state of Colorado.

Total: 25 comment(s)

Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
2477483	HYDROLOGY MAP
2477484	CONST. LAYOUT DRAWINGS
2477485	LOCATION DRAWING
2477486	RULE 306.E. CERTIFICATION
2477487	CORRESPONDENCE
400708100	FORM 2A SUBMITTED
400708113	MULTI-WELL PLAN
400708157	ACCESS ROAD MAP
400708166	FACILITY LAYOUT DRAWING
400708180	LOCATION PICTURES
400708188	TOPO MAP
400708199	SURFACE AGRMT/SURETY
400708660	WASTE MANAGEMENT PLAN
400708663	NRCS MAP UNIT DESC
400708665	NRCS MAP UNIT DESC
400709106	SURFACE AGRMT/SURETY
400709112	SURFACE AGRMT/SURETY
400719448	OTHER

Total Attach: 18 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Final Review	Corrected cultural distances for the wells using the minimum distances for each cultural feature submitted on the APDs.	12/20/2014 1:31:15 PM
Permit	Final Review Completed. No LGD or public comment received.	12/19/2014 9:38:54 AM
Permit	Per operator distance to nearest Building unit changed to 780'. Permitting Review Completed.	12/19/2014 9:38:53 AM
OGLA	IN PROCESS - Operator provided a revised Location Drawing, revised the distance to the nearest High Occupancy Building Unit, and the 306.e. Certification. No Public Comments. OGLA task passed.	12/18/2014 9:54:59 AM
OGLA	Received additional MLVT info, revised distances to various Cultural Features and the nearest downgradient surface water feature, and a revised Hydrology Map. However, the Location Drawing still needs revisions and I provided clarification on what we define as a High Occupancy Building Unit. I also requested the Rule 306.e. Certification.	12/10/2014 9:52:48 AM
OGLA	ON HOLD - Requested additional MLVT info, revise distances to various Cultural features, revise distance to nearest downgradient surface water feature, revise Hydrology Map & Location Drawing. Due by 12/18/14.	11/18/2014 9:07:49 AM
Permit	ON HOLD: Requesting confirmation of the nearest Building Unit from a proposed well.	11/6/2014 1:45:41 PM
Permit	Passed completeness.	11/4/2014 8:04:37 AM
OGLA	Buffer Zone completeness check on resubmitted Form 2A, Pre-Application Certification addressed. The nearest Building Unit from a proposed well is 780' on Location Drawing - address this issue during OGLA review. Passed Buffer Zone Completeness review.	11/3/2014 11:43:26 AM
Permit	Sent to OGLA for re-review.	10/31/2014 10:56:53 AM
OGLA	Buffer Zone completeness check - missing 305.a Pre-Notification Certification Letter, 986' distance from nearest planned well to nearest Building Unit does not match distance on Location Drawing. Push to Draft	10/28/2014 4:42:02 PM
Permit	Returned to Draft: 1. Per issues raised by OGLA.	10/28/2014 9:19:44 AM
Permit	Within Buffer Zone, sent to OGLA for further review.	10/27/2014 7:48:04 AM

Total: 13 comment(s)