

Schlegel Jacob 1 05-123-07755 - Planned WBD (P&A)

12-1/4" Surface Hole

7-7/8" Prod Hole

Existing

KB: 4886'
GL: 4876'

8 5/8", 24# Sfc Csg Shoe @ 215'

TOC 368'
Stage Tool 622'

Fox Hills Marker @ 1187'
Csg leaks cmtd 1245'-1070' 6/29/2011

Cmt squeeze 50 sx 2035'-1982' 6/23/2011

Cmt squeeze 2522'-2186' 6/17/2011

Cmt squeeze 2770'-2616' 1/24/1993

Sussex Top @ 4350'

TOC 6650' CBL 6/15/2011

NB Top @ 6910'
CIBP 6940' 12/19/2014
Niobrara Perfs 6990'-7100'

Codell perfs 7230'-7243'

CIBP 7440' 12/4/1992
J sand perfs 7692'-7706'

4 1/2", 10.5# Prod Csg to 7834'
TD @ 7846' 2/25/1974

Planned

Welded Cap
Cement to surface

CIBP @ 80'

Cmt Plug : 140 sx 450' - 100'

4 1/2" csg cut off @ 350'

Cmt plug 50 sx 1300' - 550' ID

CICR @ 1300'
Csg leaks squeezed 50 sx 1646'-1330'

Cmt plug 75 sx 2870'-1900' ID

TOC ID 3990'

Top perfs 4150'
CICR 4180'
Suicide Squeeze 300 sx

Bottom perfs 4550'

Cmt plug 25sx 6940'-6550' ID

