





TIME_1900 - Time Marked every 60.00 (s)

Description: HGNS standard resolution porosities for Platform Express Format: Log (EMD 5in Triple Combo) Index Scale: 5 in per 100 ft Index Unit: ft
Index Type: Measured Depth Creation Date: 23-Nov-2013 12:58:02

Channel Processing Parameters				
Parameter	Description	Tool	Value	Unit
ABHM	Array Induction Borehole Correction Mode	AIT-H	Compute Standoff	
ACDE	Array Induction Casing Detection Enable	AIT-H	Yes	
BARI	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BHT	Bottom Hole Temperature	Borehole	145	degF
BS	Bit Size	WLSESSION	7.875	in
BSAL	Borehole Salinity	Borehole	0	ppm
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	315	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
DFD	Drilling Fluid Density	Borehole	9.1	lbm/gal
DFT	Drilling Fluid Type	Borehole	Water	
DFT_WATER	Drilling Fluid Water Type	Borehole	Fresh Water	
DHC	Density Hole Correction	HDRS-H	Bit Size	
FD	Fluid Density	Borehole	1	g/cm3
FSAL	Formation Salinity	Borehole	0	ppm
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
GRSE	Generalized Mud Resistivity Selection, from Measured or Computed Mud Resistivity	Borehole	AMF	
GTSE	Generalized Temperature Selection, from Measured or Computed Temperature	Borehole	CTEM	
HSCO	Hole Size Correction Option	HGNS-H	Yes	
MATR	Rock Matrix for Neutron Porosity Corrections	Borehole	Depth Zoned	
MDEN	Matrix Density for Density Porosity	Borehole	Depth Zoned	g/cm3
MFST	Mud Filtrate Sample Temperature	Borehole	70	degF
RMFS	Resistivity of Mud Filtrate Sample	Borehole	0.3	ohm.m
SOCO	Standoff Correction Option	HGNS-H	Yes	
SPDR	SP Drift Per Foot	AIT-H	0	mV/ft
TD	Total Measured Depth	Borehole	5525	ft

Depth Zone Parameters			
Parameter	Value	Start (ft)	Stop (ft)
MATR	LIMESTONE	0	5160
MATR	SANDSTONE	5160	5537.5
MDEN	2.71	0	5160
MDEN	2.65	5160	5537.5
All depth are actual.			

Tool Control Parameters				
Parameter	Description	Tool	Value	Unit
HMCA_BRD_TYPE	HMCA Board Type	HGNS-H	1	
HRGD_BRD_TYPE	HRGD Board Type	HDRS-H	WITH_HET	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	3600	ft/h