Author: Mark Van Der Kuyl
Email: mark@vanderkuyl.com
Phone: 07966 ...

Copyright: Mark Van Der Kuyl
Date: 2018-07-27
Rev: 1.0
Comments: Initial release

Disclaimer: This drawing is provided for information purposes only. It is not to be used for construction purposes. Whilst every effort has been made to ensure accuracy, no responsibility is taken for any errors or omissions in the information contained herein. Any reliance placed on the information is strictly at the user's own risk.

Concept

Flexible mooring with tethers for 7 MW floating wind turbine

Tidal and Large Power Energy Vessel

Work-in-Full PTE

Anchor
Mooring
Tethers






EKG Tracing
Lead II Rhythm
1 mV = 10 mm
25 mm/sec



Calibration Report

Database File: 13772.db
Dataset Pathname: pass1
Dataset Creation: Thu Nov 20 19:58:22 2014 by Log 0

Dual Induction Calibration Report

Serial-Model: 1011-PSI
Surface Cal Performed:

	Readings		References			Results	
Loop:	Air	Loop	Air	Loop		m	b
Deep	0.000	1.000	0.000	1.000	mmho/m	0.520	-28.000
Medium	0.000	1.000	0.000	1.000	mmho/m	0.460	-27.000

Compensated Density Calibration Report

Serial-Model: 998-PSI
Source / Verifier: /
Master Calibration Performed: Fri Nov 07 01:41:14 2014
Before Survey Verification Performed:
After Survey Verification Performed:

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.750	g/cc	7210.00	9816.00	cps
Aluminum	2.690	g/cc	1326.00	6231.00	cps

Spine Angle = 74.98 Density/Spine Ratio = 0.536

	Size		Reading
Small Ring	6.20	in	1.67
Large Ring	19.85	in	1.38

Compensated Neutron Calibration Report

Serial Number: 826
Tool Model: PSI

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.9000
Long Space	1.00	cps	1.00	cps	2.1000

Gamma Ray Calibration Report

Serial Number: 939
Tool Model: PSI
Performed: Fri Nov 07 01:41:26 2014

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.6300 GAPI/cps