

WELLBORE DIAGRAM

Surface Loc: 1397' FSL, 1632' FWL

Operator:	CCI Paradox Upstream, LLC
Well Name:	MD Fed 28-32-45-15
Lease Number:	C-60053
Location:	NE SW Sec 28-T45N-R15W
Field:	Wildcat
County:	San Miguel County, CO
API Number:	05-113-06210-00
Updated: 11/26/2014 Ashley Noonan	

Log Tops

Honaker Trail	7922'
HKTR HSST Base	9211'
Ismay	9932'

49 jts 9.625" 36# J-55 ST&C (csg @ 2135', cmt w/ 190 sxs)
G Neat Tail, 475 sxs G Neat Lead

EOT @ 9210' →
2 sacks cement
CIBP set @ 9175'
11/26/2014

RBP

Set @9241.71' on 12-13-06

CBP

Set @9370' on 12-05-06
Drilled out on 12-08-06

CIBP

Set @9440' on 11-28-06

CIBP

Set @9550' on 11-28-06

CIBP

Set @9600' on 10-19-06

KB 6886.0'

GL	6867.4'
----	---------

Well History

Spud Date	08-04-06
TD Reached	09-04-06
Rig Released	09-10-06

Tubing Detail

Depth:

KB	17.00
291 jts 4.7# N-80 EUE tbg	9156.99
1.87 F-Nipple	0.86
1 jt of 4.7# N-80 EUE tubing	31.40
1.81 F-Nipple	0.80
Ret. Head	3.20
EOT	9210'

Tubing Removed prior to MIT conducted 11/26/2014

Honaker Trail Perfs shot 12-05-06 (120 holes)

3-1/8", 4 spf, 120° phasing
Frac w/44,750 gal WF 120 60Q foam,
8,846 gal of WF 120 and 77,079# of 20/40 Jordan-Unimin sand.

Honaker Trail Perfs shot 11-07-06 (64 holes)

3-1/8", 4 spf, 120° phasing
Frac w/ 63,020 gal foamed Aquivi 20 and 36,520 gal of
Avuvi 20 = 50Q foam, 115,000# of 20/40 white proppant
sand, tail in w/20,000# of 20/40 SB Excel sand

Re-Frac w/ 30,750 gal WF 120 60Q foam, 8,973 gal of WF 120 and 86,000# of 20/40 Jordan-Unimin sand

Honaker Trail Perfs shot 10-19-06 (64 holes)

3-1/8", 4 spf, 120° phasing
Frac w/ 51,000 gal foamed Aquivis 20, 15,300 gal of
Aquivis20, 125,000# of 20/40 white Proppant sand,
Tail in w/1,000# white 20/40 sand.

ISMAY perfs shot 09-25-06, (112 holes)

3-1/8", 4 SPF, 120° phasing
Frac w/ SLF 40,000 gal WF 120 70Q foam,
9,557 gal of WF 120 and 100,000# of 20/40 Jordan-Unimin sand.

239 jts 5.5" 17# P-110 LT&C csg @ 10510'
cmt w/1700 sx G 50/50 Poz Lead

TD 10552

