Company	Petroleum Development Oman
Well	Saih Rawl 1
Field	Saih Rawl
County	Dhofar
State	Sultanate of Oman
Other Services	Dipmeter, Sonic, Gamma Ray
Permanent Datum	Ground Level
Log Measured From	Rotary Table
Drilling Measured From	Rotary Table
Elevation	0 m
Elevation	0 m
Elevation	0 m
Date	1-Jan-1900
Run Number	1
Depth Driller	2000 m
Depth Logger	2000 m
Bottom Logged Interval	2000 m
Top Logged Interval	0 m
Casing Driller	0 m @ 0 m
Casing Logger	0 m
Bit Size	0 in
Type Fluid in Hole	Water
Density	0 g/cm³
Viscosity	0 cp
Fluid Loss	0 cc
Source of Sample	Flowline
Rm @ Measured Temp	0 Ω.m @ 0 °C
Rmf @ Measured Temp	0 Ω.m @ 0 °C
Rmc @ Measured Temp	0 Ω.m @ 0 °C
Rm @ BHT	0 Ω.m @ 0 °C
Max Recorded Temp	0 °C
Equipment Number	0
Location	0
Recorded By	0
Witnessed By	0

THIS DATA IS PRELIMINARY AND SUBJECT TO CHANGE AFTER FURTHER EXAMINATION

Composite Log

Logged Interval 0 - 2000 m

Depth Corrections: 0 m

Reference Log: None

Depth Tie by using Phase Energy Services

Scale 1:1 and 1:5

Depth	Casing	Lithology	Description	Log Scale	Log Scale
			CASING 13 3/8	0.00 - 0.00	20 - 80
0.00	13 3/8				
0.00					
0.00					
0.00



Contractor: Schlumberger
Operator: Chevron
Well: Gorgon 2
Field: Gorgon
Location: Barrow Island, Western Australia
Date: 2009
Time: 00:00 to 24:00
Depth Reference: Rotary Table
Elevation: 0.0 m
Log Measured From: Rotary Table
Permanent Datum: Mean Sea Level
Elevation: 0.0 m
Drilling Measured From: Rotary Table
Elevation: 0.0 m
Max Logged Depth: 3,000 m
Casing Depth: 1,000 m
Bit Size: 12.25 in
Mud Type: Water Based Mud
Mud Density: 1.05 g/cm³
Mud Viscosity: 45 s
Mud Resistivity: 0.2 Ωm
Mud Resistivity Temperature: 25 °C
Max Temperature: 85 °C
Max Deviation: 2.5 °
Max Dogleg: 0.5 °/30m
Recorded By: Schlumberger
Witnessed By: Chevron

Segmented Cement Bond Log Calibration Report

Serial Number:	11206	
Tool Model:	RBT-C3	
Calibration Casing Diameter:	7.000	in
Calibration Depth:	435.128	ft

Master Calibration, performed Tue Dec 09 06:42:06 2014:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.003	0.903	1.000	62.165	67.913	0.820
CAL	0.013	0.995				
5'	-0.001	0.884	1.000	62.165	69.068	1.087
SUM						
S1	-0.006	0.950	0.000	100.000	104.584	0.655
S2	-0.006	0.970	0.000	100.000	102.378	0.657
S3	-0.010	1.024	0.000	100.000	96.675	0.985
S4	0.003	1.154	0.000	100.000	86.900	-0.241
S5	-0.002	1.173	0.000	100.000	85.056	0.190
S6	-0.005	1.013	0.000	100.000	98.217	0.479
S7	-0.006	0.865	0.000	100.000	114.846	0.679
S8	-0.008	0.889	0.000	100.000	111.515	0.899

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.013	0.995	1.000	0.000

Air Zero Calibration, performed Tue Nov 25 22:37:44 2014:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	11206			
Tool Model:	RBT-C3			
Performed:	Wed Jun 11 03:38:10 2014			
	Reference		Reading	
Low Reference:	0.00	degF	0.00	degF
High Reference:	1.00	degF	1.00	degF
Gain:	0.30			
Offset:	12.00			
Delta Spacing	1			