





















Drilling Fluid

Drilling Fluid Type: Water Based Mud
Sample From: Flowline
Sample Time: 10:00
Sample Point: Active Pit
Sample Depth: 1,000 m
Fluid Density (g/cm3): 1.03
Funnel Viscosity (s): 40
PV (cP): 10
YP (lb/100ft2): 15
Fluid Loss (ml/30min): 6.0
Filtrate Appearance: Clear
Filter Cake Thickness (API): 1
Filter Cake Thickness (HPHT):
Filter Cake Quality: Good
Solids (%vol): 6.0
Sand (%vol): Trace
Water (%vol): 94
Oil (%vol):
Solids Corrected Density (g/cm3):
Comments: Sample Taken at Start of Interval

Gas Ratios
Ethane/Methane (C2/C1): 0.000
Propane/Ethane (C3/C2): 0.000
Butane/Propane (C4/C3): 0.000
Pentane/Butane (C5/C4): 0.000
Wetness (%): 0.000
Balance (%): 0.000

Gas Data
Sample Type: Cuttings
Gas Trap Type: Poor Boy
Trap Depth (m): 1,000
Trap Temperature (°C): 50
Trap Pressure (kPa): 101.3
Vacuum Pressure (kPa): 0
Flow Rate (l/min): 1.5
Gas Detector: FID
Detector Gases: Hydrogen, Air
Column: Packed
Column Length (m): 2
Column Packing: Porapak Q
Column Temperature (°C): 80
Run Time (min): 10
Carrier Gas: Helium
Carrier Gas Flow (ml/min): 30
Comments: Gas Data Taken at Start of Interval

Gas Readings
Background Gas (units): 100
Connection Gas (units): 500
Trip Gas (units): 1,000
Max Gas (units): 2,000

Chromatograph Readings
Methane (ppm): 1,000
Ethane (ppm): 100
Propane (ppm): 50
Isobutane (ppm): 10
Butane (ppm): 20
Isopentane (ppm): 5
Pentane (ppm): 10
Hexanes Plus (ppm): 15

Lithology
Primary Lithology: Sandstone
Secondary Lithology: Shale
Tertiary Lithology: Limestone
Lithology Description: Sandstone: light gray, fine grained, well sorted, subangular, quartz, calcareous cement. Shale: dark gray, soft, fissile, carbonaceous. Limestone: white, microcrystalline, chalky.
Porosity: Fair
Permeability: Fair
Hydrocarbon Shows: Trace oil stain in sandstone
Fluorescence: Dull yellow
Cut: Slow streaming
Residual Cut: Faint
Comments: Lithology Taken at Start of Interval

Cuttings Description
Cuttings Description: Sandstone: light gray, fine grained, well sorted, subangular, quartz, calcareous cement. Shale: dark gray, soft, fissile, carbonaceous. Limestone: white, microcrystalline, chalky.
Cuttings Color: Light gray, dark gray, white
Cuttings Size: Fine
Cuttings Shape: Subangular
Cuttings Sorting: Well sorted
Cuttings Roundness: Subangular
Cuttings Composition: Quartz, calcite, clay minerals
Cuttings Cement: Calcareous
Cuttings Matrix: Clay
Cuttings Porosity: Fair
Cuttings Permeability: Fair
Cuttings Hydrocarbon Shows: Trace oil stain
Cuttings Fluorescence: Dull yellow
Cuttings Cut: Slow streaming
Cuttings Residual Cut: Faint
Comments: Cuttings Description Taken at Start of Interval

Core Description
Core Description: Sandstone: light gray, fine grained, well sorted, subangular, quartz, calcareous cement. Shale: dark gray, soft, fissile, carbonaceous. Limestone: white, microcrystalline, chalky.
Core Color: Light gray, dark gray, white
Core Size: Fine
Core Shape: Subangular
Core Sorting: Well sorted
Core Roundness: Subangular
Core Composition: Quartz, calcite, clay minerals
Core Cement: Calcareous
Core Matrix: Clay
Core Porosity: Fair
Core Permeability: Fair
Core Hydrocarbon Shows: Trace oil stain
Core Fluorescence: Dull yellow
Core Cut: Slow streaming
Core Residual Cut: Faint
Comments: Core Description Taken at Start of Interval

Core Analysis
Core Porosity: 10
Core Permeability: 100
Core Grain Density: 2.65
Core Saturation: 50
Core Analysis Comments: Core Analysis Taken at Start of Interval

Core Photos
Core Photo Description: Core Photo Taken at Start of Interval

Core Photo

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.013	0.989	1.000	0.000

Air Zero Calibration, performed Tue Nov 25 22:37:44 2014:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number: 11206
Tool Model: RBT-C3
Performed: Mon Dec 15 05:21:22 2014

	Reference		Reading	
Low Reference:	0.00	degF	0.00	degF
High Reference:	1.00	degF	1.00	degF

Gain: 0.30
Offset: 12.00
Delta Spacing 1