

WELLBORE DIAGRAM

Surface Loc: 690' FSL, 1862' FEL

Operator:	EnCana Oil & Gas (USA) Inc.
Well Name:	Hamilton Creek 36-43
Lease Number:	
Location:	SWSE Sec 36-T45N-R15W
Field:	Hamilton Creek
County:	San Miguel County, CO
API Number:	05-113-06153
Diagram Date:	5/5/2005, Rev: 1/17/08, Rev. 04/17/15

KB 6891

GL 6869

Well History

Spud Date	10/16/2004
TD Reached	11/6/2004
Rig Released	11/7/2004
Completion Date	3/9/2005
First Sales:	2/11/2005

37 jts 9.5/8" 36# J-55 LT&C
csg @ 1657'; cmt w/ 453 sx lead)
150 sx tail

Top of Cutler 1891'

TOC @ 1800'

Plunger equipment set 7/17/07

Tubing Detail (12/06/2007):

KB
268 jts 2-7/8" 6.5# N-80 tbg
2.25 F-nipple
1 jt 2-7/8" J-55 tbg
2.25 F-nipple
Pup Joint
Re-Entry Guide
EOT

Depth:

20.00
7961.83
0.97
31.33
0.97
4.12
0.65
8014'

Top of Hermosa 6241'

2-7/8" tubing set @ 8014'

10/05/2011: TD 8055' (Sand/fill
above RBP)

RBP @ 8150'

7142-7146
7174-7176
7188-7190
7211-7213
7298-7300
7308-7310
7318-7320

Hermosa Perfs shot 2/23/05 (64 holes)
3-3/8", 4 SPF, 90° phasing
Frac w/217,080# sand, N2 foam frac

7698-7702
7716-7718
7734-7736

Hermosa Perfs shot 2/15/05 (32 holes)
3-3/8", 4 SPF, 90° phasing

8034-8036
8038-8040
8054-8056

Hermosa Perfs shot 1/30/05 (24 holes)
3-3/8", 4 SPF, 90° phasing

8200-8202
8216-8218
8334-8336
8340-8342
8374-8376

Hermosa Perfs shot 1/17/05 (40 holes)
3-3/8", 4 SPF, 90° phasing
Frac w/95,900# sand and slickwater

8453-8455
8475-8477
8551-8553
8586-8588

Hermosa Perfs shot 1/3/05 (32 holes)
3-3/8", 4 SPF, 90° phasing
Frac w/101/480# sand, 10 ppg brine

8728-8731
8772-8774

Hermosa Perfs shot 12/16/04 (20 holes)
3-3/8", 4 SPF, 90° phasing
Frac w/66,301# sand, 10 ppg brine

PBTD 8823'

TD 8884'

190 jts 5.5" 17# P-110 LT&C csg @ 8839'
Cmt w/ 1398 sx G 50/50 Poz (8-3/4" hole)