
Schlumberger
Array Induction Imager Tool
Gamma Ray
Bit Size
Caliper
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Depth
Tension
Cable Speed
Mud Type
Mud Density
Mud Resistivity
Mud Filtrate Resistivity
Mud Cake Resistivity
Source of Sample
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Maximum Recorded Temperature
Circulation Stopped Time
Logger on Bottom Time
Unit Number
Location
Recorded By
Witnessed By
Run Number
Service Order
Permanent Datum
Elevation
Log Measured From
Drilling Measured From
Elevation of Kelly Bushing
Elevation of Derrick Floor
Elevation of Ground Level
Total Depth - Driller
Total Depth - Logger
Bottom Logged Interval
Top Logged Interval
Casing - Driller
Casing - Logger
Bit Size
Type Fluid in Hole
Density
Viscosity
pH
Fluid Loss





Calibration Report

Database File: cbl encana grant brothers c unit 1.db
Dataset Pathname: pass3
Dataset Creation: Wed Dec 10 14:24:41 2014 by Log SCH 120430

Gamma Ray Calibration Report

Type / Serial: Probe275dig / 110785

SHOP CALIBRATION — Fri Nov 08 09:38:30 2013

	Counts/Sec.	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.4400			GAPI/cps

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

Cement Bond Log Calibration Report

Serial Number:	110802		
Tool Model:	Probe275Digital		
Performed:	Wed Dec 10 14:15:14 2014		
Depth:	5789.68	ft	
Casing Diameter:	4.5	in	

	3' Spacing	5' Spacing	
Signal Zero:	0.7	0	mV
Calibrated Amplitude:	81.1961	81.1961	mV
Reading at Signal Zero:	-0.00581055	-0.00524902	V
Reading in Free Pipe:	2.49878	2.37864	V
Gain:	32.1394	34.0604	
Offset:	0.886748	0.178784	