



# Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18<sup>th</sup> Street  
Denver, CO 80202  
720-929-6000

April 28, 2015

Matt Lepore  
Director, Colorado Oil and Gas Conservation Commission  
Department of Natural Resources  
The Chancery Building  
1120 Lincoln Street, Suite 801  
Denver, CO 80203

Re: Request for Exception to Rule 317.p  
TEDFORD 29C-28HZ Location  
TEDFORD 28N-28HZ (COGCC DOC# 400804489) TEDFORD 3C-28HZ (COGCC DOC# 400804487)  
TEDFORD 3N-28HZ (COGCC DOC# 400804145) TEDFORD 29N-28HZ (COGCC DOC# 400804481)  
TEDFORD 29C-28HZ (COGCC DOC# 400804300) TEDFORD 4N-28HZ (COGCC DOC# 400804199)  
TEDFORD 30C-28HZ (COGCC DOC# 400804483) TEDFORD 30N-28HZ (COGCC DOC# 400804485)  
Township 2 North, Range 66 West  
Section 28: SW/4 SW/4  
Weld County, Colorado  
Township 2 North, Range 66 West  
Section 28: SE/4 SW/4  
Weld County, Colorado

Dear Director Lepore:

Kerr-McGee Oil & Gas Onshore LP (“KMG”) respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A Cement Bond Log with cased-hole gamma-ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well requirements and have a surface location within seven hundred fifty (750) feet of the proposed well(s).

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma-ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred and fifty feet (750) with acceptable resistivity logs with gamma ray are listed in the table below:

<b>Well Name</b>	<b>Well Number</b>	<b>API Number</b>	<b>Distance From Well(s)</b>	<b>Azimuth (Degrees)</b>	<b>COGCC Well File Document Number</b>
FEHRN	4-28	05-123-15557	628	60	575612, 979201, 979200

Should you have any questions, please contact our office. Thank you for your consideration.

Very truly yours,

Kerr-McGee Oil & Gas Onshore LP



Craig Richardson  
Regulatory Analyst II