

WELLBORE DIAGRAM

Surface Loc: 690' FNL, 672' FEL

Operator:	EnCana Oil & Gas (USA) Inc.
Well Name:	HC Bray 25-24-45-15
Location:	NENE Sec 25-45N-15W
Field:	Hamilton Creek
County:	San Miguel, CO
API Number:	05-113-06208
Diagram Date:	6/29/2006
	Rev 6/11/08
	Rev 4/28/2015

KB	6603
GL	6585

Well History

Spud Date	3/9/2006
TD Reached	3/29/2006
Rig Released	3/31/2006
Completion Date	5/8/2006
First Sales:	4/29/2006

TOC @ 1962'

Tubing Detail as of 2/08/2008:

	Depth:
KB	16.00
262 jts 2-7/8" 6.5# N-80 new tbg	8491.60
2.31 F-Nipple	0.95
1 jt 2-7/8" tbg	32.45
2.25 F-Nipple	0.95
Pup Jt.	4.24
Wireline Guide	0.65
EOT	8546.84

EOT @ 8547'

PBTD 9314'

9415'

8353-8363	Honaker Trail Perfs shot 4/26/06 (70 holes)
8380-8390	3-1/8", 2 SPF, 120° phasing
8410-8415	Frac w/78250 gal WF 120 70Q foam and 7980 gal WF 120,
8420-8430	150,700# 20/40 sand
8510-8520	Honaker Trail Perfs shot 4/19/06 (50 holes)
8525-8540	3-1/8", 2 SPF, 120° phasing
	Frac w/74,000 gal of wf 120 70Q foam and 8309 gal WF 120,
	136,025# 20/40 Jordan-Unimin sand
8820-8824	Hovenweep Perfs shot 4/12/06 (56 holes)
8831-8847	3-1/8", 2 SPF, 120° phasing
8859-8867	Frac w/72,000 gal WF 120 70Q foam and 8612 gal WF 120,
	115,000 # 20/40 sand, 20,000# 20/40 Opti Prop
9161-9173	Hovenweep Perfs shot 4/6/06 (48 holes)
9183-9195	3-1/8", 2 SPF, 120° phasing
	Frac w/84.000 gal WF 120 70Q foam and 8863 gal WF 120,
	119,000# of 20/40 sand, 20,000# 20/40 OptiProp

201 jts 5.5" 17# CP-110 LT&C csg @ 9410'
Cmt w/ 1955 sx 13# 1.43 yld cmt