

FORM
6Rev
12/05State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Document Number:

400825548

Date Received:

04/15/2015

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 47120

Contact Name: Cheryl Light

Name of Operator: KERR MCGEE OIL & GAS ONSHORE LP

Phone: (720) 929-6461

Address: P O BOX 173779

Fax: (720) 929-7461

City: DENVER State: CO Zip: 80217-

Email: cheryl.light@anadarko.com

For "Intent" 24 hour notice required,

Name: Carlile, Craig

Tel: (970) 629-8279

COGCC contact:

Email: craig.carlile@state.co.us

API Number 05-123-16088-00

Well Name: HSR-DAVENPORT

Well Number: 15-16

Location: QtrQtr: SWSE Section: 16 Township: 3N Range: 67W Meridian: 6

County: WELD

Federal, Indian or State Lease Number:

Field Name: WATTENBERG

Field Number: 90750

☒ Notice of Intent to Abandon☐ Subsequent Report of Abandonment

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.220860

Longitude: -104.893800

GPS Data:

Date of Measurement: 01/06/2007

PDOP Reading: 1.8

GPS Instrument Operator's Name: Steve Fisher

Reason for Abandonment: ☐ Dry☒ Production for Sub-economic☐ Mechanical Problems☐ OtherCasing to be pulled: ☒ Yes☐ No

Estimated Depth: 850

Fish in Hole: ☐ Yes☒ No

If yes, explain details below

Wellbore has Uncemented Casing leaks: ☐ Yes☒ No

If yes, explain details below

Details:

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
CODELL	7049	7070			
NIOBRARA	6797	6941			
SHANNON	4508	4528	11/10/1993	SQUEEZED	

Total: 3 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF	12+1/4	8+5/8	24	574	400	574	0	VISU
1ST	7+7/8	4+1/2	11.6	7,198	401	7,198	3,730	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 6730 with 25 sacks cmt on top. CIPB #2: Depth 80 with 25 sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIPB #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 25 sks cmt from 6730 ft. to 6330 ft. Plug Type: CASING Plug Tagged: ☐
Set 70 sks cmt from 4650 ft. to 3750 ft. Plug Type: CASING Plug Tagged: ☒
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 170 sacks half in. half out surface casing from 950 ft. to 474 ft. Plug Tagged: ☒

Set 25 sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☒ No

Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. of _____ inch casing Plugging Date: _____

*Wireline Contractor: _____ *Cementing Contractor: _____

Type of Cement and Additives Used: _____

Flowline/Pipeline has been abandoned per Rule 1103 ☐ Yes ☐ No *ATTACH JOB SUMMARY

Technical Detail/Comments:

5. MIRU, kill as necessary using biocide treated water. NDWH. NUBOP. Unseat landing jt, LD.

6. Notify cementers to be on call. Provide volumes listed below:

6.1 Niobrara plug: 25 sx (35 cu-ft) "G" w/ 20% silica flour, 0.4% CD-32, 0.4 ASA-301 and R-3 to achieve 2:30 pump time, mixed at 15.8 ppg and 1.38 cu-ft/sk yield. Cement volume based on 400' in 4 1/2" casing.

6.2 Sussex plug: 70 sx (81 cu-ft) "G" w/ 0.4% CD-32, 0.4% ASA-301, mixed at 15.8 ppg and 1.15 cu-ft/sk yield. Cement volume based on 900' in 4 1/2" casing.

6.3 Foxhills plug: 170 sx (226 cu-ft) Type III w/cello flake and CaCl2 as necessary, mixed at 14.8 ppg and 1.33 cu-ft/sk yield. Cement volume based on 100' in 4 1/2" casing, 276' in a 9" OH with 20% excess, and 200' in 8 5/8" casing. Caliper on file.

7. TOOH 2 3/8" tubing landed at 7031'. Stand back 2 3/8" tubing.

8. MIRU WL. RIH gauge ring for 4 1/2" 11.6# casing to 6750'. POOH.

9. PU 4 1/2" 11.6# CIBP and RIH w/ WL. Set at +/- 6730' to abandon Niobrara and Codell perms. PT to 1000 psi for 15 minutes. RDMO WL.

10. RIH with 2 3/8" tubing to +/- 6730', tag CIBP and PUH 5'. Hydrotest tubing to 3000 psi while RIH.

11. RU cementers. Pump Niobrara plug: 25 sx (35 cu-ft) "G" w/ 20% silica flour, 0.4% CD-32, 0.4 ASA-301 and R-3 to achieve 2:30 pump time, mixed at 15.8 ppg and 1.38 cu-ft/sk yield. Plug to cover 6330' – 6730'.

12. PUH to +/- 6100'. Reverse circulate with biocide treated water to displace cement and clear tubing.

13. PUH to +/- 4650'.

14. RU cementers. Pump Sussex plug: 70 sx (81 cu-ft) "G" w/ 0.4% CD-32, 0.4% ASA-301, mixed at 15.8 ppg and 1.15 cu-ft/sk yield. Plug to cover 3750' – 4650'.

15. PUH to +/- 3500'. Reverse circulate with biocide treated water to displace cement and clear tubing. TOC – 3730'

16. WOC per cement company recommendation. Tag cement at or above 3750'. If not, consult with Evans Engineering.

17. POOH. Stand back 950' of tubing.

18. RU WL. Shoot off 4 1/2" casing at or below 850'. RD WL. Circulate casing with biocide treated water to remove any gas.

19. NDBOP, NDTTH.

20. Install BOP on casing head with 4 1/2" pipe rams.

21. TOOH 4 1/2" casing, LD.

22. RIH with 2 3/8" tubing to 950' inside 4 1/2" casing.

23. RU cementers. Establish circulation with biocide treated water and precede cement with 10 bbl SAPP and a minimum 20 bbl fresh water spacer. Pump Foxhills plug: 170 sx (226 cu-ft) Type III w/ cello flake and CaCl2 as necessary, mixed at 14.8 ppg and 1.33 cu-ft/sk yield. Plug to cover 950' – 850' in 4 1/2" casing, 850' – 574' in 9" OH with 20% excess, and 574' – 374' in 8 5/8" casing. Caliper readings across entire interval. RD cementers.

24. PUH to 100' and circulate with biocide treated water to displace cement and clear tubing.

25. WOC per cement company recommendation. Tag cement at or above 474'. If not, consult with Evans Engineering.

26. RU WL. RIH 8 5/8" 24# CIBP to 80'. Set and pressure test to 1000 psi for 15 minutes. If tests, RDMO WL and WO rig.

27. Instruct cementing and wireline contractors to email copies of all job logs/jobs summaries to rscDJVendors@anadarko.com within 24 hours of completion of the job.

28. Supervisor is to submit paper copies of all invoices, logs, and reports to Evans Engineering Specialist.

29. Excavation crew to notify One Call to clear excavation area around wellhead and for flowlines.

30. Excavate hole around surface casing enough to allow welder to cut casing minimum 5' below ground level.

31. Welder cut casing minimum 5' below ground level.

32. Fill casing to surface using 4500 psi compressive strength cement, (NO gravel).

33. Spot weld on steel marker plate. Marker should contain Well name, Well number, legal location (1/4 1/4 descriptor) and API number.

34. Obtain GPS location data as per COGCC Rule 215 and send to rscDJVendors

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Cheryl Light
 Title: Sr. Regulatory Analyst Date: 4/15/2015 Email: cheryl.light@anadarko.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: SCHLAGENHAUF, MARK Date: 5/26/2015

CONDITIONS OF APPROVAL, IF ANY: _____ Expiration Date: 11/25/2015

COA Type	Description
	1) Submit Form 42 electronically to COGCC 48 hours prior to MIRU. 2) If unable to pull casing contact COGCC for plugging modifications. 3) For 950' plug: pump plug and displace, shut-in, WOC 4 hours and tag plug – must be 524' or shallower. 4) Properly abandon flowlines as per Rule 1103. File electronic Form 42 once abandonment complete. 5) Please submit existing gyro survey data with Form 6 (s) Subsequent Report of Abandonment.

Attachment Check List

Att Doc Num**Name**

400825548	FORM 6 INTENT SUBMITTED
400825560	PROPOSED PLUGGING PROCEDURE
400825561	WELLBORE DIAGRAM

Total Attach: 3 Files

General Comments

User Group**Comment****Comment Date**

Permit	Well Completion Report dated 12/08/1992 & 1/10/1994.	4/16/2015 9:34:29 AM
--------	--	-------------------------

Total: 1 comment(s)