

# Mixon Harold R GU 1 05-123-08086 - Planned WBD (P&A)

12-1/4" Surface Hole

7-7/8" Prod Hole

## Existing

KB: 4940'

GL: 4930'

8 5/8", 24# Sfc Csg set @ 214'

TOC 246'

DV tool@ 703' cmt'd w/200 sx

Fox Hills Marker 1248'

Sussex Top @ 4559'

TOC 5780'

Squeeze perfs 6226'  
cmt'd w/150sx 8/3/1974

Casing leak @ 6366'  
cmt'd w/150sx 8/2/1974

BOC 6458'

Niobrara Top @ 7228'

TOC 7230'

J sand Perfs 7958'-7996'

4 1/2" 10.5, 11.6# Prod Csg @ 8110'  
TD @ 8110' 7/12/1974

## Actual

Welded Cap

Cement to surface

CIBP @ 80'

Cut 4 1/2 csg @ 235'

60 sk plug 346'-100'; TOC=100'

40 sk cmt plug 745'-450'; TOC=450'

Top perf 740'; TOC=745'

Bottom perf 1350'

TOC ID 4192'

Top Perf 4350'

Bottom Perf 4758'

TOC 6120' ID

Top Perfs 6800'

Bottom Perfs 7200'

CIBP w/ 2 sx cement cap @ 7900'

