

Whiting Petroleum Corp.

Weld County, CO

Sec 7-T10N-R57W

Horsetail #07F-1806B

Hz

Plan: Design #1

Standard Planning Report

29 January, 2015





Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Design #1		

Project	Weld County, CO		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		

Site		Sec 7-T10N-R57W			
Site Position:		Northing:	1,558,450.14 usft	Latitude:	40° 51' 14.300 N
From:	Lat/Long	Easting:	3,469,810.15 usft	Longitude:	103° 48' 5.960 W
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	1.10 °

Well	Horsetail #07F-1806B					
Well Position	+N/-S	-82.92 usft	Northing:	1,558,396.92 usft	Latitude:	40° 51' 13.480 N
	+E/-W	1,549.99 usft	Easting:	3,471,361.44 usft	Longitude:	103° 47' 45.790 W
Position Uncertainty		0.00 usft	Wellhead Elevation:		Ground Level:	4,925.70 usft

Wellbore	Hz				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	1/5/2015	7.88	67.44	53,087

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	182.29

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00	
550.00	5.00	310.00	549.68	7.01	-8.35	2.00	2.00	0.00	310.00	
5,010.00	5.00	310.00	4,992.71	256.87	-306.12	0.00	0.00	0.00	0.00	
5,260.00	0.00	0.00	5,242.39	263.88	-314.47	2.00	-2.00	0.00	180.00	
5,333.74	0.00	0.00	5,316.13	263.88	-314.47	0.00	0.00	0.00	0.00	
6,151.92	90.00	180.02	5,837.00	-256.99	-314.70	11.00	11.00	0.00	180.02	PBHL 1806B
13,860.86	90.00	180.02	5,837.00	-7,965.94	-318.00	0.00	0.00	0.00	0.00	PBHL 1806B



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	H2		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
Build 2°/100'									
400.00	2.00	310.00	399.98	1.12	-1.34	-1.07	2.00	2.00	0.00
500.00	4.00	310.00	499.84	4.49	-5.35	-4.27	2.00	2.00	0.00
550.00	5.00	310.00	549.68	7.01	-8.35	-6.67	2.00	2.00	0.00
Hold 5° Inc									
600.00	5.00	310.00	599.49	9.81	-11.69	-9.33	0.00	0.00	0.00
700.00	5.00	310.00	699.11	15.41	-18.37	-14.67	0.00	0.00	0.00
800.00	5.00	310.00	798.73	21.01	-25.04	-20.00	0.00	0.00	0.00
900.00	5.00	310.00	898.35	26.62	-31.72	-25.33	0.00	0.00	0.00
1,000.00	5.00	310.00	997.97	32.22	-38.40	-30.66	0.00	0.00	0.00
1,100.00	5.00	310.00	1,097.59	37.82	-45.07	-35.99	0.00	0.00	0.00
1,200.00	5.00	310.00	1,197.21	43.42	-51.75	-41.32	0.00	0.00	0.00
1,300.00	5.00	310.00	1,296.83	49.02	-58.42	-46.65	0.00	0.00	0.00
1,400.00	5.00	310.00	1,396.45	54.63	-65.10	-51.99	0.00	0.00	0.00
1,500.00	5.00	310.00	1,496.07	60.23	-71.78	-57.32	0.00	0.00	0.00
1,554.14	5.00	310.00	1,550.00	63.26	-75.39	-60.20	0.00	0.00	0.00
Upper Pierre									
1,600.00	5.00	310.00	1,595.69	65.83	-78.45	-62.65	0.00	0.00	0.00
1,700.00	5.00	310.00	1,695.31	71.43	-85.13	-67.98	0.00	0.00	0.00
1,800.00	5.00	310.00	1,794.93	77.04	-91.81	-73.31	0.00	0.00	0.00
1,900.00	5.00	310.00	1,894.55	82.64	-98.48	-78.64	0.00	0.00	0.00
2,000.00	5.00	310.00	1,994.17	88.24	-105.16	-83.98	0.00	0.00	0.00
2,100.00	5.00	310.00	2,093.78	93.84	-111.84	-89.31	0.00	0.00	0.00
2,200.00	5.00	310.00	2,193.40	99.44	-118.51	-94.64	0.00	0.00	0.00
2,300.00	5.00	310.00	2,293.02	105.05	-125.19	-99.97	0.00	0.00	0.00
2,400.00	5.00	310.00	2,392.64	110.65	-131.87	-105.30	0.00	0.00	0.00
2,500.00	5.00	310.00	2,492.26	116.25	-138.54	-110.63	0.00	0.00	0.00
2,600.00	5.00	310.00	2,591.88	121.85	-145.22	-115.96	0.00	0.00	0.00
2,700.00	5.00	310.00	2,691.50	127.46	-151.90	-121.30	0.00	0.00	0.00
2,800.00	5.00	310.00	2,791.12	133.06	-158.57	-126.63	0.00	0.00	0.00
2,900.00	5.00	310.00	2,890.74	138.66	-165.25	-131.96	0.00	0.00	0.00
3,000.00	5.00	310.00	2,990.36	144.26	-171.93	-137.29	0.00	0.00	0.00
3,100.00	5.00	310.00	3,089.98	149.87	-178.60	-142.62	0.00	0.00	0.00
3,200.00	5.00	310.00	3,189.60	155.47	-185.28	-147.95	0.00	0.00	0.00
3,300.00	5.00	310.00	3,289.22	161.07	-191.96	-153.28	0.00	0.00	0.00
3,400.00	5.00	310.00	3,388.84	166.67	-198.63	-158.62	0.00	0.00	0.00
3,500.00	5.00	310.00	3,488.46	172.27	-205.31	-163.95	0.00	0.00	0.00
3,511.59	5.00	310.00	3,500.00	172.92	-206.08	-164.57	0.00	0.00	0.00
Hygiene									
3,600.00	5.00	310.00	3,588.08	177.88	-211.98	-169.28	0.00	0.00	0.00
3,662.16	5.00	310.00	3,650.00	181.36	-216.13	-172.59	0.00	0.00	0.00
Lower Pierre									
3,700.00	5.00	310.00	3,687.70	183.48	-218.66	-174.61	0.00	0.00	0.00
3,800.00	5.00	310.00	3,787.32	189.08	-225.34	-179.94	0.00	0.00	0.00
3,900.00	5.00	310.00	3,886.94	194.68	-232.01	-185.27	0.00	0.00	0.00
4,000.00	5.00	310.00	3,986.55	200.29	-238.69	-190.61	0.00	0.00	0.00
4,100.00	5.00	310.00	4,086.17	205.89	-245.37	-195.94	0.00	0.00	0.00
4,200.00	5.00	310.00	4,185.79	211.49	-252.04	-201.27	0.00	0.00	0.00
4,300.00	5.00	310.00	4,285.41	217.09	-258.72	-206.60	0.00	0.00	0.00
4,400.00	5.00	310.00	4,385.03	222.69	-265.40	-211.93	0.00	0.00	0.00



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,500.00	5.00	310.00	4,484.65	228.30	-272.07	-217.26	0.00	0.00	0.00
4,600.00	5.00	310.00	4,584.27	233.90	-278.75	-222.59	0.00	0.00	0.00
4,700.00	5.00	310.00	4,683.89	239.50	-285.43	-227.93	0.00	0.00	0.00
4,800.00	5.00	310.00	4,783.51	245.10	-292.10	-233.26	0.00	0.00	0.00
4,900.00	5.00	310.00	4,883.13	250.71	-298.78	-238.59	0.00	0.00	0.00
5,010.00	5.00	310.00	4,992.71	256.87	-306.12	-244.45	0.00	0.00	0.00
Drop 2°/100'									
5,100.00	3.20	310.00	5,082.48	261.00	-311.05	-248.39	2.00	-2.00	0.00
5,200.00	1.20	310.00	5,182.40	263.47	-313.99	-250.74	2.00	-2.00	0.00
5,260.00	0.00	0.00	5,242.39	263.88	-314.47	-251.12	2.00	-2.00	0.00
Hold Vertical									
5,300.00	0.00	0.00	5,282.39	263.88	-314.47	-251.12	0.00	0.00	0.00
5,333.74	0.00	0.00	5,316.13	263.88	-314.47	-251.12	0.00	0.00	0.00
KOP, Build 11°/100'									
5,350.00	1.79	180.02	5,332.39	263.62	-314.47	-250.87	11.00	11.00	0.00
5,400.00	7.29	180.02	5,382.22	259.67	-314.48	-246.92	11.00	11.00	0.00
5,450.00	12.79	180.02	5,431.43	250.95	-314.48	-238.21	11.00	11.00	0.00
5,500.00	18.29	180.02	5,479.59	237.57	-314.49	-224.83	11.00	11.00	0.00
5,537.79	22.44	180.02	5,515.00	224.42	-314.49	-211.69	11.00	11.00	0.00
P200 Marker									
5,550.00	23.79	180.02	5,526.23	219.62	-314.49	-206.90	11.00	11.00	0.00
5,554.12	24.24	180.02	5,530.00	217.94	-314.49	-205.23	11.00	11.00	0.00
P300 Marker									
5,576.28	26.68	180.02	5,550.00	208.42	-314.50	-195.71	11.00	11.00	0.00
P350 Marker									
5,600.00	29.29	180.02	5,570.95	197.29	-314.50	-184.59	11.00	11.00	0.00
5,650.00	34.79	180.02	5,613.32	170.78	-314.51	-158.09	11.00	11.00	0.00
5,700.00	40.29	180.02	5,652.95	140.32	-314.53	-127.67	11.00	11.00	0.00
5,750.00	45.79	180.02	5,689.48	106.21	-314.54	-93.58	11.00	11.00	0.00
5,768.29	47.80	180.02	5,702.00	92.88	-314.55	-80.26	11.00	11.00	0.00
Sharon Springs									
5,775.79	48.63	180.02	5,707.00	87.29	-314.55	-74.67	11.00	11.00	0.00
Niobrara									
5,800.00	51.29	180.02	5,722.57	68.76	-314.56	-56.15	11.00	11.00	0.00
5,807.14	52.07	180.02	5,727.00	63.15	-314.56	-50.56	11.00	11.00	0.00
Top A Chalk									
5,850.00	56.79	180.02	5,751.92	28.30	-314.58	-15.73	11.00	11.00	0.00
5,872.82	59.30	180.02	5,764.00	8.94	-314.58	3.61	11.00	11.00	0.00
Top A Marl									
5,900.00	62.29	180.02	5,777.26	-14.78	-314.59	27.32	11.00	11.00	0.00
5,912.63	63.68	180.02	5,783.00	-26.04	-314.60	38.56	11.00	11.00	0.00
A Marl									
5,933.81	66.01	180.02	5,792.00	-45.20	-314.61	57.71	11.00	11.00	0.00
Top Upper B									
5,950.00	67.79	180.02	5,798.35	-60.09	-314.61	72.60	11.00	11.00	0.00
6,000.00	73.29	180.02	5,815.01	-107.22	-314.63	119.68	11.00	11.00	0.00
6,018.46	75.32	180.02	5,820.00	-124.99	-314.64	137.44	11.00	11.00	0.00
Base Upper B									
6,050.00	78.79	180.02	5,827.06	-155.72	-314.65	168.15	11.00	11.00	0.00
6,100.00	84.29	180.02	5,834.42	-205.16	-314.68	217.55	11.00	11.00	0.00
6,149.97	89.79	180.02	5,837.00	-255.04	-314.70	267.39	11.00	11.00	0.00
Top Lower B									



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	H2		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
6,151.92	90.00	180.02	5,837.00	-256.99	-314.70	269.34	11.00	11.00	0.00	
LP @ 90° Inc, Hold - 7"										
6,200.00	90.00	180.02	5,837.00	-305.07	-314.72	317.38	0.00	0.00	0.00	
6,300.00	90.00	180.02	5,837.00	-405.07	-314.76	417.31	0.00	0.00	0.00	
6,400.00	90.00	180.02	5,837.00	-505.07	-314.80	517.23	0.00	0.00	0.00	
6,500.00	90.00	180.02	5,837.00	-605.07	-314.85	617.15	0.00	0.00	0.00	
6,600.00	90.00	180.02	5,837.00	-705.07	-314.89	717.07	0.00	0.00	0.00	
6,700.00	90.00	180.02	5,837.00	-805.07	-314.93	817.00	0.00	0.00	0.00	
6,800.00	90.00	180.02	5,837.00	-905.07	-314.98	916.92	0.00	0.00	0.00	
6,900.00	90.00	180.02	5,837.00	-1,005.07	-315.02	1,016.84	0.00	0.00	0.00	
7,000.00	90.00	180.02	5,837.00	-1,105.07	-315.06	1,116.76	0.00	0.00	0.00	
7,100.00	90.00	180.02	5,837.00	-1,205.07	-315.10	1,216.68	0.00	0.00	0.00	
7,200.00	90.00	180.02	5,837.00	-1,305.07	-315.15	1,316.61	0.00	0.00	0.00	
7,300.00	90.00	180.02	5,837.00	-1,405.07	-315.19	1,416.53	0.00	0.00	0.00	
7,400.00	90.00	180.02	5,837.00	-1,505.07	-315.23	1,516.45	0.00	0.00	0.00	
7,500.00	90.00	180.02	5,837.00	-1,605.07	-315.28	1,616.37	0.00	0.00	0.00	
7,600.00	90.00	180.02	5,837.00	-1,705.07	-315.32	1,716.29	0.00	0.00	0.00	
7,700.00	90.00	180.02	5,837.00	-1,805.07	-315.36	1,816.22	0.00	0.00	0.00	
7,800.00	90.00	180.02	5,837.00	-1,905.07	-315.40	1,916.14	0.00	0.00	0.00	
7,900.00	90.00	180.02	5,837.00	-2,005.07	-315.45	2,016.06	0.00	0.00	0.00	
8,000.00	90.00	180.02	5,837.00	-2,105.07	-315.49	2,115.98	0.00	0.00	0.00	
8,100.00	90.00	180.02	5,837.00	-2,205.07	-315.53	2,215.90	0.00	0.00	0.00	
8,200.00	90.00	180.02	5,837.00	-2,305.07	-315.58	2,315.83	0.00	0.00	0.00	
8,300.00	90.00	180.02	5,837.00	-2,405.07	-315.62	2,415.75	0.00	0.00	0.00	
8,400.00	90.00	180.02	5,837.00	-2,505.07	-315.66	2,515.67	0.00	0.00	0.00	
8,500.00	90.00	180.02	5,837.00	-2,605.07	-315.70	2,615.59	0.00	0.00	0.00	
8,600.00	90.00	180.02	5,837.00	-2,705.07	-315.75	2,715.52	0.00	0.00	0.00	
8,700.00	90.00	180.02	5,837.00	-2,805.07	-315.79	2,815.44	0.00	0.00	0.00	
8,800.00	90.00	180.02	5,837.00	-2,905.07	-315.83	2,915.36	0.00	0.00	0.00	
8,900.00	90.00	180.02	5,837.00	-3,005.07	-315.87	3,015.28	0.00	0.00	0.00	
9,000.00	90.00	180.02	5,837.00	-3,105.07	-315.92	3,115.20	0.00	0.00	0.00	
9,100.00	90.00	180.02	5,837.00	-3,205.07	-315.96	3,215.13	0.00	0.00	0.00	
9,200.00	90.00	180.02	5,837.00	-3,305.07	-316.00	3,315.05	0.00	0.00	0.00	
9,300.00	90.00	180.02	5,837.00	-3,405.07	-316.05	3,414.97	0.00	0.00	0.00	
9,400.00	90.00	180.02	5,837.00	-3,505.07	-316.09	3,514.89	0.00	0.00	0.00	
9,500.00	90.00	180.02	5,837.00	-3,605.07	-316.13	3,614.81	0.00	0.00	0.00	
9,600.00	90.00	180.02	5,837.00	-3,705.07	-316.17	3,714.74	0.00	0.00	0.00	
9,700.00	90.00	180.02	5,837.00	-3,805.07	-316.22	3,814.66	0.00	0.00	0.00	
9,800.00	90.00	180.02	5,837.00	-3,905.07	-316.26	3,914.58	0.00	0.00	0.00	
9,900.00	90.00	180.02	5,837.00	-4,005.07	-316.30	4,014.50	0.00	0.00	0.00	
10,000.00	90.00	180.02	5,837.00	-4,105.07	-316.35	4,114.43	0.00	0.00	0.00	
10,100.00	90.00	180.02	5,837.00	-4,205.07	-316.39	4,214.35	0.00	0.00	0.00	
10,200.00	90.00	180.02	5,837.00	-4,305.07	-316.43	4,314.27	0.00	0.00	0.00	
10,300.00	90.00	180.02	5,837.00	-4,405.07	-316.47	4,414.19	0.00	0.00	0.00	
10,400.00	90.00	180.02	5,837.00	-4,505.07	-316.52	4,514.11	0.00	0.00	0.00	
10,500.00	90.00	180.02	5,837.00	-4,605.07	-316.56	4,614.04	0.00	0.00	0.00	
10,600.00	90.00	180.02	5,837.00	-4,705.07	-316.60	4,713.96	0.00	0.00	0.00	
10,700.00	90.00	180.02	5,837.00	-4,805.07	-316.65	4,813.88	0.00	0.00	0.00	
10,800.00	90.00	180.02	5,837.00	-4,905.07	-316.69	4,913.80	0.00	0.00	0.00	
10,900.00	90.00	180.02	5,837.00	-5,005.07	-316.73	5,013.72	0.00	0.00	0.00	
11,000.00	90.00	180.02	5,837.00	-5,105.07	-316.77	5,113.65	0.00	0.00	0.00	
11,100.00	90.00	180.02	5,837.00	-5,205.07	-316.82	5,213.57	0.00	0.00	0.00	
11,200.00	90.00	180.02	5,837.00	-5,305.07	-316.86	5,313.49	0.00	0.00	0.00	
11,300.00	90.00	180.02	5,837.00	-5,405.07	-316.90	5,413.41	0.00	0.00	0.00	

WOG
Planning Report



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
11,400.00	90.00	180.02	5,837.00	-5,505.07	-316.95	5,513.33	0.00	0.00	0.00
11,500.00	90.00	180.02	5,837.00	-5,605.07	-316.99	5,613.26	0.00	0.00	0.00
11,600.00	90.00	180.02	5,837.00	-5,705.07	-317.03	5,713.18	0.00	0.00	0.00
11,700.00	90.00	180.02	5,837.00	-5,805.07	-317.07	5,813.10	0.00	0.00	0.00
11,800.00	90.00	180.02	5,837.00	-5,905.07	-317.12	5,913.02	0.00	0.00	0.00
11,900.00	90.00	180.02	5,837.00	-6,005.07	-317.16	6,012.95	0.00	0.00	0.00
12,000.00	90.00	180.02	5,837.00	-6,105.07	-317.20	6,112.87	0.00	0.00	0.00
12,100.00	90.00	180.02	5,837.00	-6,205.07	-317.25	6,212.79	0.00	0.00	0.00
12,200.00	90.00	180.02	5,837.00	-6,305.07	-317.29	6,312.71	0.00	0.00	0.00
12,300.00	90.00	180.02	5,837.00	-6,405.07	-317.33	6,412.63	0.00	0.00	0.00
12,400.00	90.00	180.02	5,837.00	-6,505.07	-317.37	6,512.56	0.00	0.00	0.00
12,500.00	90.00	180.02	5,837.00	-6,605.07	-317.42	6,612.48	0.00	0.00	0.00
12,600.00	90.00	180.02	5,837.00	-6,705.07	-317.46	6,712.40	0.00	0.00	0.00
12,700.00	90.00	180.02	5,837.00	-6,805.07	-317.50	6,812.32	0.00	0.00	0.00
12,800.00	90.00	180.02	5,837.00	-6,905.07	-317.55	6,912.24	0.00	0.00	0.00
12,900.00	90.00	180.02	5,837.00	-7,005.07	-317.59	7,012.17	0.00	0.00	0.00
13,000.00	90.00	180.02	5,837.00	-7,105.07	-317.63	7,112.09	0.00	0.00	0.00
13,100.00	90.00	180.02	5,837.00	-7,205.07	-317.67	7,212.01	0.00	0.00	0.00
13,200.00	90.00	180.02	5,837.00	-7,305.07	-317.72	7,311.93	0.00	0.00	0.00
13,300.00	90.00	180.02	5,837.00	-7,405.07	-317.76	7,411.86	0.00	0.00	0.00
13,400.00	90.00	180.02	5,837.00	-7,505.07	-317.80	7,511.78	0.00	0.00	0.00
13,500.00	90.00	180.02	5,837.00	-7,605.07	-317.85	7,611.70	0.00	0.00	0.00
13,600.00	90.00	180.02	5,837.00	-7,705.07	-317.89	7,711.62	0.00	0.00	0.00
13,700.00	90.00	180.02	5,837.00	-7,805.07	-317.93	7,811.54	0.00	0.00	0.00
13,800.00	90.00	180.02	5,837.00	-7,905.07	-317.97	7,911.47	0.00	0.00	0.00
13,860.86	90.00	180.02	5,837.00	-7,965.94	-318.00	7,972.28	0.00	0.00	0.00
TD at 13860.90' MD - PBHL 1806B									

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
PBHL 1806B	0.00	0.00	5,837.00	-7,965.94	-318.00	1,550,426.34	3,471,196.56	40° 49' 54.770 N	103° 47' 49.927 W
- plan hits target center									
- Point									

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
6,151.92	5,837.00	7"	7.000	8.750	

WOG
Planning Report



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07F-1806B
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07F-1806B	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Design #1		

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,554.14	1,550.00	Upper Pierre				
3,511.59	3,500.00	Hygiene				
3,662.16	3,650.00	Lower Pierre				
5,537.79	5,515.00	P200 Marker				
5,554.12	5,530.00	P300 Marker				
5,576.28	5,550.00	P350 Marker				
5,768.29	5,702.00	Sharon Springs				
5,775.79	5,707.00	Niobrara				
5,807.14	5,727.00	Top A Chalk				
5,872.82	5,764.00	Top A Marl				
5,912.63	5,783.00	A Marl				
5,933.81	5,792.00	Top Upper B				
6,018.46	5,820.00	Base Upper B				
6,149.97	5,837.00	Top Lower B				

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
300.00	300.00	0.00	0.00	Build 2°/100'	
550.00	549.68	7.01	-8.35	Hold 5° Inc	
5,010.00	4,992.71	256.87	-306.12	Drop 2°/100'	
5,260.00	5,242.39	263.88	-314.47	Hold Vertical	
5,333.74	5,316.13	263.88	-314.47	KOP, Build 11°/100'	
6,151.92	5,837.00	-256.99	-312.90	LP @ 90° Inc, Hold	
13,860.90	5,837.00	-7,965.94	-289.58	TD at 13860.90' MD	