

# **PICEANCE VLY NAD 83**

**RU 08-07S-093W**

**RU 21-8 Pad**

**RU 41-8 - Slot A06**

**Wellbore #1**

**Plan: Design #2 14May15 sam**

## **Standard Planning Report**

**18 May, 2015**

# WPX

## Planning Report

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RU 41-8 (A06) - Slot A06
<b>Company:</b>	PICEANCE VLY NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Project:</b>	RU 08-07S-093W	<b>MD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Site:</b>	RU 21-8 Pad	<b>North Reference:</b>	True
<b>Well:</b>	RU 41-8	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #2 14May15 sam		

<b>Project</b>	RU 08-07S-093W		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Central Zone		

<b>Site</b>	RU 21-8 Pad		
<b>Site Position:</b>		<b>Northing:</b>	1,602,707.70 usft
<b>From:</b>	Map	<b>Easting:</b>	2,350,555.60 usft
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13.200 in
		<b>Latitude:</b>	39.465627
		<b>Longitude:</b>	-107.800612
		<b>Grid Convergence:</b>	-1.45 °

<b>Well</b>	RU 41-8 - Slot A06		
<b>Well Position</b>	<b>+N/-S</b>	-59.11 usft	<b>Northing:</b>
	<b>+E/-W</b>	-67.87 usft	<b>Easting:</b>
<b>Position Uncertainty</b>	0.00 usft		<b>Wellhead Elevation:</b>
			<b>Latitude:</b>
			<b>Longitude:</b>
			<b>Ground Level:</b>

<b>Wellbore</b>	Wellbore #1		
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination</b>
			(°)
	IGRF2010	9/8/2014	9.84
			<b>Dip Angle</b>
			(°)
			<b>Field Strength</b>
			(nT)
			51,918

<b>Design</b>	Design #2 14May15 sam		
<b>Audit Notes:</b>			
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>
			0.00
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			<b>Direction</b>
			(bearing)
			79.71

<b>Plan Sections</b>										
<b>Measured</b>	<b>Inclination</b>	<b>Azimuth</b>	<b>Vertical</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Dogleg</b>	<b>Build</b>	<b>Turn</b>	<b>TFO</b>	<b>Target</b>
<b>Depth</b>	<b>(°)</b>	<b>(bearing)</b>	<b>Depth</b>	<b>(usft)</b>	<b>(usft)</b>	<b>Rate</b>	<b>Rate</b>	<b>Rate</b>	<b>(°)</b>	
<b>(usft)</b>			<b>(usft)</b>			<b>(°/100usft)</b>	<b>(°/100usft)</b>	<b>(°/100usft)</b>		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130.00	0.00	0.00	130.00	0.00	0.00	0.00	0.00	0.00	0.00	
330.00	6.00	90.00	329.63	0.00	10.46	3.00	3.00	0.00	90.00	
826.84	20.77	79.54	811.69	16.08	123.69	3.00	2.97	-2.11	-14.49	
6,243.72	20.77	79.54	5,876.63	364.79	2,012.44	0.00	0.00	0.00	0.00	
7,628.20	0.00	0.00	7,231.00	409.84	2,256.49	1.50	-1.50	0.00	180.00	RU 41-8 TOP GAS 5C
10,378.20	0.00	0.00	9,981.00	409.84	2,256.49	0.00	0.00	0.00	0.00	

# WPX

## Planning Report

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RU 41-8 (A06) - Slot A06
<b>Company:</b>	PICEANCE VLY NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Project:</b>	RU 08-07S-093W	<b>MD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Site:</b>	RU 21-8 Pad	<b>North Reference:</b>	True
<b>Well:</b>	RU 41-8	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #2 14May15 sam		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (bearing)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
130.00	0.00	0.00	130.00	0.00	0.00	0.00	0.00	0.00	0.00	
<b>Start Build 3.00</b>										
330.00	6.00	90.00	329.63	0.00	10.46	10.29	3.00	3.00	0.00	
<b>Start Build/TurnDLS 3.00 TFO -14.49</b>										
500.00	11.01	83.31	497.72	1.89	35.49	35.26	3.00	2.95	-3.93	
826.83	20.77	79.54	811.69	16.08	123.69	124.57	3.00	2.98	-1.15	
<b>Hold 20.77 Inclination</b>										
1,000.00	20.77	79.54	973.60	27.23	184.07	185.97	0.00	0.00	0.00	
1,200.00	20.77	79.54	1,160.61	40.10	253.80	256.88	0.00	0.00	0.00	
<b>9 5/8"</b>										
1,500.00	20.77	79.54	1,441.12	59.42	358.41	363.25	0.00	0.00	0.00	
2,000.00	20.77	79.54	1,908.63	91.60	532.75	540.54	0.00	0.00	0.00	
2,500.00	20.77	79.54	2,376.15	123.79	707.08	717.82	0.00	0.00	0.00	
3,000.00	20.77	79.54	2,843.66	155.98	881.42	895.11	0.00	0.00	0.00	
3,500.00	20.77	79.54	3,311.18	188.16	1,055.76	1,072.40	0.00	0.00	0.00	
4,000.00	20.77	79.54	3,778.69	220.35	1,230.10	1,249.68	0.00	0.00	0.00	
4,176.80	20.77	79.54	3,944.00	231.73	1,291.75	1,312.37	0.00	0.00	0.00	
<b>Top of "G" Sand</b>										
4,294.44	20.77	79.54	4,054.00	239.31	1,332.77	1,354.08	0.00	0.00	0.00	
<b>Base of "G" Sand</b>										
4,500.00	20.77	79.54	4,246.21	252.54	1,404.44	1,426.97	0.00	0.00	0.00	
5,000.00	20.77	79.54	4,713.72	284.72	1,578.78	1,604.25	0.00	0.00	0.00	
5,500.00	20.77	79.54	5,181.23	316.91	1,753.12	1,781.54	0.00	0.00	0.00	
6,000.00	20.77	79.54	5,648.75	349.10	1,927.46	1,958.82	0.00	0.00	0.00	
6,243.72	20.77	79.54	5,876.63	364.79	2,012.44	2,045.24	0.00	0.00	0.00	
<b>Start Drop -1.50</b>										
6,500.00	16.92	79.54	6,119.13	379.81	2,093.83	2,128.00	1.50	-1.50	0.00	
7,000.00	9.42	79.54	6,605.63	400.49	2,205.81	2,241.87	1.50	-1.50	0.00	
7,052.02	8.64	79.54	6,657.00	401.97	2,213.84	2,250.04	1.50	-1.50	0.00	
<b>Mesaverde</b>										
7,500.00	1.92	79.54	7,102.82	409.45	2,254.38	2,291.26	1.50	-1.50	0.00	
7,628.20	0.00	0.00	7,231.00	409.84	2,256.49	2,293.41	1.50	-1.50	0.00	
<b>Top Gas Target - Approx. Top Gas</b>										
8,000.00	0.00	0.00	7,602.80	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
8,500.00	0.00	0.00	8,102.80	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
9,000.00	0.00	0.00	8,602.80	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
9,413.20	0.00	0.00	9,016.00	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
<b>Cameo Coals</b>										
9,500.00	0.00	0.00	9,102.80	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
10,000.00	0.00	0.00	9,602.80	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
10,113.20	0.00	0.00	9,716.00	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
<b>Coal D</b>										
10,228.20	0.00	0.00	9,831.00	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
<b>Rollins SS</b>										
10,378.20	0.00	0.00	9,981.00	409.84	2,256.49	2,293.41	0.00	0.00	0.00	
<b>TD at 10378.20</b>										

# WPX

## Planning Report

<b>Database:</b>	COMPASS-PICEANCE	<b>Local Co-ordinate Reference:</b>	Well RU 41-8 (A06) - Slot A06
<b>Company:</b>	PICEANCE VLY NAD 83	<b>TVD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Project:</b>	RU 08-07S-093W	<b>MD Reference:</b>	KELLY BUSHING @ 7762.00usft (Nabors 576 (26' RKB) mab)
<b>Site:</b>	RU 21-8 Pad	<b>North Reference:</b>	True
<b>Well:</b>	RU 41-8	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #2 14May15 sam		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (bearing)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
RU 41-8 TOP GAS 50' F - plan hits target center - Circle (radius 50.00)	0.00	0.00	7,231.00	409.84	2,256.49	1,603,002.90	2,352,752.40	39.466590	-107.792860

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
1,200.00	1,160.61	9 5/8"	9.625	13.500	

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (bearing)	
4,176.80	3,944.00	Top of "G" Sand		0.00		
4,294.44	4,054.00	Base of "G" Sand		0.00		
7,052.02	6,657.00	Mesaverde		0.00		
7,628.20	7,231.00	Approx. Top Gas		0.00		
9,413.20	9,016.00	Cameo Coals		0.00		
10,113.20	9,716.00	Coal D		0.00		
10,228.20	9,831.00	Rollins SS		0.00		

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
130.00	130.00	0.00	0.00	Start Build 3.00	
330.00	329.63	0.00	10.46	Start Build/TurnDLS 3.00 TFO -14.49	
826.83	811.69	16.08	123.69	Hold 20.77 Inclination	
6,243.72	5,876.63	364.79	2,012.44	Start Drop -1.50	
7,628.20	7,231.00	409.84	2,256.49	Top Gas Target	
10,378.20	9,981.00	409.84	2,256.49	TD at 10378.20	