



Schematic - Current

Well Name: NEWNAM 2I-32H C264

API # 05123397800000	Well Type Gas	Operating Region Western Ops	Division DJ Basin	Area Wattenberg	Pad Newnam 32H-C264	County/Parish Weld	State CO	Field Name Wattenberg	
Operator		Well Status	Orig KB El....	Gr Elev (ft)	KB-Grd (ft)	Total Depth (All) (ftKB)		Total Depth (TVD) (ftKB)	PBTD (All) (ftKB)

Most Recent Job

Job Category Completion	Primary Job Type Original Completion	Secondary Job Type D&C	Start Date 03/16/2015	End Date 04/24/2015
----------------------------	---	---------------------------	--------------------------	------------------------

TD: 11,625.0

Directional Horizontal Well - Original Hole, 06/17/2015 1:28:00 PM

MD (ftKB)	TVD (ftKB)	Incl (°)	DLS	Vertical schematic (actual)
-1.0	-1.0	0.4	DLS (°/...	1-2; Tubing Hanger; 2 3/8; 1.940; -0.8-0.0; 0.85
13.1	13.1	0.4		2-2; A&B section; 9 5/8; 8.835; 13.8-17.4; 3.65
17.4	17.4	0.4		3-2; Hanger & Pup Joint; 7; 6.276; 17.1-20.8; 3.74
21.7	21.7	0.4		2-3; Pup Jt below Base Plate; 9 5/8; 8.835; 17.4-21.8; 4.37
986.2	981.6	9.8		1-1; Casing Joints; 16; 15.250; 17.0-137.0; 126.00
1,030.5	1,025.2	9.7		2-4; Casing Joints; 9 5/8; 8.835; 21.8-986.4; 964.56
6,393.0	6,368.6	0.5		2-5; Float Collar; 9 5/8; 8.835; 986.4-987.3; 0.93
6,836.0	6,795.5	28.4		2-6; Casing Joints; 9 5/8; 8.835; 987.3-1,029.2; 41.90
6,875.0	6,829.8	32.2		2-7; Shoe; 9 5/8; 8.835; 1,029.2-1,030.6; 1.41
7,200.1	7,061.2	59.4		4-1; Casing Joints; 4 1/2; 3.920; 13.0-6,393.2; 6,396.39
7,202.4	7,062.4	59.6		1-3; Tubing; 2 3/8; 1.995; 0.0-6,841.9; 6,841.85
7,417.0	7,132.9	84.6		3-3; Casing Joints; 7; 6.276; 20.8-7,415.3; 7,394.51
7,482.9	7,135.7	88.1		4-2; Marker jt. A; 4 1/2; 3.920; 6,393.2-6,414.2; 21.00
7,533.1	7,137.6	90.6		1-4; Profile Nipple; 2.59; 1.875; 6,841.9-6,842.8; 0.93
7,734.9	7,137.2	89.7		1-5; Tubing; 2 3/8; 1.995; 6,842.8-7,166.4; 323.60
7,928.1	7,138.1	89.7		1-6; Tubing Nipple; 2.59; 1.995; 7,166.4-7,167.5; 1.10
8,075.1	7,138.4	90.7		1-7; Tubing; 2 3/8; 1.995; 7,167.5-7,200.1; 32.65
8,320.9	7,131.5	91.1		1-8; Profile Nipple; 3 1/16; 1.790; 7,200.1-7,201.2; 1.05
8,515.1	7,128.5	91.3		1-9; Rupture Disc; 3 1/16; 1.995; 7,201.2-7,202.0; 0.80
8,761.2	7,129.2	88.5		1-10; Mule Shoe Collar; 3 1/16; 2.594; 7,202.0-7,202.4; 0.41
8,960.0	7,135.1	89.2		3-4; Halco Float Collar; 7.92; 6.276; 7,415.3-7,417.0; 1.70
9,202.1	7,135.7	90.4		3-5; Casing Joints; 7; 6.276; 7,417.0-7,462.3; 45.32
9,284.1	7,135.5	90.1		3-6; Halco Float Shoe; 7.92; 6.276; 7,462.3-7,465.0; 2.68
9,495.1	7,136.5	89.7		Perforated; 7,488.0-7,588.0; 04/01/2015
9,690.0	7,132.0	92.4		Perforated; 7,635.0-7,735.0; 04/01/2015
9,935.0	7,125.9	90.3		Perforated; 7,781.0-7,881.0; 04/01/2015
10,095.8	7,126.1	89.0		Perforated; 7,928.0-8,028.0; 04/01/2015
10,228.0	7,129.3	88.6		Perforated; 8,075.0-8,170.0; 03/31/2015
10,429.1	7,133.1	89.0		Perforated; 8,225.0-8,321.0; 03/31/2015
10,669.0	7,133.0	89.7		Perforated; 8,368.0-8,468.0; 03/31/2015
10,861.9	7,132.8	89.4		Perforated; 8,515.0-8,615.0; 03/31/2015
11,050.0	7,137.1	89.5		Perforated; 8,662.0-8,761.0; 03/31/2015
11,301.8	7,138.4	88.8		Perforated; 8,808.0-8,905.0; 03/31/2015
11,552.8	7,141.2	91.0		4-3; Casing Joints; 4 1/2; 3.920; 6,414.2-11,549.7; 5,135.57
11,601.0	7,140.5	90.9		Perforated; 8,960.0-9,055.0; 03/31/2015
11,625.0	7,140.1	90.9		Perforated; 9,102.0-9,202.0; 03/31/2015
				Perforated; 9,248.0-9,348.0; 03/31/2015
				Perforated; 9,395.0-9,495.0; 03/30/2015
				Perforated; 9,541.0-9,645.0; 03/30/2015
				Perforated; 9,690.0-9,788.0; 03/30/2015
				Perforated; 9,835.0-9,935.0; 03/30/2015
				Perforated; 9,982.0-10,082.0; 03/30/2015
				Perforated; 10,129.0-10,228.0; 03/30/2015
				Perforated; 10,275.0-10,373.0; 03/30/2015
				Perforated; 10,429.0-10,522.0; 03/30/2015
				Perforated; 10,569.0-10,669.0; 03/29/2015
				Perforated; 10,715.0-10,815.0; 03/29/2015
				Perforated; 10,862.0-10,962.0; 03/29/2015
				Perforated; 11,009.0-11,105.0; 03/29/2015
				Perforated; 11,156.0-11,255.0; 03/29/2015
				Perforated; 11,302.0-11,402.0; 03/29/2015
				4-4; RSI Tool; 5.60; 3.920; 11,549.7-11,552.9; 3.20
				Burst Ports; 11,550.0-11,553.0; 03/28/2015
				4-5; Casing Joints; 4 1/2; 3.920; 11,552.9-11,599.5; 46.56
				4-6; Landing Collar; 5.20; 1.930; 11,599.5-11,601.2; 1.70
				4-7; Float Collar; 5.04; 3.904; 11,601.2-11,602.8; 1.55
				4-8; Shoe; 5.04; 3.904; 11,602.8-11,605.0; 2.25