



Ursa Operating Company, LLC

Rockies Region

Monument Ridge B

Monument Ridge B 24C-08-07-95

Wellbore #1

Plan: Design #1

Standard Planning Report

12 June, 2015



Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Monument Ridge B 24C-08-07-95
Company:	Ursa Operating Company, LLC	TVD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Project:	Rockies Region	MD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Site:	Monument Ridge B	North Reference:	True
Well:	Monument Ridge B 24C-08-07-95	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	Rockies Region		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		

Site		Monument Ridge B			
Site Position:		Northing:	1,596,716.55 usft	Latitude:	39° 26' 40.501 N
From:	Lat/Long	Easting:	2,287,433.43 usft	Longitude:	108° 1' 24.665 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-1.59 °

Well	Monument Ridge B 24C-08-07-95, SHL: 39.447723033 -108.012276383					
Well Position	+N/-S	1,143.6 usft	Northing:	1,597,771.59 usft	Latitude:	39° 26' 51.803 N
	+E/-W	3,174.6 usft	Easting:	2,290,638.57 usft	Longitude:	108° 0' 44.195 W
Position Uncertainty	0.0 usft		Wellhead Elevation:	5,718.8 usft	Ground Level:	5,701.8 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	6/6/2015	9.84	65.59	51,823

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	261.15

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.00	0.00	0.00	0.00	
600.0	7.00	265.00	599.5	-1.1	-12.2	3.50	3.50	0.00	265.00	
1,590.1	41.63	261.05	1,488.1	-59.2	-409.3	3.50	3.50	-0.40	-4.61	
5,181.5	41.63	261.05	4,172.4	-430.3	-2,766.3	0.00	0.00	0.00	0.00	
6,371.1	0.00	0.00	5,260.0	-494.6	-3,174.7	3.50	-3.50	0.00	180.00	
8,104.9	0.00	0.00	6,993.8	-494.6	-3,174.7	0.00	0.00	0.00	0.00	

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Monument Ridge B 24C-08-07-95
Company:	Ursa Operating Company, LLC	TVD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Project:	Rockies Region	MD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Site:	Monument Ridge B	North Reference:	True
Well:	Monument Ridge B 24C-08-07-95	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00	
0.1	0.00	0.00	0.1	0.0	0.0	0.0	0.00	0.00	0.00	
SHL: 39.447723033, -108.012276383										
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00	
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00	
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00	
Start Build 3.50										
500.0	3.50	265.00	499.9	-0.3	-3.0	3.0	3.50	3.50	0.00	
600.0	7.00	265.00	599.5	-1.1	-12.2	12.2	3.50	3.50	0.00	
Start DLS 3.50 TFO -4.61										
700.0	10.49	263.46	698.3	-2.6	-27.3	27.4	3.50	3.49	-1.54	
800.0	13.99	262.68	796.0	-5.2	-48.3	48.5	3.50	3.50	-0.78	
900.0	17.49	262.20	892.3	-8.8	-75.2	75.7	3.50	3.50	-0.47	
1,000.0	20.98	261.89	986.7	-13.4	-107.8	108.6	3.50	3.50	-0.32	
1,100.0	24.48	261.66	1,078.9	-18.9	-146.1	147.2	3.50	3.50	-0.23	
1,200.0	27.98	261.48	1,168.6	-25.4	-189.8	191.4	3.50	3.50	-0.18	
1,300.0	31.48	261.34	1,255.4	-32.8	-238.8	241.0	3.50	3.50	-0.14	
1,400.0	34.98	261.22	1,339.0	-41.1	-293.0	295.8	3.50	3.50	-0.11	
1,500.0	38.48	261.13	1,419.2	-50.3	-352.1	355.6	3.50	3.50	-0.10	
1,590.1	41.63	261.05	1,488.1	-59.2	-409.3	413.5	3.50	3.50	-0.08	
Start 3591.5 hold at 1590.1 MD										
1,600.0	41.63	261.05	1,495.5	-60.3	-415.8	420.2	0.00	0.00	0.00	
1,700.0	41.63	261.05	1,570.3	-70.6	-481.5	486.6	0.00	0.00	0.00	
1,800.0	41.63	261.05	1,645.0	-80.9	-547.1	553.0	0.00	0.00	0.00	
1,873.6	41.63	261.05	1,700.0	-88.5	-595.4	601.9	0.00	0.00	0.00	
Surface Casing										
1,900.0	41.63	261.05	1,719.7	-91.3	-612.7	619.5	0.00	0.00	0.00	
2,000.0	41.63	261.05	1,794.5	-101.6	-678.3	685.9	0.00	0.00	0.00	
2,100.0	41.63	261.05	1,869.2	-111.9	-744.0	752.3	0.00	0.00	0.00	
2,200.0	41.63	261.05	1,944.0	-122.3	-809.6	818.8	0.00	0.00	0.00	
2,300.0	41.63	261.05	2,018.7	-132.6	-875.2	885.2	0.00	0.00	0.00	
2,400.0	41.63	261.05	2,093.5	-142.9	-940.8	951.6	0.00	0.00	0.00	
2,500.0	41.63	261.05	2,168.2	-153.3	-1,006.5	1,018.1	0.00	0.00	0.00	
2,600.0	41.63	261.05	2,242.9	-163.6	-1,072.1	1,084.5	0.00	0.00	0.00	
2,700.0	41.63	261.05	2,317.7	-173.9	-1,137.7	1,150.9	0.00	0.00	0.00	
2,800.0	41.63	261.05	2,392.4	-184.3	-1,203.4	1,217.4	0.00	0.00	0.00	
2,900.0	41.63	261.05	2,467.2	-194.6	-1,269.0	1,283.8	0.00	0.00	0.00	
3,000.0	41.63	261.05	2,541.9	-204.9	-1,334.6	1,350.2	0.00	0.00	0.00	
3,100.0	41.63	261.05	2,616.6	-215.2	-1,400.2	1,416.7	0.00	0.00	0.00	
3,200.0	41.63	261.05	2,691.4	-225.6	-1,465.9	1,483.1	0.00	0.00	0.00	
3,300.0	41.63	261.05	2,766.1	-235.9	-1,531.5	1,549.6	0.00	0.00	0.00	
3,400.0	41.63	261.05	2,840.9	-246.2	-1,597.1	1,616.0	0.00	0.00	0.00	
3,500.0	41.63	261.05	2,915.6	-256.6	-1,662.7	1,682.4	0.00	0.00	0.00	
3,600.0	41.63	261.05	2,990.4	-266.9	-1,728.4	1,748.9	0.00	0.00	0.00	
3,700.0	41.63	261.05	3,065.1	-277.2	-1,794.0	1,815.3	0.00	0.00	0.00	
3,800.0	41.63	261.05	3,139.8	-287.6	-1,859.6	1,881.7	0.00	0.00	0.00	
3,900.0	41.63	261.05	3,214.6	-297.9	-1,925.3	1,948.2	0.00	0.00	0.00	
4,000.0	41.63	261.05	3,289.3	-308.2	-1,990.9	2,014.6	0.00	0.00	0.00	
4,100.0	41.63	261.05	3,364.1	-318.6	-2,056.5	2,081.0	0.00	0.00	0.00	
4,200.0	41.63	261.05	3,438.8	-328.9	-2,122.1	2,147.5	0.00	0.00	0.00	

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Monument Ridge B 24C-08-07-95
Company:	Ursa Operating Company, LLC	TVD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Project:	Rockies Region	MD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Site:	Monument Ridge B	North Reference:	True
Well:	Monument Ridge B 24C-08-07-95	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,300.0	41.63	261.05	3,513.6	-339.2	-2,187.8	2,213.9	0.00	0.00	0.00
4,400.0	41.63	261.05	3,588.3	-349.5	-2,253.4	2,280.3	0.00	0.00	0.00
4,434.1	41.63	261.05	3,613.8	-353.1	-2,275.8	2,303.0	0.00	0.00	0.00
Williams Fork									
4,500.0	41.63	261.05	3,663.0	-359.9	-2,319.0	2,346.8	0.00	0.00	0.00
4,600.0	41.63	261.05	3,737.8	-370.2	-2,384.6	2,413.2	0.00	0.00	0.00
4,700.0	41.63	261.05	3,812.5	-380.5	-2,450.3	2,479.6	0.00	0.00	0.00
4,800.0	41.63	261.05	3,887.3	-390.9	-2,515.9	2,546.1	0.00	0.00	0.00
4,900.0	41.63	261.05	3,962.0	-401.2	-2,581.5	2,612.5	0.00	0.00	0.00
5,000.0	41.63	261.05	4,036.7	-411.5	-2,647.1	2,678.9	0.00	0.00	0.00
5,100.0	41.63	261.05	4,111.5	-421.9	-2,712.8	2,745.4	0.00	0.00	0.00
5,181.5	41.63	261.05	4,172.4	-430.3	-2,766.3	2,799.6	0.00	0.00	0.00
Start Drop -3.50									
5,200.0	40.99	261.05	4,186.3	-432.2	-2,778.3	2,811.7	3.50	-3.50	0.00
5,300.0	37.49	261.05	4,263.7	-442.0	-2,840.8	2,875.0	3.50	-3.50	0.00
5,400.0	33.99	261.05	4,344.9	-451.1	-2,898.5	2,933.4	3.50	-3.50	0.00
5,500.0	30.49	261.05	4,429.5	-459.4	-2,951.2	2,986.7	3.50	-3.50	0.00
5,600.0	26.99	261.05	4,517.1	-466.9	-2,998.7	3,034.8	3.50	-3.50	0.00
5,700.0	23.49	261.05	4,607.6	-473.5	-3,040.8	3,077.4	3.50	-3.50	0.00
5,790.8	20.31	261.05	4,691.8	-478.8	-3,074.2	3,111.3	3.50	-3.50	0.00
Top of Gas									
5,800.0	19.99	261.05	4,700.5	-479.3	-3,077.3	3,114.4	3.50	-3.50	0.00
5,900.0	16.49	261.05	4,795.4	-484.1	-3,108.3	3,145.7	3.50	-3.50	0.00
6,000.0	12.99	261.05	4,892.1	-488.1	-3,133.4	3,171.2	3.50	-3.50	0.00
6,100.0	9.49	261.05	4,990.2	-491.1	-3,152.6	3,190.6	3.50	-3.50	0.00
6,200.0	5.99	261.05	5,089.3	-493.2	-3,165.9	3,204.1	3.50	-3.50	0.00
6,300.0	2.49	261.05	5,189.0	-494.4	-3,173.2	3,211.5	3.50	-3.50	0.00
6,371.1	0.00	0.00	5,260.0	-494.6	-3,174.7	3,213.0	3.50	-3.50	0.00
Start 1733.8 hold at 6371.1 MD - Back to Vertical									
6,400.0	0.00	0.00	5,288.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
6,500.0	0.00	0.00	5,388.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
6,600.0	0.00	0.00	5,488.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
6,700.0	0.00	0.00	5,588.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
6,800.0	0.00	0.00	5,688.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
6,900.0	0.00	0.00	5,788.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,000.0	0.00	0.00	5,888.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,100.0	0.00	0.00	5,988.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,104.9	0.00	0.00	5,993.8	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
Cameo									
7,200.0	0.00	0.00	6,088.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,300.0	0.00	0.00	6,188.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,400.0	0.00	0.00	6,288.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,500.0	0.00	0.00	6,388.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,600.0	0.00	0.00	6,488.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,700.0	0.00	0.00	6,588.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,800.0	0.00	0.00	6,688.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
7,804.9	0.00	0.00	6,693.8	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
Rollins									
7,900.0	0.00	0.00	6,788.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
8,000.0	0.00	0.00	6,888.9	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
8,104.8	0.00	0.00	6,993.7	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well Monument Ridge B 24C-08-07-95
Company:	Ursa Operating Company, LLC	TVD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Project:	Rockies Region	MD Reference:	Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)
Site:	Monument Ridge B	North Reference:	True
Well:	Monument Ridge B 24C-08-07-95	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
BHL: 39.4463646000, -108.0235184000									
8,104.9	0.00	0.00	6,993.8	-494.6	-3,174.7	3,213.0	0.00	0.00	0.00
TD at 8104.9 - TD									


Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
Monument Ridge B-24C	0.00	0.00	4,691.8	-494.6	-3,174.7	1,597,364.97	2,287,451.37	39° 26' 46.913 N	108° 1' 24.666 W
- plan misses target center by 95.8usft at 5822.6usft MD (4721.8 TVD, -480.4 N, -3084.8 E)									
- Rectangle (sides W100.0 H40.0 D2,302.0)									

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
4,434.1	3,613.8	Williams Fork		0.00		
5,790.8	4,691.8	Top of Gas		0.00		
7,104.9	5,993.8	Cameo		0.00		
7,804.9	6,693.8	Rollins		0.00		
8,104.9	6,993.8	TD		0.00		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
0.1	0.1	0.0	0.0	SHL: 39.447723033, -108.012276383
400.0	400.0	0.0	0.0	Start Build 3.50
600.0	599.5	-1.1	-12.2	Start DLS 3.50 TFO -4.61
1,590.1	1,488.1	-59.2	-409.3	Start 3591.5 hold at 1590.1 MD
1,873.6	1,700.0	-88.5	-595.4	Surface Casing
5,181.5	4,172.4	-430.3	-2,766.3	Start Drop -3.50
6,371.1	5,260.0	-494.6	-3,174.7	Start 1733.8 hold at 6371.1 MD
6,371.1	5,260.0	-494.6	-3,174.7	Back to Vertical
8,104.8	6,993.7	-494.6	-3,174.7	BHL: 39.4463646000, -108.0235184000
8,104.9	6,993.8	-494.6	-3,174.7	TD at 8104.9



Well Name: Monument Ridge B 24C-08-07-95
Surface Location: Monument Ridge B
North American Datum 1983, US State Plane 1983, Colorado Central Zone
Ground Elevation: 5701.8
+N/-S +E/-W Northing Easting Latitude Longitude
0.0 0.0 1597771.59 2290638.57 39° 26' 51.803 N 108° 0' 44.195 W
PLAN KB Monument Ridge B 24C-08-07-95 @ 5718.8usft (PLAN KB)



Azimuths to True North
Magnetic North: 9.84°
Magnetic Field
Strength: 51823.1snT
Dip Angle: 65.59°
Date: 6/6/2015
Model: IGRF2010

Monument Ridge B
Monument Ridge B 24C-08-07-95
Design #1
11:27, June 12 2015

WELLBORE TARGET DETAILS (MAP CO-ORDINATES AND LAT/LONG)

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
Monument Ridge B-24C-08-07-95 TGT	4691.8	-494.6	-3174.7	1597364.97	2287451.36	39° 26' 51.803 N	108° 0' 44.195 W	Rectangle (Sides: L40.0 W100.0)

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	400.0	0.00	0.00	400.0	0.0	0.0	0.00	0.00	0.0	
3	600.0	7.00	265.00	599.5	-1.1	-12.2	3.50	265.00	12.2	
4	1590.1	41.63	261.05	1488.1	-59.2	-409.3	3.50	-4.61	413.5	
5	5181.5	41.63	261.05	4172.4	-430.3	-2766.3	0.00	0.00	2799.6	
6	6371.1	0.00	0.00	5260.0	-494.6	-3174.7	3.50	180.00	3213.0	
7	8104.9	0.00	0.00	6993.8	-494.6	-3174.7	0.00	0.00	3213.0	

ANNOTATIONS

TVD	MD	Annotation
0.1	0.1	SHL: 39.447723033, -108.012276383
400.0	400.0	Start Build 3.50
599.5	600.0	Start DLS 3.50 TFO -4.61
1488.1	1590.1	Start 3591.5 hold at 1590.1 MD
1700.0	1873.6	Surface Casing
4172.4	5181.5	Start Drop -3.50
5260.0	6371.1	Start 1733.8 hold at 6371.1 MD
5260.0	6371.1	Back to Vertical
6993.7	8104.8	BHL: 39.4463646000, -108.0235184000
6993.8	8104.9	TD at 8104.9

FORMATION TOP DETAILS

TVDPath	MDPath	Formation	DipAngle	DipDir
3613.8	4434.1	Williams Fork	0.00	
4691.8	5790.8	Top of Gas	0.00	
5993.8	7104.9	Cameo	0.00	
6693.8	7804.9	Rollins	0.00	
6993.8	8104.9	TD	0.00	

