

Document Number:  
400885812

Date Received:  
08/18/2015

**WELL ABANDONMENT REPORT**

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 24320 Contact Name: Dave Peterson

Name of Operator: DIAMOND OPERATING, INC. Phone: (303) 4944420

Address: 6666 GUNPARK DR STE #200 Fax: (303) 4943931

City: BOULDER State: CO Zip: 80301 Email: davep@flatironenergy.com

**For "Intent" 24 hour notice required,** Name: Schure, Kym Tel: (970) 520-3832

**COGCC contact:** Email: kym.schure@state.co.us

API Number 05-075-08134-00 Well Number: 1

Well Name: MARSH

Location: QtrQtr: SESE Section: 22 Township: 12N Range: 53W Meridian: 6

County: LOGAN Federal, Indian or State Lease Number: 33400

Field Name: POW WOW Field Number: 70000

Notice of Intent to Abandon       Subsequent Report of Abandonment

*Only Complete the Following Background Information for Intent to Abandon*

Latitude: 40.994620 Longitude: -103.269980

GPS Data:  
Date of Measurement: 09/03/2010 PDOP Reading: 1.8 GPS Instrument Operator's Name: Duane Russell

Reason for Abandonment:  Dry  Production for Sub-economic  Mechanical Problems  
 Other \_\_\_\_\_

Casing to be pulled:  Yes  No Estimated Depth: 2000

Fish in Hole:  Yes  No If yes, explain details below

Wellbore has Uncemented Casing leaks:  Yes  No If yes, explain details below

Details: \_\_\_\_\_

**Current and Previously Abandoned Zones**

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
J SAND	5388	5402	08/01/2015		

Total: 1 zone(s)

**Casing History**

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF	12+1/2	8+5/8	24	124	30	124	0	VISU
1ST	6+7/8	5+1/2	14	5,468	25	5,468	2,200	CALC

## Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 5350 with 2 sacks cmt on top. CIBP #2: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
 CIBP #3: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #4: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
 CIBP #5: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 40 sks cmt from 1980 ft. to 2200 ft. Plug Type: STUB PLUG Plug Tagged:   
 Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:   
 Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:   
 Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:   
 Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged:

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
 Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
 Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth  
(Cast Iron Cement Retainer Depth)

Set 60 sacks half in. half out surface casing from 0 ft. to 175 ft. Plug Tagged:   
 Set \_\_\_\_\_ sacks at surface  
 Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker:  Yes  No  
 Set \_\_\_\_\_ sacks in rat hole Set \_\_\_\_\_ sacks in mouse hole

### Additional Plugging Information for Subsequent Report Only

Casing Recovered: \_\_\_\_\_ ft. of \_\_\_\_\_ inch casing Plugging Date: \_\_\_\_\_  
 \*Wireline Contractor: \_\_\_\_\_ \*Cementing Contractor: \_\_\_\_\_  
 Type of Cement and Additives Used: \_\_\_\_\_  
 Flowline/Pipeline has been abandoned per Rule 1103  Yes  No \*ATTACH JOB SUMMARY

Technical Detail/Comments:  

See attachment for wellbore diagram and proposed procedure.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Dave Peterson  
 Title: President Date: 8/18/2015 Email: davep@flatironenergy.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: SUTPHIN, DIRK Date: 8/26/2015

**CONDITIONS OF APPROVAL, IF ANY:** \_\_\_\_\_ Expiration Date: 2/25/2016

COA Type	Description
	1) Provide 48 hour notice of MIRU via electronic Form 42. 2) Stub plug: If casing is not recovered or stub plug is deeper than 4000', perf and squeeze 40 sacks cement between 2500' - 1400', (for aquifer protection) 3) Shoe plug: Tag 50' above surface casing shoe and top out from 50' to surface, (if cement falls).

## Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
400885812	FORM 6 INTENT SUBMITTED
400885832	WELLBORE DIAGRAM

Total Attach: 2 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Wellbore Diagram attachment includes proposed, current and plugging procedure.	8/19/2015 7:59:15 AM

Total: 1 comment(s)