

Bruton 30-09E Mesa County, Colorado DRILLING PROGNOSIS

Surface Location

SW/4 of NE/4
Section 30 T9S R93W 6th P.M.
Graded Elevation 7643' MSL
RKB Elevation 7665' (22' KB Patterson 306)

SHL Geographical Coordinates (NAD-83)

Slot B-8
Latitude 39.248163889° N
Longitude 107.808930556° W

Directional Target

50-ft radius cylinder centered on BHL
From estimated top of gas (TOG) to TD

BHL Geographical Coordinates (NAD-83)

Latitude 39.249372222° N
Longitude 107.805408333° W

Casing OD	Hole Size	Weight	Condition	Grade	Coupling	Setting Depth (MD)	Top of Cement
16"	26"	¾" WT	New	-	Welded	40-ft BGL	surface
8-5/8"	11"	24 ppf	New	J-55	STC	1546-ft	surface
4-1/2"	7-7/8"	11.6 ppf	New	I-80	LTC	7912-ft	1022-ft

Cementing Details

8-5/8" Surface Casing

Halliburton Name
Type
Additives
Planned top
Density (ppg)
Yield (cf/sx)
Volume (sx)
Volume (bbls)

Lead

VariCem GJ5
Extended
Pol-E-Flake
Surface
12.30
2.45
192
84

Tail

VariCem GJ5
Extended
Pol-E-Flake
1000-ft
12.80
2.17
114
44

4-1/2" Production Casing

Halliburton Name
Type
Additives
Planned top
Density (ppg)
Yield (cf/sx)
Volume (sx)
Volume (bbls)

Lead

VersaCem
50:50 Poz:G
Pol-E-Flake, Kol-Seal
1022-ft
12.80
1.75
909
284

Tail

ExpandaCem
50:50 Poz:G
Silica Flour, Pol-E-Flake, Kol-Seal
5712-ft
13.30
1.89
414
139

Formation Tops (Sd = Sand; Sh = Shale; SW = salt water)

Name	MD (ft)	TVD (ft)	Description	Expected Pore Pressure (ppg)	Planned Mud Weight (ppg)
Wasatch	-	G.L.	Sd/Sh; freshwater to 500'	8.3	8.5 - 8.8
'G' Sand	2802	2750	Sd/Sh; gas	8.8	9.0 - 9.3
Williams Fork	4695	4600	Sd/Sh; gas & SW	8.8	9.0 - 9.3
Top of Gas	5912	5800	Sd/Sh; gas & SW	8.8 - 9.2	9.0 - 9.5
Cameo	7012	6900	Sd/Sh/Coals; gas & condensate	8.8 - 9.2	9.0 - 9.5
Base Cameo Coal	7670	7558	Sd/Sh/Coals; gas & condensate	8.8 - 9.2	9.0 - 9.5
Rollins	7712	7600	Sd/Sh; gas, condensate & SW	9.0 - 9.5	9.3 - 9.7
Total Depth	7912	7800	Sd/Sh; gas, condensate & SW	9.0 - 9.5	9.5 - 9.7

BOP : 11" 5M Double Gate & 11" 5M Annular Preventer, Rotating Head