



Service Order #: 18661

Date: 12-Aug-15

Well Name	Location	County	St	API#		
STATE KOMATZ 1-36	36-2S-50W	WASHINGTON	CO			
Formation	Cement Via	Type Of Service	Well Type	Age	AFE#	PO#
	CASING	ANNULAR FILL	OIL	REWORK		

Customer: STELBAR OIL CORPORATION

155 NORTH MARKET, STE. 500
WICHITA KS 67202

Remarks: 150 SKS, 30 BBLS
CMT 540'-590' CASING
0'-590' ANNULUS

Customer Rep: TYSON

PH:

WELLBORE DATA				
Type	Size	Weight	Depth	Volume
Surface Casing:	8.625	24.0	590.0	
Production Casing:	4.500	10.5	590.0	
Intermediate:				
Drill Pipe:				
Tubing:				

Type	Size	Depth (Top)	Depth (Bot)	Volume
Liner:				
Open Hole:				

OTHER DATA		
BHT	Max PSI	Total Depth
120	250	590.0

Packer or RetainerType / Depth:

--	--

Perf Depths: # Total

590.0			

TIME	PUMP RATES		DENSITY	PRESS	STG TOT	TOTAL	REMARKS
	WATER (gpm)	PUMP (bpm)	(lb/gal)	(psi)	(bbbls)	(bbbls)	
14:02	52	0.0	8.22	35		0.0	BREAK CIRCULATION
14:03	52	1.6	14.18	59		0.9	MIX CMT @ 15.2 PPG
14:17	0	2.9	14.80	88		40.5	14:17:20
14:17	0	3.0	14.76	77		40.5	14:17:21
14:23	0	0.0	10.27	35		42.0	START DISPLACEMENT
14:29	0	0.0	10.24	11		48.8	CIRC CMT. TO RETURN TANK

Summary

Max Fl. Rate	Avg Fl. Rate	Max Psi	Avg Psi
3.0	2.5	258	83

Customer Acknowledgement:

Service Rating:

- ☐ Satisfactory
☐ Unsatisfactory

Cementer:

KEVEN / ADAM

PRODUCTS USED

150 SKS 60/40 POZ

STELBAR OIL CORP.

STATE KOMATZ 1-36



