

State of Colorado  
Oil and Gas Conservation Commission  
1120 Lincoln Street, Suite 801, Denver, Colorado 80203  
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:  
400878162  
**(SUBMITTED)**

APPLICATION FOR PERMIT TO:

☒ Drill ☐ Deepen ☐ Re-enter ☐ Recomplete and Operate

TYPE OF WELL OIL ☒ GAS ☐ COALBED ☐ OTHER ☐  
Refilling ☐  
ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐  
Sidetrack ☐

Date Received:

Well Name: Silverback Well Number: 1  
Name of Operator: EXTRACTION OIL & GAS LLC COGCC Operator Number: 10459  
Address: 370 17TH STREET  
City: DENVER State: CO Zip: 80202  
Contact Name: Jennifer Grosshans Phone: (303)928-7128 Fax: (303)218-5678  
Email: regulatory@petro-fs.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20130028

WELL LOCATION INFORMATION

QtrQtr: NWNW Sec: 36 Twp: 12N Rng: 62W Meridian: 6  
Latitude: 40.972554 Longitude: -104.272579  
Footage at Surface: 300 feet FNL/FSL FNL 1307 feet FEL/FWL FWL  
Field Name: WILDCAT Field Number: 99999  
Ground Elevation: 5283 County: WELD  
GPS Data:  
Date of Measurement: 06/24/2015 PDOP Reading: 2.1 Instrument Operator's Name: Buster Rainwater  
If well is ☐ Directional ☒ Horizontal (highly deviated) **submit deviated drilling plan.**  
Footage at Top of Prod Zone: FNL/FSL FEL/FWL Bottom Hole: FNL/FSL FEL/FWL  
300 FNL 660 FWL 300 FSL 660 FWL  
Sec: 36 Twp: 12N Rng: 62W Sec: 1 Twp: 11N Rng: 62W

LOCATION SURFACE & MINERALS & RIGHT TO CONSTRUCT

Surface Ownership: ☐ Fee ☒ State ☐ Federal ☐ Indian

The Surface Owner is: ☒ is the mineral owner beneath the location.  
(check all that apply) ☒ is committed to an Oil and Gas Lease.  
☒ has signed the Oil and Gas Lease.  
☐ is the applicant.

The Mineral Owner beneath this Oil and Gas Location is: ☐ Fee ☒ State ☐ Federal ☐ Indian

The Minerals beneath this Oil and Gas Location will be developed by this Well: Yes

The right to construct the Oil and Gas Location is granted by: oil and gas lease

Surface damage assurance if no agreement is in place: Surface Surety ID:

## LEASE INFORMATION

Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)

Township 12 North, Range 62 West of the 6th P.M.  
Section 36: ALL

Total Acres in Described Lease: 640 Described Mineral Lease is: ☐ Fee ☒ State ☐ Federal ☐ Indian

Federal or State Lease # 8754.5

Distance from Completed Portion of Wellbore to Nearest Lease Line of described lease: 0 Feet

## CULTURAL DISTANCE INFORMATION

Distance to nearest:

Building: 1030 Feet  
Building Unit: 1190 Feet  
High Occupancy Building Unit: 5280 Feet  
Designated Outside Activity Area: 5280 Feet  
Public Road: 286 Feet  
Above Ground Utility: 1502 Feet  
Railroad: 5280 Feet  
Property Line: 300 Feet

### INSTRUCTIONS:

- All measurements shall be provided from center of the Proposed Well to nearest of each cultural feature as described in Rule 303.a.(5).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

## DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a: ☐ Buffer Zone  
☐ Exception Zone  
☐ Urban Mitigation Area

- Buffer Zone - as described in Rule 604.a.(2), within 1,000' of a Building Unit
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: \_\_\_\_\_

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: \_\_\_\_\_

## SPACING and UNIT INFORMATION

Distance from Completed Portion of Wellbore to Nearest Wellbore Permitted or Completed in the same formation: 1320 Feet

Distance from Completed Portion of Wellbore to Nearest Unit Boundary 600 Feet (Enter 5280 for distance greater than 1 mile.)

Federal or State Unit Name (if appl): \_\_\_\_\_ Unit Number: \_\_\_\_\_

## SPACING & FORMATIONS COMMENTS

Distance from Completion portion of wellbore to nearest wellbore permitted or completed in the same formation is Silverback 3.

Codell - Unit Configuration:

T12N, R62W: Sec 36 - All

T11N, R62W: Sec 1 - All

Pending Spacing Order Docket Number 150900546.

## OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
CODELL	CODL		1280	All:36 12 62-1 11 62

## DRILLING PROGRAM

Proposed Total Measured Depth: 17643 Feet

Distance to nearest permitted or existing wellbore penetrating objective formation: 879 Feet (Including plugged wells)

Will a closed-loop drilling system be used? Yes

Is H<sub>2</sub>S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No (If Yes, attach an H<sub>2</sub>S Drilling Operations Plan)

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? Yes

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☒ Rotating Head ☐ None

## GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 609

## DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Methods: Commercial Disposal

Cuttings Disposal: ONSITE Cuttings Disposal Method: Other

Other Disposal Description:

See comments for additional disposal information.  
Extraction Windsor Land Application COGCC Facility 433752 will be used for offsite disposal.

Beneficial reuse or land application plan submitted? Yes

Reuse Facility ID: 433752 or Document Number:

## CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	24	16	42	0	80	100	80	0
SURF	12+1/4	9+5/8	36	0	1500	400	1500	0
1ST	7+7/8	5+1/2	20	0	17643	1650	17643	1500

☐ Conductor Casing is NOT planned

## DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- ☐ Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- ☐ Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- ☐ Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- ☐ Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

## GREATER WATTENBERG AREA LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318A.a. Exception Location (GWA Windows).
- ☐ Rule 318A.c. Exception Location (GWA Twinning).

## RULE 502.b VARIANCE REQUEST

☐ Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number

## OTHER LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318.c. Exception Location from Rule or Spacing Order Number \_\_\_\_\_
- ☐ Rule 603.a.(2) Exception Location (Property Line Setback).

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

## OPERATOR COMMENTS AND SUBMITTAL

Comments Drill cuttings will either be hauled off site by a licensed third party transporter to be re-used by land application on COGCC approved land-farms, or recycled and re-used on location using Bio-Remediation. See attached Waste Management Plan. A Form 4 Sundry will be filed once a disposal method is decided. If land spreading is utilized, then a signed Surface Owner agreement will be submitted with the Form 4 Sundry.

Nearest permitted or existing wellbore penetrating objective formation is Silverback 2.

Pending Spacing Order Docket Number 150900546 to modify Order Number 421-44.

This application is in a Comprehensive Drilling Plan \_\_\_\_\_ CDP #: \_\_\_\_\_

Location ID: \_\_\_\_\_

Is this application being submitted with an Oil and Gas Location Assessment application? \_\_\_\_\_ Yes

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Jennifer Grosshans

Title: Regulatory Analyst Date: \_\_\_\_\_ Email: regulatory@petro-fs.com

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: \_\_\_\_\_ Director of COGCC Date: \_\_\_\_\_

Expiration Date: \_\_\_\_\_

API NUMBER

05

## Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

## Best Management Practices

No	BMP/COA Type	Description
1	Pre-Construction	Anti-collision: Operator will perform an anti-collision evaluation of all active (producing, shut in, or temporarily abandoned) offset wellbores that have the potential of being within 150 feet of a proposed well prior to drilling operations for the proposed well. Notice shall be given to all offset operators prior to drilling.
		Identification of plugged and abandoned wells will be identified pursuant to 319.a.(5).
2	General Housekeeping	Visual Impacts: Equipment, regardless of construction date, which are observable from any public highway shall be painted with uniform, non-contrasting, non-reflective color tones (similar to the Munsell Soil Color Coding System), and with colors matched to, but slightly darker than, the surrounding landscape.



3	Dust control	Operator shall employ practices for control of fugitive dust caused by their operations. Such practices shall include but are not limited to the use of speed restrictions, regular road maintenance, restriction of construction activity during high- wind days, and silica dust controls when handling sand used in hydraulic fracturing operations. Additional management practices such as road surfacing, wind breaks and barriers may be used.
4	Emissions mitigation	805.b.(3)A. Green completion practices are not required for this area as it is considered exploratory. If it is determined that the wells will produce gas in economic quantities, then Extraction will negotiate with nearby midstream operators to connect to their gas sales line.
5	Odor mitigation	Equipment shall be operated in such a manner that odors and dust do not constitute a nuisance or hazard to public welfare.
6	Drilling/Completion Operations	One of the first wells drilled on the pad will be logged with openhole Resistivity Log and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which openhole logs were run.

7	Drilling/Completion Operations	<p>A closed –loop system will be used for drilling operations.</p> <p>Blowout Prevention Equipment (“BOPE”): A double ram and annular preventer will be used during drilling. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid.</p> <p>Bioremediation of Drill Cuttings</p> <p>1. Mixing and Treatment:</p> <p>A. All cuttings shall be mixed on location</p> <p>B. Cuttings shall be mixed with additives. The amount of additives shall be determined based on laboratory analysis of untreated cuttings.</p> <p>C. Mixing shall be performed with equipment to ensure contact between the cuttings and additives</p> <p>D. Additives</p> <p>i. CMC – polymer absorbent, non-toxic, non-hazardous</p> <p>ii. Oppenheimer Piranha – bioremediation of hydrocarbons</p> <p>iii. Water soluble calcium – chemical reduction of SAR</p> <p>2. Stockpile Management:</p> <p>A. Treated, solidified cuttings shall be stored on location in individual well stockpiles. One stockpile per well. Each stockpile shall be marked with the name of the well.</p> <p>B. Stockpiles shall be windrows with a height as tall as practical. Taller windrows aid in the retention of warmth increasing microbial activity</p> <p>C. Leachate shall be managed by absorbent material. The inherent properties of CMC reduces leachate levels of TDS to below standards based on laboratory analysis.</p> <p>D. An earthen berm, one foot in height, shall be constructed around the stockpile(s) to minimize storm water runoff</p> <p>E. As the solidified cuttings dry, a protective crust layer will form on the surface of the stockpile. This crust layer helps retain moisture and heat within the stockpile while also protecting the native landscape from windborne contaminated particulate. Care shall be taken by the Operator and all contractors to minimize stockpile disturbance until a properly trained soil sampling technician visits the site.</p> <p>3. Sampling &amp; Testing:</p> <p>A. The stockpile of treated cuttings will be sampled and tested according to standard laboratory and sampling protocols and COGCC table 910-1. Stockpiles will be sampled in increments no greater than 100 cubic yards. Ten samples shall be taken from each segment of the stockpile of treated drill cuttings, mixed and then one composite sample will be used for testing. Samples will be taken from the stockpile in such as way as to preserve any potential volatile organic compounds. Ten random samples shall be taken of the stockpile of subsoil for use as a source for background data.</p> <p>B. After the cuttings have achieved the threshold limits specified in table 910-1, the treated material will be thin spread on the well site and incorporated into the reclamation fill material.</p> <p>A permanent record of the laboratory analysis shall be maintained by the Operator.</p>
8	Final Reclamation	<p>Within 90 days subsequent to the time of plugging and abandonment of the entire site, superfluous debris and equipment shall be removed from the site. The Operator shall restore the surface of the Land affected by such terminated operations as near as possible to the previous state that existed prior to operations.</p>

Total: 8 comment(s)

### **Attachment Check List**

Att Doc Num	Name
400891130	WELL LOCATION PLAT
400891742	DEVIATED DRILLING PLAN
400891743	DIRECTIONAL DATA

Total Attach: 3 Files

## General Comments

User Group

Comment

Comment Date

--	--	--

Total: 0 comment(s)

