

FORM  
2A

Rev  
08/13

# State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203  
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400885770

**(SUBMITTED)**

Date Received:

## Oil and Gas Location Assessment

New Location     Refile     Amend Existing Location    Location#: \_\_\_\_\_

Submit signed original form. This Oil and Gas Location Assessment is to be submitted to the COGCC for approval prior to any ground disturbance activity associated with oil and gas operations. Approval of this Oil and Gas Location Assessment will allow for the construction of the below specified Location; however, it does not supersede any land use rules applied by the local land use authority. Please see the COGCC website at <http://cogcc.state.co.us/> for all accompanying information pertinent this Oil and Gas Location Assessment.

Location ID:

Expiration Date:

This location assessment is included as part of a permit application.

### CONSULTATION

- This location is included in a Comprehensive Drilling Plan. CDP # \_\_\_\_\_
- This location is in a sensitive wildlife habitat area.
- This location is in a wildlife restricted surface occupancy area.
- This location includes a Rule 306.d.(1)A.ii. variance request.

### Operator

Operator Number: 10110  
 Name: GREAT WESTERN OPERATING COMPANY LLC  
 Address: 1801 BROADWAY #500  
 City: DENVER      State: CO      Zip: 80202

### Contact Information

Name: Allison Linz  
 Phone: (303) 398-0355  
 Fax: ( )  
 email: regulatorypermitting@gwogco.com

### RECLAMATION FINANCIAL ASSURANCE

- Plugging and Abandonment Bond Surety ID: 20090080       Gas Facility Surety ID: \_\_\_\_\_  
 Waste Management Surety ID: \_\_\_\_\_

### LOCATION IDENTIFICATION

Name: Leffler FE Pad      Number: 20-019HN  
 County: WELD  
 Quarter: NENE    Section: 21    Township: 6N    Range: 66W    Meridian: 6    Ground Elevation: 4751

Define a single point as a location reference for the facility location. When the location is to be used as a well site then the point shall be a well location.

Footage at surface: 972 feet FNL from North or South section line  
215 feet FEL from East or West section line

Latitude: 40.478486      Longitude: -104.774133

PDOP Reading: 1.2      Date of Measurement: 04/21/2015

Instrument Operator's Name: Dallas Nielsen



## DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Method: Commercial Disposal

Cutting Disposal: OFFSITE Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted? No

Reuse Facility ID: \_\_\_\_\_ or Document Number: \_\_\_\_\_

Centralized E&P Waste Management Facility ID, if applicable: \_\_\_\_\_

## SURFACE & MINERALS & RIGHT TO CONSTRUCT

Name: Donn Leffler Phone: \_\_\_\_\_

Address: 14492 Highway 392 Fax: \_\_\_\_\_

Address: \_\_\_\_\_ Email: \_\_\_\_\_

City: Greely State: CO Zip: 80631

Surface Owner:  Fee  State  Federal  Indian

Check all that apply. The Surface Owner:  is the mineral owner

is committed to an oil and Gas Lease

has signed the Oil and Gas Lease

is the applicant

The Mineral Owner beneath this Oil and Gas Location is:  Fee  State  Federal  Indian

The Minerals beneath this Oil and Gas Location will be developed from or produced to this Oil and Gas Location: Yes

The right to construct this Oil and Gas Location is granted by: oil and gas lease

Surface damage assurance if no agreement is in place: \_\_\_\_\_ Surface Surety ID: \_\_\_\_\_

Date of Rule 306 surface owner consultation \_\_\_\_\_

## CURRENT AND FUTURE LAND USE

Current Land Use (Check all that apply):

Crop Land:  Irrigated  Dry land  Improved Pasture  Hay Meadow  CRP

Non-Crop Land:  Rangeland  Timber  Recreational  Other (describe): \_\_\_\_\_

Subdivided:  Industrial  Commercial  Residential

Future Land Use (Check all that apply):

Crop Land:  Irrigated  Dry land  Improved Pasture  Hay Meadow  CRP

Non-Crop Land:  Rangeland  Timber  Recreational  Other (describe): \_\_\_\_\_

Subdivided:  Industrial  Commercial  Residential

## CULTURAL DISTANCE INFORMATION

Provide the distance to the nearest cultural feature as measured from Wells or Production Facilities onsite.

	From WELL	From PRODUCTION FACILITY
Building:	916 Feet	458 Feet
Building Unit:	967 Feet	449 Feet
High Occupancy Building Unit:	5280 Feet	5280 Feet
Designated Outside Activity Area:	5280 Feet	5280 Feet
Public Road:	202 Feet	145 Feet
Above Ground Utility:	236 Feet	180 Feet
Railroad:	5280 Feet	5280 Feet
Property Line:	215 Feet	159 Feet

### INSTRUCTIONS:

- All measurements shall be provided from center of nearest Well or edge of nearest Production Facility to nearest of each cultural feature as described in Rule 303.b.(3)A.
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.
- For measurement purposes only, Production Facilities should only include those items with an asterisk(\*) on the Facilities Tab.

## DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a:

Buffer Zone

Exception Zone

Urban Mitigation Area

- Buffer Zone - as described in Rule 604.a.(2), within 1,000' of a Building Unit.
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: \_\_\_\_\_

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: 07/21/2015

## FOR MULTI-WELL PADS AND PRODUCTION FACILITIES WITHIN DESIGNATED SETBACK LOCATIONS ONLY:

- Check this box if this Oil and Gas Location has or will have Production Facilities that serve multiple wells (onl or offsite) and the Production Facilities are proposed to be located less than 1,000 feet from a Building Unit. *(Pursuant to Rule 604.c.(2)E.i., the operator must evaluate alternative locations for the Production Facilities that are farther from the Building Unit, and determine whether those alternative locations were technically feasible and economically practicable for the same proposed development.)*
- By checking this box, I certify that no alternative placements for the Production Facilities, farther from the nearest Building Unit, were available based on the analysis conducted pursuant to Rule 604.c.(2)E.i.

In the space below, explain rationale for siting the multi-well Production Facility(ies) that supports your Rule 604.c.(2)E.i determination. Attach documentation that supports your determination to this Form 2A.

Please see attached placement rationale.

## SOIL

List all soil map units that occur within the proposed location. attach the National Resource Conservation Service (NRCS) report showing the "Map Unit Description" report listing the soil typical vertical profile. This data is to used when segregating topsoil.

The required information can be obtained from the NRCS web site at <http://soildatamart.nrcs.usda.org/> or from the COGCC web site GIS Online map page found at <http://colorado.gov/cogcc>. Instructions are provided within the COGCC web site help section.

NRCS Map Unit Name: Kim Loam 1 to 3 percent Slopes. 32

NRCS Map Unit Name: Olney Fine Sandy Loam 1 to 3 percent slopes. 47

NRCS Map Unit Name: Kim Loam, 3 to 5 percent slopes. 33

**PLANT COMMUNITY:**

Complete this section only if any portion of the disturbed area of the location's current land use is on non-crop land.

Are noxious weeds present: Yes  No

Plant species from:  NRCS or,  field observation Date of observation: \_\_\_\_\_

List individual species:

Check all plant communities that exist in the disturbed area.

- Disturbed Grassland (Cactus, Yucca, Cheatgrass, Rye)
- Native Grassland (Bluestem, Grama, Wheatgrass, Buffalograss, Fescue, Oatgrass, Brome)
- Shrub Land (Mahogany, Oak, Sage, Serviceberry, Chokecherry)
- Plains Riparian (Cottonwood, Willow, Aspen, Maple, Poplar, Russian Olive, Tamarisk)
- Mountain Riparian (Cottonwood, Willow, Blue Spruce)
- Forest Land (Spruce, Fir, Ponderosa Pine, Lodgepole Pine, Juniper, Pinyon, Aspen)
- Wetlands Aquatic (Bullrush, Sedge, Cattail, Arrowhead)
- Alpine (above timberline)
- Other (describe): \_\_\_\_\_

**WATER RESOURCES**

Is this a sensitive area:  No  Yes

Distance to nearest

downgradient surface water feature: 449 Feet

water well: 27 Feet

Estimated depth to ground water at Oil and Gas Location 4 Feet

Basis for depth to groundwater and sensitive area determination:

Is the location in a riparian area:  No  Yes

Was an Army Corps of Engineers Section 404 permit filed  No  Yes If yes attach permit.

Is the location within a Rule 317B Surface Water Supply Area buffer zone: No

If the location is within a Rule 317B Surface Water Supply Area buffer have all public water supply systems within 15 miles been notified: \_\_\_\_\_

Is the Location within a Floodplain?  No  Yes Floodplain Data Sources Reviewed (check all that apply)

Federal (FEMA)

State

County

Local

Other

**GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING**

Water well sampling required per Rule 318A

**DESIGNATED SETBACK LOCATION EXCEPTIONS**

Check all that apply:

- Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

**RULE 502.b VARIANCE REQUEST**

- Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number \_\_\_\_\_

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

**OPERATOR COMMENTS AND SUBMITTAL**

Comments

1. The manufacturer of the TLVST is Brewer Steel Company
2. The size of the TLVST is 40,000 BBLs
3. The anticipated time frame the TLVST will be onsite is four weeks.
4. A Construction Layout Drawing depicting the placement of the MLVT's has been attached.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: \_\_\_\_\_ Date: \_\_\_\_\_ Email: regulatorypermitting@gwogco.com  
 Print Name: Allison Linz Title: Regulatory Technician

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: \_\_\_\_\_ Director of COGCC \_\_\_\_\_ Date: \_\_\_\_\_

**Conditions Of Approval**

All representations, stipulations and conditions of approval stated in this Form 2A for this location shall constitute representations, stipulations and conditions of approval for any and all subsequent operations on the location unless this Form 2A is modified by Sundry Notice, Form 4 or an Amended Form 2A.

**Best Management Practices**

No	BMP/COA Type	Description
1	Traffic control	GWOC works closely with all municipalities as appropriate to develop a mutually acceptable road traffic access plan addressing site specific traffic-related issues. These plans may address issues such as; routes, construction specification of access roads, maintenance, dust control, jake brake limits, traffic controls, enforcement, emergency response, etc. GWOC will work with municipalities, the County's Planning Department and/or Road Department to address complaints related to traffic or dust issues as appropriate. Dust control measures may include surface stabilization, or dust control with appropriate chemical or water applications.

2	General Housekeeping	General housekeeping will consist of neat and orderly storage of materials and fluids. Wastes will be temporarily stored in sealed containers and regularly collected and disposed of at offsite, suitable facilities. If spills occur prompt cleanup is required to minimize any commingling of waste materials with storm water runoff. Routine maintenance will be limited to fueling and lubrication of equipment. Drip pans will be used during routine fueling and maintenance to contain spills or leaks. Any waste product from maintenance will be containerized and transported offsite for disposal or recycling. There will be no major equipment overhauls conducted onsite. Equipment will be transported offsite for major overhauls. Cleanup will consist of patrolling the roadways, access areas, and other work areas to pick up trash, scrap debris, other discarded materials, and any contaminated soil. These materials will be disposed of properly and promptly.
3	Storm Water/Erosion Control	Storm Water Management Plans (SWMP) are in place to address construction, drilling and operations associated with Oil and Gas development throughout the state of Colorado in accordance with Colorado Department of Public Health and Environment (CDPHE). Barriers will be constructed around the perimeter of the site prior to construction. Typically, GWOC utilizes a ditch and berm system of storm water control at its sites. BMP's used are determined just prior to construction by a third-party storm water contractor and may vary according to the location. Storm water controls will remain in place until the pad is stabilized or reaches final reclamation.
4	Material Handling and Spill Prevention	Spill Prevention Control and Countermeasures (SPCC) plans in place to address any possible spills associated with Oil and Gas operations throughout the state of Colorado in accordance with CFR 112. In accordance with COGCC Rule 1002.f.(2)A. & B., shall provide a designated storage area for dry bulk chemicals and miscellaneous fluids. The storage area shall be covered to prevent contact of precipitation with chemicals, shall be elevated above storm- or standing water, and shall provide sufficient containment to prevent release of spilled fluids or chemicals from impacting soil, surface water or groundwater and will prevent the co-mingling of spilled fluids or chemicals with other E & P Waste.
5	Noise mitigation	The subject Great Western Operating Company, L.L.C. (GWOC) location will operate in accordance with maximum permissible noise levels per COGCC Rule 604.c.(2)A. and 802, as applicable. GWOC will utilize reasonable and cost-effective best practices to endeavor to reduce noise levels below these limits in areas where occupied structures occur within a Designated Setback Zone. Where possible, drilling rig and completion equipment engine exhaust will be directed away from occupied buildings to assist with noise mitigation. No noise compliance issues are expected from the production area.
6	Odor mitigation	Where possible, drilling rig and completion equipment engine exhaust will be directed away from occupied buildings to assist in mitigating potential odors. Light sources will be directed downwards, and away from occupied structures where possible. While GWOC does not anticipate any mitigation measures will be necessary for odors, sealed tanks with pressure relief valves and emissions controls will be utilized for the production phase. Once the drilling and completion rigs leave the site, there will be no permanently installed lighting on site.
7	Drilling/Completion Operations	Load line containment is a necessary part of a complete secondary containment system. In any designated setback zone all loadlines are capped or bullplugged or locked shut to reduce the likelihood of a release occurring. In addition, GWOC places all load line receivers/valves inside secondary containment areas or in a proper load line containment device or both.
8	Drilling/Completion Operations	All surface debris, trash, unusable scrap, or solid waste from the facility will be properly temporarily stored on location in a secure container and ultimately removed and disposed of in a legal manner.
9	Drilling/Completion Operations	Guy line anchors left buried for future use shall be identified by a brightly colored marker at least 4-feet in height and within 1-foot to the east of the anchor.
10	Drilling/Completion Operations	All newly installed or replaced crude oil and condensate storage tanks shall be designed, constructed, and maintained in accordance with National Fire Protection Association (NFPA) Code 30 (2008 version). GWOC shall maintain written records verifying proper design, construction, and maintenance, and shall make these records available for inspection by the Director. Only the 2008 version of NFPA Code 30 applies to this rule.

11	Drilling/Completion Operations	All access roads are designed, constructed, and maintained such that heavy equipment, including emergency response vehicles, can readily access and exit the location. In addition, GWOC will implement manual mud mitigation measures (eg. tracking control rock aprons) at location exits onto paved roads as necessary and in conjunction with county requirements.
12	Drilling/Completion Operations	GWOC is utilizing a Closed Loop Drilling System on the subject facility. No open pit storage of water is foreseen for this facility. If open pit storage of fresh water is required, a Form 15 will be submitted and approved prior to use of such pit, and appropriate signage and escape provisions will be provided as required. Cuttings and drilling fluids will be removed from location and properly treated or disposed of according to applicable regulations.
13	Drilling/Completion Operations	<p>As applicable, per COGCC Rule 805, GWOC will utilize all reasonable and cost-efficient best practices, including but not limited to those listed in Rule 805, to maximize resource recovery and mitigate releases to the environment.</p> <ul style="list-style-type: none"> <li>• Initial frac and drillout effluent is routed through a sand catcher/trap and a junk/sand tank to remove sand and well frac debris.</li> <li>• Once any hydrocarbons are detected but prior to encountering salable quality combustible gas or significant volumes of liquid hydrocarbons (condensate or oil) (greater than 10 barrels per day average) the effluent is routed through a high-pressure separator and closed-top tanks to minimize emissions to the environment. Hydrocarbon liquids, produced water, and sand are separated utilizing the high-pressure separator.</li> <li>• The quality (combustibility) of the gas is typically monitored directly at the high-pressure separator. When salable (combustible) quality gas is measured/detected the gas stream is immediately diverted to the sales pipeline or the well is shut in or a from 42 for flaring will be submitted for approval.</li> <li>• The separated produced water and hydrocarbon liquids (condensate/oil) are directed to specific tanks for storage until being unloaded and hauled to disposal or sales as appropriate.</li> </ul>
14	Drilling/Completion Operations	GWOC strives to utilize multi-well pads wherever technically and economically practicable to minimize potential impacts to neighbors and the environment. Multi-well pads are not always feasible due to numerous possible issues including but not limited to; landowner requirements, topographic constraints, well bore reaches, setback requirements, etc. This pad will be constructed in such a manner that noise mitigation may be installed and removed without disturbing the site or landscaping. The pad has all weather access roads to allow for operator and emergency response. This pad has been placed as far as possible from building units.
15	Drilling/Completion Operations	GWOC designs its new facilities to both avoid leaks or releases as well as to help detect them in a time-efficient manner to minimize potential impacts. Tanks and all visible pipelines and valves etc. are inspected informally on a daily basis by company lease operators. In addition, GWOC also conducts formal annual SPCC inspections, and formal site specific and random audits, by third-party consultants to inspect for general site conditions as well as condition of tanks, pipelines, and containment structures. In addition, our company lease operators and Production staff review production records, including volumes and pressures, looking for irregularities that may indicate a problem with a tank or pipeline. If an irregularity is detected that may indicate a potential release the suspect tank and/or pipeline(s) are removed from service, isolated, and either pressure tested or visibly inspected for indications of a potential leak.
16	Drilling/Completion Operations	<p>A minimum containment capacity of 150% of the single largest storage vessel inside the containment will be constructed around any liquids storage area within a designated setback zone. For this location, steel containment with sealed liners will be utilized at all storage facilities on this location.</p> <p>Tanks and all visible pipelines and valves etc. will be inspected informally on a daily basis by company lease operators. In addition, GWOC also conducts formal annual SPCC inspections, and formal site specific and random audits, by third-party consultants to inspect for general site conditions as well as condition of tanks, pipelines, and containment structures.</p>

17	Drilling/Completion Operations	A BOPE with a minimum pressure rating of 3,000 psi will be utilized. At a minimum it will consist of 2 ram preventers and 1 annular preventer. The blind rams will be positioned below the pipe rams. A backup system of pressure control will be onsite consisting of at a minimum 1,000 psi accumulator (backup pressure). Accumulator is tested to 1,000 psi. Operator may use fixed sized pipe rams matching the tubular size. The annular preventer will be pressure tested to 250 psi low and 2,000 psi high for 10 minutes each. The ram preventers will be tested to 250 psi low and 2,500 psi high for 10 minutes each. All remaining well control equipment will be tested to 250 psi low and 2,500 psi high for 10 minutes each. The pressure tests will be conducted when the equipment is first installed and every 30 days thereafter. Pipe rams and blind rams will be function tested before every well service operation. Annual BOP inspections and pressure tests will be performed by the service company and will be charted & retained for 1 year. Backup stabbing valves shall be used on operations that require reverse circulation. Valves will be pressure tested before each well service operation in low pressure and high pressure range. The GWOC onsite representative will be certified in Well Control Operations by a Well-Cap certified training service.
18	Drilling/Completion Operations	GWOC does not typically utilize pits in any of its operations. If a pit was to be used proper pit Level indicators would be installed to indicate pit levels and compliance with pit volume rules.
19	Drilling/Completion Operations	Conventional drill stem tests will not be conducted on DJ Basin horizontal wells currently being executed or planned by GWOC. If plans change in the future a well specific drill stem testing plan will be prepared for that particular well. Note that GWOC may elect to use one of several available wireline deployed tools for the purpose of measuring downhole formation pressures and/or collecting downhole fluid samples from the target formation(s) of a particular well.
20	Drilling/Completion Operations	At a minimum GWOC installs appropriate fencing to restrict access by any unauthorized persons. This fencing may vary depending on site-specific situations. Fencing will be properly noted on facility layout diagrams for both drilling/completion and the production phases of operations.
21	Drilling/Completion Operations	GWOC constructs and operates our facilities to meet state and API codes, as appropriate, including API RP 500 electrical classifications inside bermed areas. Any unused potentially flammable materials are moved a minimum distance of 25-feet from wellhead, tanks, and separator areas. In addition, GWOC implements a Hot Work Permit Program for employees and contractors doing any defined 'Hot Work' activities on GWOC locations.
22	Drilling/Completion Operations	GWOC shall identify the location of the P&A wellbore with a permanent monument as specified in Rule 319.a.(5). The operator shall also inscribe or imbed the well number and date of plugging upon the permanent monument. P&A wellbores shall be cutoff well below ground surface in agricultural areas to provide for landowners to safely farm the reclaimed well area.
23	Drilling/Completion Operations	GWOC will comply with the "COGCC Policy for Bradenhead Monitoring during Hydraulic Fracturing Treatments in the Greater Wattenberg Area", dated May 29, 2012
24	Drilling/Completion Operations	One of the first wells drilled on the pad will be logged with open-hole Resistivity and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing id production liner is run) into the surface casing. The horizontal portion of every well will be logging with a measure-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open hole logs shall clearly state "No open-hole logs were run" and shall clearly identify (by API#, well name and number) the well in which open-hole logs were run.
25	Drilling/Completion Operations	Prior to drilling operations, Operator will perform an anti-collision scan of existing offset wells that have the potential of being within close proximity of the proposed well. This anti-collision scan will include definitive MWD or gyro surveys of the offset wells with included error of uncertainty per survey instrument, and compared against the proposed wellpath with its respective error of uncertainty. If current surveys do not exist for the offset wells, Operator may have gyro surveys conducted to verify bottomhole location. The proposed well will only be drilled if the anti-collision scan results indicate that there is not a risk for collision, or harm to people or the environment.

26	Final Reclamation	Within ninety (90) days after a well is plugged and abandoned, the well site shall be cleared of all non-essential equipment, trash, and debris.
27	Final Reclamation	GWOC shall identify the location of the P&A wellbore with a permanent monument as specified in Rule 319.a.(5). The operator shall also inscribe or imbed the well number and date of plugging upon the permanent monument. P&A wellbores shall be cutoff well below ground surface in agricultural areas to provide for landowners to safely farm the reclaimed well area.
28	Planning	CERTIFICATION STATEMENT: Great Western Operating Company certifies that the MLVTs on this location will be designed and implemented consistent with the COGCC Policy on the use of MLVTs in the state of Colorado.

Total: 28 comment(s)

### Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
400886500	ACCESS ROAD MAP
400886501	CONST. LAYOUT DRAWINGS
400886502	HYDROLOGY MAP
400886503	LOCATION DRAWING
400886504	LOCATION PICTURES
400886507	FACILITY LAYOUT DRAWING
400886509	MULTI-WELL PLAN
400886510	REFERENCE AREA MAP
400886511	REFERENCE AREA PICTURES
400886514	TOPO MAP
400886516	SURFACE AGRMT/SURETY
400886517	WASTE MANAGEMENT PLAN
400886760	NRCS MAP UNIT DESC
400886761	NRCS MAP UNIT DESC
400886762	NRCS MAP UNIT DESC
400888119	SITING RATIONALE
400888129	30 DAY NOTICE LETTER

Total Attach: 17 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>

Total: 0 comment(s)