



DRILLING COMPANY, INC. **WICHITA, KANSAS**

Final P&A Wellbore Configuration

| | | |
|---|-------------------|--------------------|
| Cut casing 5' below surface and welded cap on top | | |
| 15 sk plug at surface | Date: | 9/28/2015 |
| | Well Name: | State-Hines #1-16 |
| | Location: | SE SE 16-T13S-R47W |
| | County: | Cheyenne |
| | State: | Colorado |
| | API: | 05-017-06568 |
| | KB: | 4380' |
| | GL: | 4369' |
| | Spud Date: | 9/26/1985 |
| Perfed @ 400' & squeezed with 100 sks. leaving 100' in casing | | |
| Top Dakota @ 1887' | | |
| Perfed @ 1937' & squeezed with 100 sks. leaving 100' in casing | | |
| Top Cheyenne @ 2200' | | |
| Top Morrison @ 2375' (Base of Cheyenne) | | |
| Perfed @ 2425' & squeezed with 100 sks. leaving 100' in casing | | |
| Top of Cement at 4216' (CBL dated 10/12/85) | | |
| Set CIBP at 4850' w/2 sks. cement on top | | |
| Marmaton Perforations at 4875'-4894' (42 holes) | | |
| Dumped 2 sks. cement on top of CIBP | | |
| CIBP set at 4930' | | |
| Morrow Sand Perfs at 5414'-5417' (10 holes) | | |
| 5-1/2", 17# csg set at 5558' | | |
| Cemnted with 175 sks. 50/50 Pozmix | | |