



Client Name Bonanza Creek Energy Operation Co, LLC	Well Name State Antelope B12 - V42 - 2HNC	Rig Craig 4	Job Date June 27,2015	Call Sheet 1058724
Client Representative Mr. Tim Joel	Surface Well Location SW NW Sec 2:T5N:R62W	Down Hole Well Location	Job Type Surface Casing	Lead Supervisor Laeger, Kacey (25046)

Well Profile

Well Type:	Oil
Maximum Treating Pressure (psi):	---
Predicted Bottom Hole Static Temperature (°F):	--- @ --
Bottom Hole Circulating Temperature (°F):	--- @ --
Bottom Hole Logged Temperature (°F):	--- @ --

Open Hole

Size (in)	Excess (%)	TMD From (ft)	TMD To (ft)	TVD From (ft)	TVD To (ft)
13.500	--	0.000	469.000	--	--

Casing

Size (in)	Weight (lb/ft)	Grade	Collapse Pressure (psi)	Internal Yield Pressure (psi)	Capacity (bbl)	I.D. (in)	O.D. (in)	Depth From (ft)	Depth To (ft)
9.625	36.000	J-55	2,020.0	3,520.0	36.26	8.921	10.625	0.0	469.0

Products

Stage 1

From Depth (ft): 0
To Depth (ft): 469

Acids/Blends/Fluids :

Tail: 275 Sacks of 0:1:0 Type III, Density = 14.8 lb/gal, Volume Pumped = 65 (bbl)
Water Temperature(°F) = 55 , Bulk Temperature(°F) = 60 , Slurry Temperature(°F) = 65
+ 1 % of CaCl2 (Preblend),
+ 0.25 lb/sack of Polyflake (Preblend),
+ 0.2 % of CDF-4P (Preblend)

Stage 2

From Depth (ft):
To Depth (ft):

Acids/Blends/Fluids :

Fluid & Cement Data

Expected Cement Top: Surface

Wellbore Fluid

Fluid Type	Viscosity (cP)	Density (lbs/gal)	Yield Point (psi)	Temperature (°F)	Recorded@
Water	--	8.400	--	--	Feb 26, 2015 14:02

Attachment & Tools

Down Hole Tools

Tool Type	Depth (ft)	Supplier
Float Collar	419.000	Third Party

Tubular Plugs

Tubular Plug Type	Size (in)	Supplier
Rubber Top	9.625	Sanjel