Company	EXTRACTION OIL AND GAS
Well	TROUDT 6
Field	WATTENBERG
County	WELD
State	CO

PIONEER
Pioneer Energy Services

DUAL INDUCTION COMPENSATED DENSITY COMPENSATED NEUTRON GAMMA RAY

Company	EXTRACTION OIL AND GAS
Well	TROUDT 6
Field	WATTENBERG
County	WELD State CO

Location: API # : 05-123-41436
SHL: 537' FSL & 1091' FEL SESE
SEC 32 TWP 2N RGE 67W

Other Services
NONE

Permanent Datum	GL	Elevation 5079'
Log Measured From	KB	
Drilling Measured From	KB	

Elevation
K.B. 5099'
D.F. 5098'
G.L. 5079'

Date	AUGUST 12, 2015
Run Number	1
Depth Driller	8284'
Depth Logger	7600'
Bottom Logged Interval	7600'
Top Log Interval	SURFACE CASING
Casing Driller	1554'
Casing Logger	1554'
Bit Size	8.75"
Type Fluid in Hole	OBM
Density / Viscosity	8.8 / 46
pH / Fluid Loss	N/A
Source of Sample	FLOWLINE
Rm @ Meas. Temp	N/A
Rmf @ Meas. Temp	N/A
Rmc @ Meas. Temp	N/A
Source of Rmf / Rmc	N/A
Rm @ BHT	N/A
Time Circulation Stopped	0400
Time Logger on Bottom	1050
Maximum Recorded Temperature	203 F
Equipment Number	52
Location	FT. MORGAN
Recorded By	SHAUN STUMP
Witnessed By	SHAWN MCINTYRE

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Pioneer Wireline Services, LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Pioneer Wireline Services, LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

ANNULAR VOLUMES CALCULATED FOR 5.5" CASING

SAVANNA DRILLING RIG #802

NO REPEAT DUE TO HOLE CONDITIONS
NO FOCUS TOOL DUE TO OIL BASE MUD

THANK YOU FOR USING PIONEER ENERGY SERVICES

SO# 2-013995

Log Variables

Database C:\ProgramData\Warrior\Data\2-013995.db
Dataset field/well/run1/pass2/_vars_

Top - Bottom

SZCOR	NPORSEL	FLUIDDEN g/cc	MATRXDEN g/cc	SPSHIFT mV	SNDERRM mmho/m	SNDERR mmho/m	SRFTEMP degF
Off	Sandstone	1	2.68	107	0	0	0

CASETHCK in	CASEOD in	PERFS	TDEPTH ft	BOTTEMP degF	BOREID in
0	5.5	0	0	203	8.75



Sensor	Offset (ft)
GR	0.00
CNLSC	3.67
CNSSC	4.17
DCAL	11.84
LSD	12.67
SSD	13.17
RLL3	17.52
CILD	24.97
CILM	28.42
SP	32.42

Description	Length (ft)	O.D. (in)	Weight (lb
CHD (~0)	2.00	3.50	30.00
GR-PSI (939)	2.92	3.50	40.00
CNT-PSI (856)	5.00	3.50	70.00
CDL-PSI (998)	8.50	5.00	285.00
DIL-PSI (1011)	18.25	3.75	175.00

Dataset: 2-013995.db: field/well/run1/pass2
Total length: 36.67 ft
Total weight: 600.00 lb
O.D.: 5.00 in

MAIN PASS

Database File 2-013995.db
Dataset Pathname pass2.2
Presentation Format split
Dataset Creation Wed Aug 12 11:54:15 2015
Charted by Depth in Feet scaled 1:600

-0.5 Corr (g/cc) 0.5
7 Density Caliper (in) 17
0 Gamma Ray (GAPI) 200
-150 SP (mV) 250
TBHV (ft3) ABHV (ft3)

2 Deep Resistivity (Ohm-m) 200
2 Medium Resistivity (Ohm-m) 200
2 Shallow Resistivity (Ohm-m) 200

30 Density Porosity (pu) 0
30 Neutron Porosity (pu) 0

-0.5 Corr (g/cc) 0.5
7 Density Caliper (in) 17
0 Gamma Ray (GAPI) 200
-150 SP (mV) 250
TBHV (ft3) ABHV (ft3)

2 Deep Resistivity (Ohm-m) 200
2 Medium Resistivity (Ohm-m) 200
2 Shallow Resistivity (Ohm-m) 200

30 Density Porosity (pu) 0
30 Neutron Porosity (pu) 0

MAIN PASS

Database File 2-013995.db
Dataset Pathname pass2.2
Presentation Format split
Dataset Creation Wed Aug 12 11:54:15 2015
Charted by Depth in Feet scaled 1:240

-0.5 Corr (g/cc) 0.5
7 Density Caliper (in) 17
0 Gamma Ray (GAPI) 200
-150 SP (mV) 250
TBHV (ft3) ABHV (ft3)

2 Deep Resistivity (Ohm-m) 200
2 Medium Resistivity (Ohm-m) 200
2 Shallow Resistivity (Ohm-m) 200

30 Density Porosity (pu) 0
30 Neutron Porosity (pu) 0



2096
1250
2500
2076
1238
2550
2055
1226
2600
2035
1214
2650
2015
1202
2700
1995
1190
2750
1975
1178
2800
1954
1166
2850
1934
1154
2900
1914
1142
2950
1894
1130
3000
1873
1118
3050
1853
1106
3100
1833
1094
3150
1813
1082
3200
1793
1070
3250
1772
1058
3300
1752
1046
3350
1732
1034
3400
1712
1022
3450
1691
1010
3500
1671
998
3550
1651
986
3600
1630
974
3650
1610
962
3700
1590
950
3750
1569
938
3800
1549
926
3850
1529
914
3900
1508
901
3950
1488
889
4000
1467
877
4050
1447
865
4100
1426
853
4150
1406
840
4200
1385
828
4250
1365
816
4300
1344
804
4350
1324
792
4400
1304
780
4450
1283
768
4500
1263
755
4550
1243
743
4600
1222
731
4650
1202
719
4700
1182
707
4750
1161
695
4800
1141
682
4850
1120
670
4900
1100
658
4950
1079
646
5000
1058
633
5050
1038
621
5100
1017
609
5150
997
596
5200
976
584
5250
956
572
5300
936
560
5350
915
547
5400
894
535
5450
873
522
5500
852
509
5550
831
497
5600
811
485
5650
790
472
5700
769
459
5750
748
447
5800
728
435
5850
707
422
5900
686
409
5950
665
397
6000
644
384
6050
623
371
6100
602
358
6150
581
346
6200
560
333
6250
539
320
6300
518
308
6350
498
295
6400
476
282
6450



Pioneer Energy Services

MAIN PASS

Database File 2-013995.db
Dataset Pathname pass2.2
Presentation Format cdl
Dataset Creation Wed Aug 12 11:54:15 2015
Charted by Depth in Feet scaled 1:240

Calibration Report

Database File 2-013995.db
Dataset Pathname pass2
Dataset Creation Wed Aug 12 10:25:23 2015

Dual Induction Calibration Report

Serial-Model: 1011-PSI
Surface Cal Performed:

	Readings		References			Results	
Loop:	Air	Loop	Air	Loop		m	b
Deep	0.000	1.000	0.000	1.000	mmho/m	0.580	-28.000
Medium	0.000	1.000	0.000	1.000	mmho/m	0.490	-21.000

Compensated Density Calibration Report

Serial-Model: 998-PSI
Source / Verifier: 52 / PSI
Master Calibration Performed: Thu Jul 30 13:50:47 2015
Before Survey Verification Performed:
After Survey Verification Performed:

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.750	g/cc	5781.01	7666.81	cps
Aluminum	2.690	g/cc	1082.67	4886.43	cps

Spine Angle = 74.95 Density/Spine Ratio = 0.542

	Size		Reading
Small Ring	6.20	in	1.67
Large Ring	19.85	in	1.38

Compensated Neutron Calibration Report

Serial Number: 856
Tool Model: PSI

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.9000
Long Space	1.00	cps	1.00	cps	2.1500

Gamma Ray Calibration Report

Serial Number: 939
Tool Model: PSI
Performed: Thu Jul 30 13:50:58 2015

Calibrator Value: 150.0 GAPI

Background Reading: 45.0 cps
Calibrator Reading: 295.0 cps

Sensitivity: 0.6000 GAPI/cps

PIONEER
Pioneer Energy Services

Company	EXTRACTION OIL AND GAS
Well	TROUDT 6
Field	WATTENBERG
County	WELD
State	CO