

### **Attachment #1 – Wellbore Diagram**

|  |   |
|--|---|
| <b>EnCana Oil &amp; Gas (USA) Inc.</b>           |   |
| <b>Well :</b>                                    | <b>Gittlein 12-4</b>                      |
| <b>Field :</b>                                   | <b>Wattenberg</b>                         |
| <b>County :</b>                                  | <b>Weld State : Colorado</b>              |
| <b>Surface :</b>                                 | <b>Lat: 40.0832790 Long: -104.6717610</b> |
| <b>: 1659 FNL, 1682 FWL NWSNW Sec 4 T1N R65W</b> |   |
| <b>API # :</b>                                   | <b>05-123-21042</b>                       |
| <b>Grd Elev :</b>                                | <b>4910' GR KB Elevation: 4927' KB</b>    |

**Log Tops:**

|                |       |
|----------------|-------|
| Fox Hills Base | 904'  |
| Sussex         | 4452' |
| Niobrara       | 7135' |
| Codell         | 7477' |
| J Sand         | 7926' |
| Dakota         | 8123' |

**Surface Casing**  
8-5/8" 24# Surface Casing  
set @ 1025', cmt'd w/ 420 sx

TOC @ 6880'  
CBL 09/09/02

**Production Casing**  
4-1/2" 11.6# IPSCO I-80 production casing set @ 8241'. Cmt w/ 240 sx

**Production Tubing**  
2-3/8" Tubing set @ 7912'  
257 jts

**J Sand Perfs**  
7930'-7938', 7948'-7654', 7958'-7964', 7970'-  
7974' w/ 2 SPF  
Frac'd with 121,296 gal CWS-500 gel and  
350,000# 20/40 sand (10/22/02)

**Dakota Perfs**  
8126'-8129', 8145'-8158', 8164'-8170' w/ 2 SPF  
Frac'd with 36,858 gal Dynaflo-2 gel and 6,000#  
100 mesh sand, 40,000# 20/40 sand, and 10,000#  
ACFRAC PR-6000 20/40 (09/12/02)

PBTD 8220'

TD 8241'

**Well History:**  
  
 Spud 07/31/02  
 TD 08/07/02

# **Attachment #2 – Proposed Wellbore Diagram**

