

FORM

2

Rev
08/13

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109

Document Number:

400799579

APPLICATION FOR PERMIT TO:

☒ Drill
 ☐ Deepen
 ☐ Re-enter
 ☐ Recomplete and Operate

Date Received:

06/16/2015

TYPE OF WELL OIL ☒ GAS ☐ COALBED ☐ OTHER _____Refiling ☐ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐Sidetrack ☐

Well Name: Ivey

Well Number: H-11-2HN

Name of Operator: SYNERGY RESOURCES CORPORATION

COGCC Operator Number: 10311

Address: 20203 HIGHWAY 60

City: PLATTEVILLE State: CO Zip: 80651

Contact Name: Erin Ekblad

Phone: (303)942-0506

Fax: ()

Email: eekblad@syrginfo.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20090043

WELL LOCATION INFORMATION

QtrQtr: SWSE Sec: 11 Twp: 1S Rng: 68W Meridian: 6

Latitude: 39.975058

Longitude: -104.965558

Footage at Surface: 1105 feet FNL/FSL FSL 1720 feet FEL/FWL FEL

Field Name: SPINDLE

Field Number: 77900

Ground Elevation: 5108

County: ADAMS

GPS Data:

Date of Measurement: 05/07/2014 PDOP Reading: 2.5 Instrument Operator's Name: Owen McKee

If well is ☐ Directional ☒ Horizontal (highly deviated) submit deviated drilling plan.

Footage at Top of Prod Zone: FNL/FSL FEL/FWL Bottom Hole: FNL/FSL FEL/FWL

 1785 FSL 2472 FWL 465 FNL 2446 FWL
 Sec: 11 Twp: 1S Rng: 68W Sec: 2 Twp: 1S Rng: 68W

LOCATION SURFACE & MINERALS & RIGHT TO CONSTRUCT

Surface Ownership: ☒ Fee ☐ State ☐ Federal ☐ IndianThe Surface Owner is: ☒ is the mineral owner beneath the location.

(check all that apply)

☒ is committed to an Oil and Gas Lease.☒ has signed the Oil and Gas Lease.☐ is the applicant.The Mineral Owner beneath this Oil and Gas Location is: ☒ Fee ☐ State ☐ Federal ☐ Indian

The Minerals beneath this Oil and Gas Location will be developed by this Well: No

The right to construct the Oil and Gas Location is granted by: Surface Use Agreement

Surface damage assurance if no agreement is in place:

Surface Surety ID:

LEASE INFORMATION

Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)

T1S R68W Sec. 11: N/2SE/4, NE/4, N/2NW/4; Section 12: NW/4

Total Acres in Described Lease: 480 Described Mineral Lease is: ☒ Fee ☐ State ☐ Federal ☐ Indian

Federal or State Lease # _____

Distance from Completed Portion of Wellbore to Nearest Lease Line of described lease: 0 Feet

CULTURAL DISTANCE INFORMATION

Distance to nearest:

Building: 2606 Feet
Building Unit: 2606 Feet
High Occupancy Building Unit: 3296 Feet
Designated Outside Activity Area: 5280 Feet
Public Road: 569 Feet
Above Ground Utility: 2049 Feet
Railroad: 4820 Feet
Property Line: 217 Feet

INSTRUCTIONS:

- All measurements shall be provided from center of the Proposed Well to nearest of each cultural feature as described in Rule 303.a.(5).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a: ☐ Buffer Zone
☐ Exception Zone
☐ Urban Mitigation Area

- Buffer Zone – as described in Rule 604.a.(2), within 1,000' of a Building Unit
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: _____

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: _____

SPACING and UNIT INFORMATION

Distance from completed portion of proposed wellbore to nearest completed portion of offset wellbore permitted or completed in the same formation: 330 Feet

Distance from Completed Portion of Wellbore to Nearest Unit Boundary 460 Feet (Enter 5280 for distance greater than 1 mile.)

Federal or State Unit Name (if appl): _____ Unit Number: _____

SPACING & FORMATIONS COMMENTS

The proposed spacing unit is comprised of 552 acres: T1S R68W Sec. 11: NESW, NWSE, SENW, SWNE, NENW, NWNE; Sec. 2: SESW, SWSE, NESW, NWSE, SWNE, SENW, W2 of Lot 1 aka NWNE, E2 of Lot 2 aka NENW

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR		552	GWA

DRILLING PROGRAM

Proposed Total Measured Depth: 16229 Feet

Distance from proposed wellbore to nearest existing or permitted wellbore belonging to another operator:

330 Feet (Including plugged wells)

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No (If Yes, attach an H₂S Drilling Operations Plan)

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? No

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☒ Rotating Head ☐ None

GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 318A

DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Methods: Commercial Disposal

Cuttings Disposal: OFFSITE Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted?

Reuse Facility ID: or Document Number:

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
SURF	12+1/4	9+5/8	36	0	1200	450	1200	0
1ST	8+3/4	7	26	0	7586	600	7586	3000
1ST LINER	6+1/8	4+1/2	11.6	7186	16229			

☒ Conductor Casing is NOT planned

DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- ☐ Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- ☐ Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- ☐ Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- ☐ Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

GREATER WATTENBERG AREA LOCATION EXCEPTIONS

Check all that apply:

- ☒ Rule 318A.a. Exception Location (GWA Windows).
- ☒ Rule 318A.c. Exception Location (GWA Twinning).

RULE 502.b VARIANCE REQUEST

- ☐ Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number

OTHER LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318.c. Exception Location from Rule or Spacing Order Number _____
- ☐ Rule 603.a.(2) Exception Location (Property Line Setback).

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

OPERATOR COMMENTS AND SUBMITTAL

Comments

Distance from completed portion of the wellbore to nearest wellbore permitted or completed in the same formation was measured to the Ivey I-11-2HN. Distance to nearest permitted or existing wellbore penetrating object formation was measured to the Ivey I-11-2HN.

The Surface Owner for the Ivey Location in the Sec. 11: S/2SE/4 is not the mineral owner for this well which the penetration point is located in the N/2SW/4 of Sec. 11. The lease noted is for the N/2SW/4 of Sec. 11

This application is in a Comprehensive Drilling Plan _____ CDP #: _____

Location ID: 442411

Is this application being submitted with an Oil and Gas Location Assessment application? No

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Erin Ekblad

Title: Permit Agent Date: 6/16/2015 Email: EEKBLAD@SYRGINFO.COM

Operator must have a valid water right or permit allowing for industrial use or purchased water from a seller that has a valid water right or permit allowing for industrial use, otherwise an application for a change in type of use is required under Colorado law. Operator must also use the water in the location set forth in the water right decree or well permit, otherwise an application for a change in place of use is required under Colorado law. Section 37-92-103(5), C.R.S. (2011).

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved:  Director of COGCC Date: 11/20/2015

Expiration Date: 11/19/2017

API NUMBER

05 001 09912 00

Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type

Description

	Operator acknowledges the proximity of the listed wells. Operator agrees to: provide mitigation option 1 or 2 (per the DJ Basin Horizontal Offset Policy) to mitigate the situation, ensure all applicable documentation is submitted based on the selected mitigation option chosen, and submit a Form 42 ("OFFSET MITIGATION COMPLETED") stating that appropriate mitigation occurred and that it has been completed, prior to the hydraulic stimulation of this well. REHFELD K UNIT 1, API # 001-08886, SACK #1 API # 001-07059 BYDALAK #1-11 API # 001-08368, BYDALEK #2-11 API # 001-08881 SACK G UNIT #1 API # 001-08895
	1) Submit Form 42 electronically to COGCC 48 hours prior to MIRU for first well on pad, subsequent wells 48 hours prior to spud. 2) Comply with Rule 317.j. and provide cement coverage from end of 7" casing to a minimum of 200' above Niobrara and from 200' below Sussex to 200' above Sussex. Verify coverage with cement bond log.

Best Management Practices

No BMP/COA Type

Description

1	Planning	Multi-well Pads. It is a multi-well pad located in a manner which allows for resource extraction while maintaining the highest distances possible from the offsetting residential areas.
2	Traffic control	Access Road. The access road will be constructed to accomodate local emergency vehicles. This road will be maintained for access at all times.
3	General Housekeeping	Fencing Requirements. A permanent fencing plan will be reviewed by the surface owner, and the applicant
4	General Housekeeping	Removal of surface trash. All trash, debris, and material not intrinsic to the operation of the oil and gas facility shall be removed and legally disposed of as is applicable.
5	Material Handling and Spill Prevention	Leak Detection Plan. Pumper will visit the location daily and visually inspect all tanks and fittings for leaks. Additionally, monthly documented SPCCP inspections are conducted pursuant to CFR 112.
6	Material Handling and Spill Prevention	Berm construction. Tank berms shall be constructed of steel rings with a synthetic or engineered liner and designed to contain 150% of the capacity of the largest tank. All berms will be visually checked periodically to ensure proper working condition.
7	Material Handling and Spill Prevention	Load-lines. All load lines shall be bull-plugged or capped.
8	Material Handling and Spill Prevention	Tank specifications. Tanks will be designed, constructed and maintained in accordance with NFPA Code 30. The tanks are visually inspected once a day for issues, and recorded inspections are conducted once a month.
9	Drilling/Completion Operations	Green Completions - Emission Control Systems. Test separators and associated flow lines and sand traps shall be installed on-site to accommodate Green completion techniques pursuant to COGCC Rules. In the anticipated absence of a viable gas sales line, the flow-back gas shall be thermally oxidized in an emissions control device (ECD), which will be installed and kept in operable condition for at least the first 90 days of production pursuant to CDPHE rules. The ECD shall have an adequate capacity for 1.5 times the largest flow-back within a 10 mile radius, will be flanged to route gas to other or permanent oxidizing equipment and shall be provided with the equipment needed to maintain combustion where non-combustible gases are present.

10	Drilling/Completion Operations	Blowout preventer equipment ("BOPE"). A double ram and annular preventer will be used during drilling. At least the drilling company shall have a valid well blowout prevention certifications.
11	Drilling/Completion Operations	BOPE for well servicing operations. Adequate BOP equipment shall be used. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid.
12	Drilling/Completion Operations	Drill stem tests. Not applicable, no Drill stem tests are planned.
13	Drilling/Completion Operations	Control of Fire Hazards. All materials which are considered fire hazards shall be a minimum of 25' from the wellhead tanks or separators. Electrical equipment shall comply with API RP 500 and will comply with the current national electrical code. An emergency response plan has been generated for this site.
14	Drilling/Completion Operations	Guy line anchors. All guy line anchors shall be brightly marked pursuant to Rule 604.c (2)Q.
15	Drilling/Completion Operations	Closed Loop Drilling Systems - Pit Restrictions. Not Applicable; a closed loop system will be used for drilling.
16	Drilling/Completion Operations	Pit Level indicators. Not applicable; a closed-loop system will be used and no pits shall be dug.
17	Drilling/Completion Operations	One of the first wells drilled on the pad will be logged with open-hole Resistivity Log and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which open-hole logs were run.
18	Final Reclamation	Well site cleared. Within 90 days subsequent to the time of plugging and abandonment of the entire site, superfluous debris and equipment shall be removed from the site.
19	Final Reclamation	Identification of plugged and abandoned wells. P & A'd wells shall be identified pursuant to 319.a.(5).

Total: 19 comment(s)

Applicable Policies and Notices to Operators

Policy
Notice Concerning Operating Requirements for Wildlife Protection. http://cogcc.state.co.us/documents/reg/Policies/Wildlife_Notice.pdf

Attachment Check List

Att Doc Num	Name
400799579	FORM 2 RESUBMITTED
400879919	FORM 2 SUBMITTED
400879920	FORM 2 REJECTED
400880425	WELL LOCATION PLAT
400880426	WASTE MANAGEMENT PLAN
400880427	PROPOSED SPACING UNIT
400880428	EXCEPTION LOC WAIVERS
400880432	DEVIATED DRILLING PLAN
400880433	OTHER
400880466	DIRECTIONAL DATA
400881000	SURFACE AGRMT/SURETY
400889427	OffsetWellEvaluations Data
400889432	EXCEPTION LOC REQUEST
400889447	FORM 2 SUBMITTED

Total Attach: 14 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Final Review Completed.	11/18/2015 10:25:43 AM
Engineer	offset COA wells - lack demonstrated cement across the Fox Hills (indicate that there was a DV tool with cement but no CBL)	11/15/2015 12:04:52 PM
Permit	Added email for Operator's Wellbore Integrity Contact. Permitting Review Complete.	10/27/2015 12:00:01 PM
Permit	Open Hole Logging BMP submitted by operator.	10/27/2015 11:59:47 AM
LGD	An executed Memorandum of Understanding shall be on file prior to commencing operations.	10/1/2015 9:26:26 AM
Permit	Passed completeness.	8/25/2015 9:13:42 AM
Permit	Removed the related form reference. Per the operator, no Location Assessment is being submitted with this APD.	8/25/2015 9:11:29 AM
Permit	REJECTION COMMENT: This APD is being rejected per the Rejection Process criteria that a pad of Form 2's requiring a total of four or more attachments to be added will be rejected. This pad requires a Surface Use Agreement and 317.s Waivers, to a total of eleven APD's. Operator and COGCC staff have been consulted.	8/5/2015 10:23:06 AM
Permit	Requested information from the operator about the right to construct. Lease described does not include the surface location.	8/4/2015 11:52:20 AM
Permit	Corrected the distance to the nearest wellbore completed in the same formation from 462' to 360' per the operator's request.	3/4/2015 7:59:35 AM
Permit	requested revised distances to the nearest wellbore in the same formation on the Spacing tab.	7/30/2015 11:11:08 AM
Permit	Corrected distance to nearest lease line from 178' to 0' per the operator's request.	7/30/2015 10:58:38 AM
Permit	Added the location ID per the operator.	7/30/2015 10:09:13 AM
LGD	An approved Moemorandum of Understanding will be on file prior to the approval of this application.	6/22/2015 6:42:55 AM
Permit	Passed completeness.	6/19/2015 7:34:30 AM
Permit	Returned to draft. Missing complete 317.p BMP	6/18/2015 9:40:09 AM

Total: 16 comment(s)