

Company: Noble Energy Inc

Well: Greyson LD28-753  
Field: Wattenberg  
County: Weld

State: Colorado

County: Weld			
Field: Wattenberg			
Location: SESW Sec 28 T9N R58W			
Well: Greyson LD28-753			
Company: Noble Energy Inc			
USI-LITE	LOCATION		
	Permanent Datum: Log Measured From: Drilling Measured From:		GL KB KB
			Elev: K.B. 4877.0 F G.L. 4853.0 F D.F. 4877.0 F
Logging Date	11-Sep-2015		
Run Number	ONE		
Depth Driller	10625.0 F		
Schlumberger Depth	10625.0 F		
Bottom Log Interval	5900.0 F		
Top Log Interval	60.0 F		
Casing Fluid Level	8.0 F		
Salinity			
Density	8.40 LB/G		
Fluid Level	8.0 F		
BIT/CASING/TUBING STRING			
Bit Size	8.500 IN		
From	-999.2 F		
To	10625.0 F		
Casing Size	9.62 IN		
Weight	36.00 LB/F		
Grade	N/A		
From	0.0 F		
To	1125.0 F		
Max Recorded Temp	198.0		
Logger on bottom (date)	11-Sep-2015		
Location	Fort Morgan CO		
Recorded By	Evan Meadows		
Witnessed By			

DEPTH SUMMARY LISTING

DEPTH SYSTEM EQUIPMENT

Depth Measuring Device	Tension Device	Logging Cable
Type: Serial Number: Calibration Date: Calibration Cable Type: Wheel Correction 1: Wheel Correction 2:	Type: Serial Number: Calibration Date: Calibrator Serial Number: Number Of Calibration Points: Calibration RMS: Calibration Peak Error:	Serial Number: Length: 24000.00000


DISCLAIMER


THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIIONS ON USE OF THE RECORDED-DATA (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF ANR RELIANCE UPN THE RECORDED-DATA; AND (c)CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISIONS MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA


1. TOOLS RAN AS PER TOOL SKETCH.
2. REPEAT PASS RAN AT 0 PSI MAIN PASS RAN AT 2500 PSI
3. BHT 198 DEG F
4. ESTIMATED TOC 1145'


Main Pass


Company: Noble Energy Inc  
Well: Greyson LD28-753  
Field: Wattenberg































































































BS	8.50000	IN	Bit Size
CASG	N/A		Casing Grade
CDIA	9.62500	IN	Casing Outer Diameter
CSID	8.92100	IN	Casing Inner Diameter
CSIZ	9.62500	IN	Current Casing Size
CWEI	36.00000	LB/F	Casing Weight
DFD	8.40000	LB/G	Drilling Fluid Density
DFVL	190.00000	US/F	Default Fluid Velocity
DO			
DOT	2.87400	IN	Diameter of Transducer Sensor
EMXV	50	V	EMEX Voltage
FDII	0.00000	F	FPM Data Interpolation Interval
FSOD	0_OFF		Fluid Slowness Fits Casing Outer Diameter
LOGMODE			
PP			
STEP	-0.5	F	STEP
THDH	130.00000	%	Maximum Search Thickness (percentage of nominal)
THDL	70.00000	%	Minimum Search Thickness (percentage of nominal)
THDP	Fundamental		Thickness Detection Policy
THNO	0.35200	IN	Nominal Thickness of Casing
TMUC	BRINE		Type of Mud
U-USIT_DT3P			
UPAT	375K		Emission Pattern
USUB	7INC		USIT Sub Identifier
UWKM	D603010L		Working Mode
VCAS	51.40000	US/F	Ultrasonic Transversal Velocity in Casing
WINB	33.86500	US	Window Begin Time
WINE	73.86501	US	Window End Time
ZCAS	46.25000	MRAY	Acoustic Impedance of Casing
ZINI	-1.00000	MRAY	Initial Estimate of Cement Impedance
ZMUD	1.68000	MRAY	Acoustic Impedance of Mud
ZTCM	2.60000	MRAY	Acoustic Impedance Threshold for Cement
ZTGS	0.20000	MRAY	Acoustic Impedance Threshold for Gas
WLEN	22.50350	US	T^3 Processing Length


Repeat Pass

Company: Noble Energy Inc  
Well: Greyson LD28-753  
Field: Wattenberg









## Fluid Properties Used for Main Pass

