

FORM
2

Rev
08/13

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

400918299

Date Received:

10/15/2015

APPLICATION FOR PERMIT TO:

☒ Drill ☐ Deepen ☐ Re-enter ☐ Recomplete and Operate

TYPE OF WELL OIL ☒ GAS ☐ COALBED ☐ OTHER _____

Refilling ☒

ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐

Sidetrack ☐

Well Name: CS-Kinkade

Well Number: 3-1-12

Name of Operator: EXTRACTION OIL & GAS LLC

COGCC Operator Number: 10459

Address: 370 17TH STREET SUITE 5300

City: DENVER State: CO Zip: 80202

Contact Name: Alyssa Andrews

Phone: (720)420-5749

Fax: ()

Email: alyssa.andrews@iptenergyservices.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20130028

WELL LOCATION INFORMATION

QtrQtr: SWSE Sec: 36 Twp: 6N Rng: 66W Meridian: 6

Latitude: 40.438370

Longitude: -104.722650

Footage at Surface: 339 feet FNL/FSL FSL 1888 feet FEL/FWL FEL

Field Name: WATTENBERG

Field Number: 90750

Ground Elevation: 4664

County: WELD

GPS Data:

Date of Measurement: 03/05/2012 PDOP Reading: 1.0 Instrument Operator's Name: B. TESSELY

If well is ☐ Directional ☒ Horizontal (highly deviated) submit deviated drilling plan.

Footage at Top of Prod Zone: FNL/FSL FEL/FWL Bottom Hole: FNL/FSL FEL/FWL

866 FSL 1309 FEL 2525 FNL 1346 FEL
Sec: 36 Twp: 6N Rng: 66W Sec: 12 Twp: 5N Rng: 66W

LOCATION SURFACE & MINERALS & RIGHT TO CONSTRUCT

Surface Ownership: ☒ Fee ☐ State ☐ Federal ☐ Indian

The Surface Owner is: ☐ is the mineral owner beneath the location.

(check all that apply)

☐ is committed to an Oil and Gas Lease.

☐ has signed the Oil and Gas Lease.

☐ is the applicant.

The Mineral Owner beneath this Oil and Gas Location is: ☒ Fee ☐ State ☐ Federal ☐ Indian

The Minerals beneath this Oil and Gas Location will be developed by this Well: No

The right to construct the Oil and Gas Location is granted by: Surface Use Agreement

Surface damage assurance if no agreement is in place: Surface Surety ID:

LEASE INFORMATION

Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)

Please see the lease map provided on the scout card.

Total Acres in Described Lease: 43 Described Mineral Lease is: ☒ Fee ☐ State ☐ Federal ☐ Indian

Federal or State Lease # _____

Distance from Completed Portion of Wellbore to Nearest Lease Line of described lease: 0 Feet

CULTURAL DISTANCE INFORMATION

Distance to nearest:

Building: 258 Feet

Building Unit: 258 Feet

High Occupancy Building Unit: 3848 Feet

Designated Outside Activity Area: 5280 Feet

Public Road: 339 Feet

Above Ground Utility: 293 Feet

Railroad: 239 Feet

Property Line: 200 Feet

INSTRUCTIONS:

- All measurements shall be provided from center of the Proposed Well to nearest of each cultural feature as described in Rule 303.a.(5).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a: ☒ Buffer Zone
☒ Exception Zone
☒ Urban Mitigation Area

- Buffer Zone – as described in Rule 604.a.(2), within 1,000' of a Building Unit
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: _____

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: _____

SPACING and UNIT INFORMATION

Distance from completed portion of proposed wellbore to nearest completed portion of offset wellbore permitted or completed in the same formation: 665 Feet

Distance from Completed Portion of Wellbore to Nearest Unit Boundary 460 Feet (Enter 5280 for distance greater than 1 mile.)

Federal or State Unit Name (if appl): _____ Unit Number: _____

SPACING & FORMATIONS COMMENTS

S/2SE/4 Sec 36-T5N-R66W; E/2 Sec 1-T5N-R66W; NE/4 Sec 12-T5N-R66W. PSU Map is attached to the scout card

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR		560	GWA

DRILLING PROGRAM

Proposed Total Measured Depth: 16103 Feet

Distance from proposed wellbore to nearest existing or permitted wellbore belonging to another operator:

369 Feet (Including plugged wells)

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No (If Yes, attach an H₂S Drilling Operations Plan)

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? No

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☐ Rotating Head ☐ None

GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 318A

DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Methods: Commercial Disposal

Cuttings Disposal: OFFSITE Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Beneficial reuse or land application plan submitted?

Reuse Facility ID: or Document Number:

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
SURF	12+1/4	9+5/8	36	0	500	265	500	0
1ST	8+3/4	7	26	0	7421	704	7421	3000
1ST LINER	6+1/8	4+1/2	11.6	6500	16103			

☒ Conductor Casing is NOT planned

DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- ☒ Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- ☐ Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- ☒ Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- ☐ Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

GREATER WATTENBERG AREA LOCATION EXCEPTIONS

Check all that apply:

- ☒ Rule 318A.a. Exception Location (GWA Windows).
- ☒ Rule 318A.c. Exception Location (GWA Twinning).

RULE 502.b VARIANCE REQUEST

☐ Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number

OTHER LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318.c. Exception Location from Rule or Spacing Order Number _____
- ☐ Rule 603.a.(2) Exception Location (Property Line Setback).

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

OPERATOR COMMENTS AND SUBMITTAL

Comments

Distance to well completed in the same formation: 665' (Ref. Well: CS-Kinkade 1-1-12)
Distance to well penetrating the formation: 369' (Ref. Well: CS-Kinkade 2-1-12)

This permit is a refile and the current APD expires 1/16/16.

- 1.) The pad has been built.
- 2.) The pits (if any needed) have been constructed and are permitted as necessary.
- 3.) Drilling the proposed Well being refiled will not require any pad expansion or additional surface disturbance.
- 4.) The location does not require a variance from any of the rules listed in Rule 306.d.(1).(A).(ii) and consultation with CDPHE.
- 5.) Consultation with CPW in accordance with Rule 1202 is not required.

Please see the exception location requests and waivers to Rules 604.b.(1)A, 604.b.(2), 318A.a., and 318A.c. attached to the scout card.

The right to construct is granted by the Surface Use Agreement. Please see the SUA attached to the scout card.

This application is in a Comprehensive Drilling Plan _____ CDP #: _____

Location ID: 430474

Is this application being submitted with an Oil and Gas Location Assessment application? No

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Alyssa Andrews

Title: Operations Engineer Date: 10/15/2015 Email: alyssa.andrews@iptenergyservi

Operator must have a valid water right or permit allowing for industrial use or purchased water from a seller that has a valid water right or permit allowing for industrial use, otherwise an application for a change in type of use is required under Colorado law. Operator must also use the water in the location set forth in the water right decree or well permit, otherwise an application for a change in place of use is required under Colorado law. Section 37-92-103(5), C.R.S. (2011).

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved:  Director of COGCC Date: 12/31/2015

Expiration Date: 12/30/2017

API NUMBER

05 123 38823 00

Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type

Description

	<p>Submit Form 42 electronically to COGCC 48 hours prior to MIRU for the first well activity with a rig on the pad and provide 48 hour spud notice for each subsequent well drilled on the pad.</p> <p>Comply with Rule 317.j and provide cement coverage from end of 7" casing to a minimum of 200' above Niobrara. Verify coverage with cement bond log.</p>
--	--

Best Management Practices

No BMP/COA Type

Description

1	Planning	The C Street location is fenced with a combination of chain link and wood privacy fencing. Wood privacy fencing is located along the south side of the location, adjacent to C Street, and chain link fencing is located along the west, east, and north sides. Access to the site is controlled by an automated security gate.
2	Planning	The C Street location has an approved Use by Special Review permit with Weld County, USR 13-0009.
3	Planning	804. Visual Impacts: All existing structures have been and any future long term facility structures will be painted a color that enables the facilities to blend in with the natural background color of the landscape, as seen from a viewing distance and location typically used by the public. Maintain appearance with garbage clean-up; a trash bin will be located on site to accumulate waste by the personnel drilling the wells. Site will have unused equipment, trash and junk removed immediately.
4	Planning	604.c.(2)J.i Blowout Prevention Equipment ("BOPE"): A double ram and annular preventer will be used during drilling. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid.
5	Planning	604.c.(2)J.ii Backup stabbing valves will be required on well servicing operations during reverse circulation. Valves shall be pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.
6	Planning	604.c.(2)N. Control of fire hazards: All material that is considered a fire hazard shall be a minimum of 25' from the wellhead tanks or separators. Electrical equipment shall comply with API IRP 500 and will comply with the current national electrical code.
7	Traffic control	604.c.(2)S. Access Roads: The access road has been constructed to accommodate local emergency vehicles. The access road is paved from C Street to the gate entrance to reduce dust and sediment tracking onto C Street.
8	General Housekeeping	604.c.(2)P. Trash Removal: All trash, debris and material not intrinsic to the operation of the oil and gas facility shall be removed and legally disposed of as applicable.
9	Storm Water/Erosion Control	Implement and maintain BMPs to control stormwater runoff in a manner that minimizes erosion, transport of sediment offsite, and site degradation. A water quality pond is located in the northeastern corner of the property to provide sediment retention from stormwater flows. An Erosion and Sediment Control Plan was submitted to Weld County as part of the approved grading permit and will be covered under Extraction Oil & Gas's field wide CDPHE permit, permit number COR03M013.
10	Material Handling and Spill Prevention	604.c.(2)F. Leak Detention Plan: Pumper will visit the location daily and visually inspect all tanks and fittings for leaks. Additionally, monthly documented SPCCP inspections are conducted pursuant to 40 CFR 112.
11	Material Handling and Spill Prevention	604.c.(2)R Tank Specifications: Tanks will be designed, constructed and maintained in accordance with NFPA Code 30. The tanks are visually inspected once a day for issues, and recorded inspections are conducted once a month.

12	Dust control	Operator shall employ practices for control of fugitive dust caused by their operations. Such practices shall include but are not limited to the use of speed restrictions, regular road maintenance, restriction of construction activity during high- wind days, and silica dust controls when handling sand used in hydraulic fracturing operations. Additional management practices such as road surfacing, wind breaks and barriers may be used. The access road from C Street to the gate entrance has been paved to minimize dust and sediment tracking off of the location.
13	Construction	604.c.(3)B. Berm Construction. The berming around the tank battery is constructed of a steel ring with an engineered liner, designed to contain 150% of the capacity of the largest tank. All berms will be visually checked periodically to ensure proper working condition. Secondary containment devices shall be sufficiently impervious to contain any spilled or released material. Tertiary containment, such as an earthen berm, will be installed around additional production facilities. All berms will be visually checked periodically to ensure proper working condition.
14	Construction	803 Light sources during all phases of operations will be directed downwards and away from occupied structures where possible. Permanent lighting shall be mounted at compressor stations on a pole or building and directed downward to illuminate key areas within the facility, while minimizing the amount of light projected outside the facility.
15	Construction	604.c.(2).Q. All guy line anchors left buried for future use shall be identified by a marker of bright color not less than four (4) feet in height and not greater than one (1) foot east of the guy line anchor.
16	Noise mitigation	604.c.(2)A. Extraction intends on powering the drilling rig off of highline power, which would eliminate the noise caused by the generators on the rig. This noise mitigation solution requires proper infrastructure supplied by Xcel Energy. Extraction is currently working with Xcel Energy to have this infrastructure in place prior to the start of drilling. It is anticipated that this infrastructure will be ready for use by October 2015. Additionally sound walls will be constructed around this location to aid in the reduction of noise levels.
17	Emissions mitigation	604.c.(2)C.i. Green Completions - Emission Control System: Test separators and associated flow lines and sand traps shall be installed on-site to accommodate green completions techniques pursuant to COGCC Rules. In the anticipated absence of a viable gas sales line, the flowback gas shall be thermally oxidized in an emissions control device (ECD), which will be installed and kept in operable condition for least the first 90-days of production pursuant to CDPHE rules. This ECD shall have an adequate capacity for 1.5 times the largest flowback within a 10 mile radius, will be flanged to route gas to other or permanent oxidizing equipment and shall be provided with the equipment needed to maintain combustions where non-combustible gases are present.
18	Odor mitigation	805: Oil & gas facilities and equipment shall be operated in such a manner that odors and dust do not constitute a nuisance or hazard to public welfare. The production facilities will have VOC combustors with emission control devices to comply with the Department of Public Health and Environment, Air Quality Control Commission.
19	Drilling/Completion Operations	604.c.I: Upon initial rig-up and at least once every thirty (30) days during drilling operations thereafter, pressure testing of the casing string and each component of the blowout prevention equipment including flange connections shall be performed to seventy percent (70%) of working pressure or seventy percent (70%) of the internal yield of casing, whichever is less. Pressure testing shall be conducted and the documented results shall be retained by the operator for inspection by the Director for a period of one (1) year. Activation of the pipe rams for function testing shall be conducted on a daily basis when practicable.
20	Drilling/Completion Operations	604.c.(2)L. Closed chamber drill stem tests shall be allowed. All other drill stem tests shall require approval by the Director. None planned for this well.
21	Drilling/Completion Operations	Operations 604.c.(2).K. Drilling and Completion- Pit level Indicators shall be used on location.

22	Drilling/Completion Operations	604.c.(2).O. Drilling and Completion-All loadlines shall be bullplugged or capped.
23	Drilling/Completion Operations	604.c.(2)B.i Operator will be utilizing a closed loop system
24	Drilling/Completion Operations	Operator acknowledges and will comply with COGCC policy for Bradenhead Monitoring during Hydraulic Fracturing treatments in the Greater Wattenberg Area dated May 29, 2012.
25	Drilling/Completion Operations	Requirement to log well. 317.p One of the first wells drilled on the pad will be logged with open-hole Resistivity Log and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which open-hole logs were run.
26	Drilling/Completion Operations	Landscaping and screening has been installed adjacent to C Street in accordance with the approved landscape plan per the Use by Special Review permit. Landscaping includes a mix of evergreen trees and deciduous shrubs planted along berms. A wood privacy fence is installed on the top of the berms and access is controlled by a cast iron security gate.
27	Interim Reclamation	Operator shall be responsible for segregating the topsoil, backfilling, repacking, reseeding, and re-contouring the surface of any disturbed area so as not to interfere with Owner's operations and shall reclaim such area to be returned to pre-existing conditions as best as possible with control of all noxious weeds.
28	Final Reclamation	604.c.(2)T. Within 90 days subsequent to the time of plugging and abandonment of the entire site, superfluous debris and equipment shall be removed from the site. Identification of plugged and abandoned wells will be identified pursuant to 319.a.(5)
29	Final Reclamation	604.c.(2).U. Final Reclamation-The operator shall identify the location of the wellbore with a permanent monument as specified in Rule 319.a.(5). The operator shall also inscribe or imbed the well number and date of plugging upon the permanent monument.

Total: 29 comment(s)

Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
2238596	WASTE MANAGEMENT PLAN
400918299	FORM 2 SUBMITTED

Total Attach: 2 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Final review complete.	12/30/2015 10:57:55 AM
Permit	Form 4 adding new Waste Management Plan to location approved. Permit task complete.	12/30/2015 10:00:20 AM
Permit	Per operator request, drilling disposal method changed from recycle/reuse to commercial disposal, cuttings disposal method changed from beneficial reuse to commercial disposal. Revised waste management plan attachment submitted. Corrected minerals beneath this oil and gas location will be developed to yes. On hold- Waiting on operator to submit form 4 to add new waste management plan attachment to location.	12/21/2015 3:14:17 PM
Engineer	Evaluated offset wells.	12/18/2015 2:13:05 PM
LGD	The subject site is within the City of Greeley's Long Range Expected Growth Area (LREGA), which is the area in which urban-scale development is anticipated to occur within the next 20+ years. The site is presently bordered by the City of Greeley to the north, south, and west. Existing area development is already fairly urban, with several existing medium-density neighborhoods in the vicinity. The City of Greeley has previously fielded complaints regarding previous operations at this site concerning noise, activity, and fugitive dust. Because of its proximity to a high number of residences and its visibility from C Street, an important community thoroughfare, the operator should be mindful regarding impacts of the operation. We encourage the operator to take steps to control and reduce the impacts regarding traffic, noise, refuse, and visual aesthetics that can be created by the operations contemplated by this permit. A list of additional preferred Best Management Practices can be provided by contacting the City.	11/6/2015 4:10:55 PM
Permit	Passed completeness.	10/21/2015 9:17:07 AM

Total: 6 comment(s)