
PRODUCTION
Schlumberger
Company: CHEVRON U.S.A. INC.
Well: CHEVRON ET AL #1 ROSS 16-1 FEDERAL
Field: CHEVRON ET AL #1 ROSS 16-1 FEDERAL
County: Lincoln
State: Nevada
Country: United States
API Number: 49-017-05001
Location: Sec 16 T2N R68E
Permanent Datum: Ground Level
Elevation: 5,000 ft
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Elevation: 5,000 ft
Elevation: 4,980 ft
Elevation: 4,975 ft
Date: 10-Jun-2025
Run Number: ONE
Depth Driller: 10,000 ft
Depth Logger: 10,000 ft
Bottom Logged Interval: 10,000 ft
Top Logged Interval: 4,000 ft
Casing Driller Size @ Depth: 13.375 in @ 4,000 ft
Casing Logger Size @ Depth: 13.375 in @ 4,000 ft
Bit Size: 12.25 in
Type Fluid in Hole: WBM
Density: 9.2 lb/gal
Viscosity: 45 s
Fluid Loss: 6.0 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.18 @ 120 °F
Rmf @ Meas Temp: 0.15 @ 120 °F
Rmc @ Meas Temp: 0.22 @ 120 °F
Rm @ BHT: 0.12 @ 185 °F
Time Since Circulation: 4.5 hr
Max Recorded Temp: 185 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWO
Depth Driller: 14,250 ft
Depth Logger: 14,250 ft
Bottom Logged Interval: 14,250 ft
Top Logged Interval: 10,000 ft
Casing Driller Size @ Depth: 9.625 in @ 10,000 ft
Casing Logger Size @ Depth: 9.625 in @ 10,000 ft
Bit Size: 8.5 in
Type Fluid in Hole: WBM
Density: 9.4 lb/gal
Viscosity: 48 s
Fluid Loss: 5.2 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.16 @ 138 °F
Rmf @ Meas Temp: 0.13 @ 138 °F
Rmc @ Meas Temp: 0.20 @ 138 °F
Rm @ BHT: 0.10 @ 210 °F
Time Since Circulation: 6.0 hr
Max Recorded Temp: 210 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THREE
Depth Driller: 18,500 ft
Depth Logger: 18,500 ft
Bottom Logged Interval: 18,500 ft
Top Logged Interval: 14,250 ft
Casing Driller Size @ Depth: 7.625 in @ 14,250 ft
Casing Logger Size @ Depth: 7.625 in @ 14,250 ft
Bit Size: 6.5 in
Type Fluid in Hole: WBM
Density: 9.6 lb/gal
Viscosity: 52 s
Fluid Loss: 4.8 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.14 @ 162 °F
Rmf @ Meas Temp: 0.11 @ 162 °F
Rmc @ Meas Temp: 0.18 @ 162 °F
Rm @ BHT: 0.09 @ 245 °F
Time Since Circulation: 8.0 hr
Max Recorded Temp: 245 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: FOUR
Depth Driller: 22,000 ft
Depth Logger: 22,000 ft
Bottom Logged Interval: 22,000 ft
Top Logged Interval: 18,500 ft
Casing Driller Size @ Depth: 5.5 in @ 18,500 ft
Casing Logger Size @ Depth: 5.5 in @ 18,500 ft
Bit Size: 4.75 in
Type Fluid in Hole: WBM
Density: 9.8 lb/gal
Viscosity: 55 s
Fluid Loss: 4.2 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.12 @ 185 °F
Rmf @ Meas Temp: 0.09 @ 185 °F
Rmc @ Meas Temp: 0.15 @ 185 °F
Rm @ BHT: 0.08 @ 275 °F
Time Since Circulation: 10.0 hr
Max Recorded Temp: 275 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: FIVE
Depth Driller: 24,000 ft
Depth Logger: 24,000 ft
Bottom Logged Interval: 24,000 ft
Top Logged Interval: 22,000 ft
Casing Driller Size @ Depth: 4.5 in @ 22,000 ft
Casing Logger Size @ Depth: 4.5 in @ 22,000 ft
Bit Size: 3.75 in
Type Fluid in Hole: WBM
Density: 10.0 lb/gal
Viscosity: 58 s
Fluid Loss: 3.8 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.11 @ 198 °F
Rmf @ Meas Temp: 0.08 @ 198 °F
Rmc @ Meas Temp: 0.14 @ 198 °F
Rm @ BHT: 0.07 @ 295 °F
Time Since Circulation: 12.0 hr
Max Recorded Temp: 295 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: SIX
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 24,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: SEVEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: EIGHT
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: NINE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: ELEVEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWELVE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: FOURTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: FIFTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: SIXTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: SEVENTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: EIGHTEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: NINETEEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-ONE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-TWO
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-THREE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-FOUR
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-FIVE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-SIX
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-SEVEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-EIGHT
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: TWENTY-NINE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-ONE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-TWO
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-THREE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-FOUR
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-FIVE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-SIX
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-SEVEN
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-EIGHT
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circulation: 14.0 hr
Max Recorded Temp: 310 °F
Equipment Number: PCM-1
Location: Ely, NV
Recorded By: J. Whitfield
Witnessed By: M. Caldwell
Run Number: THIRTY-NINE
Depth Driller: 25,000 ft
Depth Logger: 25,000 ft
Bottom Logged Interval: 25,000 ft
Top Logged Interval: 25,000 ft
Casing Driller Size @ Depth: 3.5 in @ 24,000 ft
Casing Logger Size @ Depth: 3.5 in @ 24,000 ft
Bit Size: 3.0 in
Type Fluid in Hole: WBM
Density: 10.2 lb/gal
Viscosity: 62 s
Fluid Loss: 3.5 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.10 @ 210 °F
Rmf @ Meas Temp: 0.07 @ 210 °F
Rmc @ Meas Temp: 0.13 @ 210 °F
Rm @ BHT: 0.06 @ 310 °F
Time Since Circ


REPEAT PASS (0 PSI)
FREE PIPE PASS (0 PSI)



Log Variables

Database:C:\Warrior\Data\bayswater_carlson_h-15-16hc_rcbl.db
Dataset: field/well/run1/pass10

Top - Bottom

PPT usec	CASEWGHT lb/ft	MAXAMPL mV	MINAMPL mV	MINATTN db/ft	SRFTEMP degF	CASEOD in	PERFS	TDEPTH ft
284	29	62.2	1	0.8	75	7	0	7407

BOTTEMP degF	BOREID in
150	8.75

Calibration Report

Database File: bayswater_carlson_h-15-16hc_rcbl.db
Dataset Pathname: pass10
Dataset Creation: Thu Aug 20 20:15:45 2015 by Log 7.0 B1

Gamma Ray Calibration Report

Serial Number:	110109-Dig	
Tool Model:	Probe275	
Performed:	Fri Jun 11 16:02:47 2004	
Calibrator Value:	138.0	GAPI
Background Reading:	37.7	cps
Calibrator Reading:	241.8	cps
Sensitivity:	0.6763	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	110224	
Tool Model:	Probe	
Calibration Casing Diameter:	7.000	in
Calibration Depth:	1473.958	ft

Master Calibration, performed Thu Aug 20 19:42:32 2015:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	-0.021	0.490	0.000	62.165	121.663	2.551
CAL	-0.016	0.746				
5'	-0.018	0.525	0.000	62.165	114.545	2.023
SUM						
S1	0.008	0.530	0.000	100.000	215.000	-1.544
S2	-0.021	0.560	0.000	100.000	172.209	3.588
S3	-0.019	0.562	0.000	100.000	172.206	3.199
S4	-0.018	0.516	0.000	100.000	187.357	3.371
S5	-0.019	0.481	0.000	100.000	199.922	3.746
S6	-0.020	0.465	0.000	100.000	206.270	4.031
S7	-0.022	0.461	0.000	100.000	207.020	4.478
S8	-0.021	0.497	0.000	100.000	192.921	4.025

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.016	0.746	1.000	0.000

Air Zero Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Service Ticket No. 46017	API No. 05-123-41717	PGM Ver WARRIOR 7.0 CH

The Well Name, Location, Borehole Description, and / or Cementing Data Furnished by Client

EQUIPMENT DATA

PROBE 2.75" RADII		PROBE GR-CCL					
Run No.	ONE	Run No.	ONE	Run No.		Run No.	
Serial No.	110224	Serial No.	110109	Serial No.		Serial No.	
Model No.	RADII 275	Model No.	GR 275	Model No.		Model No.	
Diameter	2.75IN	Diameter	2.75IN	Diameter		Diameter	

LOGGING DATA

General Data

Pass	Depths		Well Head	Speed	Logging Run Comments
No.	From	To	Pressure	Ft/Min	
8	6400FT	6200FT	0 PSI	100	REPEAT PASS
10	7054FT	0FT	0 PSI	100	MAIN PASS

	AMP 3FT		SECTORS		VDL		GAMMA RAY	
Pass	Scale		Scale		Scale		Scale	
No.	L	R	L	R	L	R	L	L
8	0	100	-5	150	200	1200	0	150
10	0	100	-5	150	200	1200	0	150

DIRECTIONAL INFORMATION

Maximum Deviation	N/A	deg. @	N/A	KOP	N/A	

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CHD-STNDRD (GOI) Standard Cable Head	1.00	1.69	10.00
			RBT-Probe (110224) Probe Radii Bond Tool with Digital Telemetry	8.75	2.75	90.00
WVF3FT	9.03					
WVFCAL	9.03					
WVFS1	9.03					
WVFS2	9.03					
WVFS3	9.03					
WVFS4	9.03					
WVFS5	9.03					
WVFS6	9.03					
WVFS7	9.03					
WVFS8	9.03					
WVF5FT	8.03					
CCL	3.88					
GR	2.54		GR-Probe275 (110109-Dig)	4.78	2.75	57.00

Dataset: bayswater_carlson_h-15-16hc_rcbl.db: field/well/run1/pass10
Total Length: 14.53 ft
Total Weight: 157.00 lb
O.D. 2.75 in

ALLIED HORIZONTAL WIRELINE SERVICES

Company	BAYSWATER EXPLORATION & PRODUCTION
Well	CARLSON H-15-16HC
Field	WATTENBERG
County	WELD
State	COLORADO
Country	USA