

FORM 5A Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400978085

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322 2. Name of Operator: NOBLE ENERGY INC 3. Address: 1625 BROADWAY STE 2200 City: DENVER State: CO Zip: 80202 4. Contact Name: Julie Webb Phone: (720) 587-2223 Fax: Email: jwebb@progressivepcs.net

5. API Number 05-123-41587-00 6. County: WELD 7. Well Name: Greyson Well Number: LD28-760 8. Location: QtrQtr: SESW Section: 28 Township: 9N Range: 58W Meridian: 6 9. Field Name: WILDCAT Field Code: 99999

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/23/2015 End Date: 11/25/2015 Date of First Production this formation: 01/04/2016 Perforations Top: 6360 Bottom: 10528 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: Niobrara Frac'd with 2751331 lb Ottawa sand, 4649282 gal fresh water, 4778146 gal silverstem and slick water.

This formation is commingled with another formation: Total fluid used in treatment (bbl): 224462 Max pressure during treatment (psi): 5764 Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43 Type of gas used in treatment: Min frac gradient (psi/ft): 0.80 Total acid used in treatment (bbl): Number of staged intervals: 23 Recycled water used in treatment (bbl): 113765 Flowback volume recovered (bbl): 1361 Fresh water used in treatment (bbl): 110697 Disposition method for flowback: RECYCLE Total proppant used (lbs): 2751331 Rule 805 green completion techniques were utilized: Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 01/10/2016 Hours: 24 Bbl oil: 235 Mcf Gas: 195 Bbl H2O: 453 Calculated 24 hour rate: Bbl oil: 235 Mcf Gas: 195 Bbl H2O: 453 GOR: 830 Test Method: Flowing Casing PSI: 1000 Tubing PSI: 755 Choke Size: 20/64 Gas Disposition: SOLD Gas Type: WET Btu Gas: 1327 API Gravity Oil: 55 Tubing Size: 2 + 3/8 Tubing Setting Depth: 6146 Tbg setting date: 12/20/2015 Packer Depth:

Reason for Non-Production: Date formation Abandoned: Squeeze: If yes, number of sacks cmt \*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Julie Webb

Title: Regualtory Analyst Date: \_\_\_\_\_ Email: jwebb@progressivepcs.net  
:

### Attachment Check List

**Att Doc Num**      **Name**

--	--

Total Attach: 0 Files

### General Comments

**User Group**      **Comment**      **Comment Date**

--	--	--

Total: 0 comment(s)