



COMPANY					DATE	
Schneider Energy Services, Inc					2/4/16	
LEASE						
Miur 13-A						
CASING	Size	Weight	Grade	Thread	Depth	
	8-5/8"	24	J-55	LT&C	221	
Casing	Size	Weight	Grade	Thread	Depth	
	4-1/2"	10.5	J-55	LT&C	6440	
Tubing	First String	Size	Weight	Grade	Thread	Depth
		2-3/8"	4.7	J-55	8rd EUE	6399'
Second String	Size	Weight	Grade	Thread	Depth	
Prepared for: COGCC CURRENT WBD.			Perforations: D-Sand 6410' to 6416".			
ITEM No#	Length	Description		ID	OD	Depth
1	221.00	8-5/8", 23# Surface casing landed @ 221'. Cemented with 125 sacks				
2		Top of the Niobrara 5680'.				
3		Top of cement @ 6156'				
4		2-3/8" tubing landed @ 6399'				
5		D-Sand Perfs 6410' to 6416"				
6	6440.00	4-1/2", 10.5# casing set @ 6440'. Cemented with 125 sacks.				-6440.00
PREPARED BY: Jeff Schneider				PHONE:		
				970-381-9588		
OFFICE			PHONE		INVOICE #	