Company NOBLE ENERGY, INC.
Well BOLENDER 29-62
Field WATTENBERG
County WELD
State COLORADO

Casedhole Solutions

GAMMA RAY / CCL
CEMENT BOND / VDL

Company NOBLE ENERGY, INC.
Well BOLENDER 29-62
Field WATTENBERG
Location API # 05-123-33551
County WELD
State COLORADO

Other Services

Permanent Datum: GROUND LEVEL
Log Measured From: KELLY BUSHING
Drilling Measured From: KB

	Elev.	Above Perm. Datum
K.B.	4917	0
D.F.		
G.L.	4907	

Date 11-Dec-15
Run Number ONE
Depth Driller 7150
Schlum. Depth 7150
Bottom Logged Interval 7150
Top Logged Interval 6800
Casing Driller 7" @ 7150
Casing Schlum. 7" @ 7150
Bit Size 6.125
Type Fluid in Hole WATER
Density / Viscosity 8.4
PH / Fluid Loss
Source of Sample
Rm @ Meas. Temp
Rmf @ Meas. Temp
Rmc @ Meas. Temp
Source of Rmf / Rmc
Rm @ BHT
Time Since Circ.
Max. Rec. Temp. 180
Equip. Location GREELEY
Recorded By MICHAEL
Witnessed By

	Size	Weight	From	To
Run No.				
Tool Type				
Tool No.				
Bottom				

*** Field Data ***

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING
CASEDHOLE SOLUTIONS

Calibration Report

Database File: cbl\bolender29-2.db
Dataset Pathname: pass6
Dataset Creation: Fri Dec 11 07:52:48 2015 by Log SCH 126430

Gamma Ray Calibration Report

Type / Serial: Probe2755dg / 101010

Wed Feb 27 07:52:48 2013

SHOP CALIBRATION

	Counts/Sec	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.6500			GAPI/cps

PRIMARY VERIFICATION

Background	0.0			cps
Calibrator	0.0			cps
Difference			0.0	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0			cps
Calibrator	0.0			cps
Difference			0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0			cps
Calibrator	0.0			cps
Difference			0.0	GAPI

Cement Bond Log Calibration Report

Serial Number:	110802	
Tool Model:	Probe2750gital	
Performed:	Fri Dec 11 07:51:20 2015	
Depth:	861.858	ft
Casing Diameter:	4.5	in
	3' Spacing	5' Spacing
Signal Zero:	0.0	0
Sig/Hand Amplitude:	61.1961	61.1961
Reading at Signal Zero:	-0.012950	-0.012207
Reading in Free Pipe:	2.479101	2.39841
Gain:	32.2254	33.6827
Offset:	1.28944	0.411165

Signal Zero:	mV
Sig/Hand Amplitude:	mV
Reading at Signal Zero:	V
Reading in Free Pipe:	V

Database File: cbl\bolender29-2.db
Dataset Pathname: pass6
Presentation Format: ndde-en
Dataset Creation: Fri Dec 11 07:52:48 2015 by Log SCH 126430
Charted by: Depth in Feet scaled 1:240

80	CCL	-4	0	Amplified Amplitude (mV)	30	200	Variable Density 1200
0	Gamma Ray (GAPI)	150	0	Amplitude (mV)	100		
340	TT3 (usec)	240					

← SQUEEZE PERF'S 4170'

80 CCL -4 | 0 Amplified Amplitude (mV) 30 200 Variable Density 1200
0 Gamma Ray (GAPI) 150 | 0 Amplitude (mV) 100
340 TT3 (usec) 240