

NOBLE ENERGY INC.

Loloff #01

NESW 26-5N-64W

1980' FSL & 1980' FWL

WELD COUNTY, CO

Wattenberg

CURRENT WELLBORE SCHEMATIC W/ PROPOSED P&A

4/1/2016

API: 05-123-11068

COGCC #

Spud Date: 3/25/1983

GL Elev: 4609'

KB Elev: 4622'

Surface Casing :

8.625" 24# (Grade ?) SET AT 327'

Cement: 280 sx

TOC: Surface

Cut surface casing off 6'-8' below surface.

Pump approx 175 sx shoe plug at 427'

142 sx out and 33 sx in

Will bring cement to surface.

Surface Casing = 327' + 100' = 427'

Deepest water well perf = 142' + 150' = 292'

Fox Hills = 136' + 150' = 286'

427

TOC @ 5800

NIO Top @ 6431

Codell Top @ 6724

Shoot holes at 2500' & 427'

Set CIBC at 2400' and cement with: 95 sx

87 sx through and 8 sx on top

No Sussex Production within a mile

Set CIBC @ 6394 w/ 2 sx cement

NIOBRARA Perforations 6444' - 6558'

CODELL Perforations 6728' - 6738'

Production Casing :

4.5" 11.6# (Grade ?) SET AT 6811'

Cement: 225 sx

TD: 3/30/1983

TD: 6811'

