

WELLBORE DIAGRAM
NGL Water Solutions DJ LLC
NGL C3B
 NENE Sec 29-T4N-R65W
 Weld County, CO
 API - 05-123-42811

CURRENT

4/25/2016
 PAG

Directions: From WCR 42 at WCR 41,
 1000' South, West into

Spud Date 3/7/2016

K.B.= 4897.5

G.L.= 4875

22.5

TOPS

All listed in MD

Parkman - 3130'

Sussex - 4337'

Shannon - 5065'

Niobrara - 7122'

Ft. Hays - 7242'

Codell - 7282'

Carlile - 7296'

X-Bentonite - 7576'

J-Sand - 7744'

Skull Creek - 7896'

Dakota - 7968'

Morrison - 8104'

Entrada - 8390'

Lykins - 8432'

Permian - 8680'

Forelle - 8781'

Minnekahta - 8825'

Blaine - 8952'

Lyons - 9006'

L. Satanka- 9142'

Wolfcamp- 9390'

Amazon - 9439'

Council Grove - 9497'

Admire - 9730'

Virgil - 9752'

Missouri - 9922'

Fountain - 10064'

TD - 10,640'

DJINJ - 9018'-10,640'

9-5/8", 36# J-55 ST&C CSG Set @ 747' (12-1/4" O.H.)
 Cmt'd w/ 255 sx total

DV Tool @ 7560'
 Cmt'd w/ 646 sx lead, 200 sx tail - TOTAL 846 sks

PermaPak & Tbg Setting Depth @ 8945'

PBR & TOL @ 8,970'
 7" 26# L-80 LT&C CSG Set @ 9018' (8-3/4" O.H.)
 Cmt'd w/ 200 sx (1st stage)

ECP4 @ 9,722'

ECP3 @ 9,898'

Slotted Liner Liner slotted with 2" by 0.040" slots on 6" centers

ECP2 @ 10,093'

ECP1 @ 10,444'

4-1/2" 11.6# N-80 LT&C Slotted Liner (TOL @ 8,970', EOL @ 10,640')
 (6-1/8" O.H.)

MD = 10,640'
PBTD = 10,633'