

Well Name: Rhodes 1

Location: Twn:34N Rng:6W Sec:7 QtrQtr:SENW

Elevation: GL 6927', KB 6938'

Date: 3-Jun-2016

API #: 05-067-09955-00

Spud Date: 24-Mar-2016

8.625", 24 #/ft, J-55 Casing

TOC = surface (circulated 25bbls to surf)
behind 8.625" casing

Casing set at 442'

Note: This is a build and hold well. This diagram reflects measured depths but not lateral aspects of the wellbore.

TOC = surface (circulated 35bbls to surf)
behind 5.5" casing

| 4/22/2016 | Jts | Lgth | TS |
|---------------------------------|-----|------|------|
| TUBING HANGER | 1 | 1 | 11 |
| 3.5, 9.5# J-55 Barrier Tubing | 1 | 32 | 12 |
| 3.5, 9.3# J-55 Poly Line Tubing | 106 | 3452 | 43 |
| 3.5x2.875 X Over J-55 | 1 | 1 | 3496 |
| 2 7/8 F-Nipple 2.28 Profile | 1 | 1 | 3497 |
| 2 7/8 Weep Hole Nipple | 1 | 1 | 3498 |
| 2 7/8 J-55 Tubing Jnt | 1 | 33 | 3499 |
| 2 7/8 6.4# J-55 Mule Shoe | 1 | 3 | 3532 |
| EOT | | | 3535 |

Perforations 3184' - 3190'
3204' - 3213'
3251' - 3278'
3388' - 3415'

| 4/23/2016 | Jts | Lgth | TS |
|-------------------|-----|------|------|
| 1.25 Polished Rod | 1 | 26 | 4 |
| 7/8 Slick Rod | 1 | 25 | 30 |
| 2' Pony Rod | 1 | 2 | 55 |
| #4 Co-Rod | 1 | 3430 | 57 |
| 4' Pony | 1 | 2 | 3487 |
| Shear Tool 20k | 1 | 1 | 3489 |
| 4' Pony Rod | 1 | 4 | 3490 |
| 2.5x2.0x12' RWAC | 1 | 12 | 3494 |
| EOR | | | 3506 |

3.5", 9.3 #/ft, J-55 Tubing
5.5", 15.5 #/ft, J-55 Casing

Tubing landed at 3534.61'
PBTD: 3668'

Casing set at 3715.3'

TD: 3726'