



# Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18<sup>th</sup> Street  
Denver, CO 80202  
720-929-6000

June 17, 2016

Matt Lepore  
Director, Colorado Oil and Gas Conservation Commission  
Department of Natural Resources  
The Chancery Building  
1120 Lincoln Street, Suite 801  
Denver, CO 80203

Re: Request for Exception to Rule 317.p  
BABCOCK 19N-33HZ (Doc. Number 401060900)  
BABCOCK 11N-33HZ (Doc. Number 401060903)  
BABCOCK 12N-33HZ (Doc. Number 401060905)  
BABCOCK 13E-33HZ (Doc. Number 401060906)  
BABCOCK 14C-33HZ (Doc. Number 401060907)  
BABCOCK 22N-33HZ (Doc. Number 401060908)  
BABCOCK 23N-33HZ (Doc. Number 401060909)  
BABCOCK 32N-33HZ (Doc. Number 401060910)  
BABCOCK 33C-33HZ (Doc. Number 401060913)  
BABCOCK 35C-33HZ (Doc. Number 401060917)  
Township 2 North, Range 67 West  
Gov. Lot 1, Section 4: SENW  
Weld County, Colorado

Dear Director Lepore:

Kerr-McGee Oil & Gas Onshore LP ("KMG") respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A Cement Bond Log with cased-hole gamma-ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well requirements and have a surface location within seven hundred fifty (750) feet of the proposed well(s).

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma-ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the

kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred and fifty feet (750) with acceptable resistivity logs with gamma ray are listed in the table below:

Well Name	Well Number	API Number	Distance From Well(s)	Azimuth (Degrees)	COGCC Well File Document Number
HSR-DODERO	6-4A	05-123-19671	52	3	978005

Should you have any questions, please contact our office. Thank you for your consideration.

Sincerely,

**Kerr-McGee Oil & Gas Onshore LP**

A handwritten signature in cursive script that reads "Shayelyn Marshall".

Shayelyn Marshall  
Regulatory Analyst