

FORM
6Rev
12/05State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Document Number:

401074382

Date Received:

07/07/2016

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 69175

Contact Name: Kelsi Welch

Name of Operator: PDC ENERGY INC

Phone: (303) 831-3974

Address: 1775 SHERMAN STREET - STE 3000

Fax:

City: DENVER State: CO Zip: 80203

Email: kelsi.welch@pdce.com

For "Intent" 24 hour notice required,

Name: Gomez, Jason

Tel: (970) 573-1277

COGCC contact:

Email: jason.gomez@state.co.us

API Number 05-123-20585-00

Well Name: DUNN/MILLER

Well Number: 17B

Location: QtrQtr: NWSW Section: 17 Township: 5N Range: 64W Meridian: 6

County: WELD

Federal, Indian or State Lease Number:

Field Name: WATTENBERG

Field Number: 90750

☒ Notice of Intent to Abandon☐ Subsequent Report of Abandonment

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.395940

Longitude: -104.578690

GPS Data:

Date of Measurement: 10/16/2010

PDOP Reading: 1.7

GPS Instrument Operator's Name: Steve Cure

Reason for Abandonment: ☐ Dry☒ Production Sub-economic☐ Mechanical Problems☐ OtherCasing to be pulled: ☒ Yes☐ No

Estimated Depth: 590

Fish in Hole: ☐ Yes☒ No

If yes, explain details below

Wellbore has Uncemented Casing leaks: ☐ Yes☒ No

If yes, explain details below

Details:

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
CODELL	6870	6878			

Total: 1 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF	12+1/4	8+5/8	24	387	330	387	0	VISU
1ST	7+7/8	4+1/2	10.5	7,061	170	7,061	5,984	CBL
S.C. 1.1					270	5,984	3,136	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 6820 with 2 sacks cmt on top. CIBP #2: Depth 6462 with 2 sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 250 sacks half in. half out surface casing from 640 ft. to 0 ft. Plug Tagged: ☐

Set _____ sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No

Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. _____ inch casing Plugging Date: _____
of _____

*Wireline Contractor: _____ *Cementing Contractor: _____

Type of Cement and Additives Used: _____

Flowline/Pipeline has been abandoned per Rule 1103 ☐ Yes ☐ No *ATTACH JOB SUMMARY

Technical Detail/Comments:

Dunn-Miller 17B (05-123-20585)/Plugging Procedure (Intent)
Producing Formation: Codell 6870'-6878'
TD: 7080' PBD: 7036'
Surface Casing: 8 7/8" 24# @ 387' w/ 330 sks cmt.
Production Casing: 4 1/2" 10.5# @ 7061' w/ 440 sks cmt (TOC 3136' CBL).

Tubing: 2 7/8" 4.7# EUE set at 6827'. (1/17/2002)

Proposed Procedure:

1. MIRU RU pulling unit. Pull tubing.
2. RU wireline company.
3. TIH with CIBP. Set bridge plug at 6830'. TIH with dump bailer. Spot 2 sxs cement on top of CIBP.
4. TIH with CIBP. Set bridge plug at 6500'. TIH with dump bailer. Spot 2 sxs cement on top of CIBP.
5. TIH with casing cutter. Cut 4 1/2" casing at 590'. Pull 4 1/2" casing.
6. TIH with tubing to 640'. Mix and pump 250 sxs of 15.8#/gal CI G cement. Cement should circulate to surface.
7. Cut surface casing 6' below ground level and weld on cap.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kelsi Welch

Title: Regulatory Analyst Date: 7/7/2016 Email: kelsi.welch@pdce.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

CONDITIONS OF APPROVAL, IF ANY:

Expiration Date: 1/26/2017

COA Type**Description**

	<p>NOTE CHANGES IN PLUGGING PROCEDURE:</p> <ol style="list-style-type: none">1) Provide 48 hour notice of plugging MIRU via electronic Form 42.2) Move CIBP from 6830', to 6820', to be 50' above the top perforation.3) Move CIBP at 6500', to 6462' to be 50' above the Niobrara.4) For the 640' plug: pump plug and displace. If surface casing plug is not circulated to surface then tag plug – must be at 337' or shallower and provide 10 sx plug at the surface. Leave at least 100' of cement in the casing for each plug.5) Properly abandon flowlines as per Rule 1103. File electronic Form 42 once abandonment complete.6) Prior to initiation of plugging operations, a Bradenhead test shall be performed. If any pressure remains at the conclusion of the test or any liquids were present call COGCC Engineer for sampling requirements. Form 17 shall be submitted within 10 days.
--	--

Attachment Check List**Att Doc Num****Name**

401074382	FORM 6 INTENT SUBMITTED
401074389	WELLBORE DIAGRAM
401074391	WELLBORE DIAGRAM

Total Attach: 3 Files

General Comments**User Group****Comment****Comment Date**

Public Room	Document verification complete	7/8/2016 12:03:53 PM
-------------	--------------------------------	-------------------------

Total: 1 comment(s)