

### WORKOVER PROCEDURE

**WELL NAME:** Reinick 02 **DATE:** 7/28/2016  
**LOCATION:**  
Qtr/Qtr: NW/NE Section: 9 Township: 4N Range: 64W  
Footages: 660 FNL & 1980 FEL  
**COUNTY:** WELD **STATE:** CO **API #:** 05-123-11923

**ENGINEER:** Jon Lefor 7 Day Notice Sent:  
(Please notify Engineer of any major changes prior to work) Do not start operations until:  
Notice Expires:

**OBJECTIVE:** P&A

**WELL DATA:** Surface Csg: 8 5/8" 24#, @ 435' KB Elevation: 4718'  
Surface Cmt: 300 sx GL Elevation: 4705'  
Long St Csg: 4 1/2" 10.5#, K-55 @ 6993' TD: 7013'  
Long St Cmt: 250 sx PBTB: 6939'  
Long St Date: 9/19/1984

Plug Back (Sand or CIBP):  
Perforation Interval (1): Codell Perforations 6870' - 6885'  
Perforation Interval (2):  
Perforation Interval (3):  
Perforation Interval (4):  
Tubing: 2 3/8" 4.7# J-55 tbg @ 6865' Rods:  
Pump:  
Misc.:

**PRODUCTION STATUS:**  
**COMMENTS:** Provide 48 hr notice of plugging MIRU via electronic form 42.  
Abandon flowlines as per Rule 1103. File electronic form 42 once abandonment completed.

**PROCEDURE:**

- Prior to plugging operations, perform a bradenhead test. If any pressure remains at the conclusion of the test or any liquids were present call COGCC engineer for sampling requirements. Submit form 17 within 10 days.
- MIRU Workover rig, pump & tank.
- POOH w/ 2 3/8" tbg and lay down.
- RIH w/ tubing-set CIBP. Set CIBP @ 6820', pump 30 sx of cement on top.
- Unland casing. Cut casing off @ 2500'. POOH w/ casing laying down on trailer.  
RIH w/ workstring to pump 100 sx stub plug where csg was pulled. If maintain circulation, no need to tag plug. 100' of cement is required, at least 50' in casing and at least 50' above csg, to be verified by tagging.
- POOH w/ workstring to 535'. Pump 210 sx shoe plug. Cement to surface.  
If circulation not maintained to surface then tag plug, must be at 385' or shallower, provide 10 sx plug at surface
- at least 100' of cement in the casing for each plug.
- SI, WOC. RIH. Tag shoe plug. Add cement if needed.
- Cut surface casing off 6'-8' below ground.
- Clean up location. Reclaim location. RDMO.