

FORM 5A Rev 06/12

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



Table with columns DE, ET, OE, ES

Document Number: 400714697 Date Received: 10/27/2014

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322 2. Name of Operator: NOBLE ENERGY INC 3. Address: 1625 BROADWAY STE 2200 City: DENVER State: CO Zip: 80202 4. Contact Name: Kathleen Mills Phone: (720) 587-2226 Fax: (303) 228-4286 Email: eroberts@nobleenergyinc.com

5. API Number 05-123-38866-00 6. County: WELD 7. Well Name: TAHOMA E Well Number: 22-69HC 8. Location: QtrQtr: SWSW Section: 14 Township: 6N Range: 65W Meridian: 6 9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 08/30/2014 End Date: 09/05/2014 Date of First Production this formation: 09/09/2014

Perforations Top: 8861 Bottom: 11891 No. Holes: Hole size:

Provide a brief summary of the formation treatment: Open Hole: [X]

FRAC'D W/2459634 GALS SILVERSTIM AND SLICK WATER AND 2343883# OTTAWA SAND

This formation is commingled with another formation: [] Yes [X] No

Total fluid used in treatment (bbl): 58562 Max pressure during treatment (psi): 6140

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: Min frac gradient (psi/ft): 0.79

Total acid used in treatment (bbl): Number of staged intervals: 6

Recycled water used in treatment (bbl): 2537 Flowback volume recovered (bbl): 1077

Fresh water used in treatment (bbl): 56025 Disposition method for flowback: RECYCLE

Total proppant used (lbs): 2343883 Rule 805 green completion techniques were utilized: [X]

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 10/02/2014 Hours: 24 Bbl oil: 182 Mcf Gas: 430 Bbl H2O: 20

Calculated 24 hour rate: Bbl oil: 182 Mcf Gas: 430 Bbl H2O: 20 GOR: 2362

Test Method: FLOWING Casing PSI: 1840 Tubing PSI: 1160 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1256 API Gravity Oil: 40

Tubing Size: 2 + 7/8 Tubing Setting Depth: 7282 Tbg setting date: 09/16/2014 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: [] Yes [] No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

| |
|--|
| |
|--|

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kathleen Mills

Title: Regulatory Analyst Date: 10/27/2014 Email: eroberts@nobleenergyinc.com
:

Attachment Check List

Att Doc Num **Name**

| | |
|-----------|-------------------|
| 400714697 | FORM 5A SUBMITTED |
|-----------|-------------------|

Total Attach: 1 Files

General Comments

User Group **Comment** **Comment Date**

| | | |
|--|--|--|
| | | |
|--|--|--|

Total: 0 comment(s)