



Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well PUCKETT 42A-23
Company:	Caerus Oil & Gas	TVD Reference:	30' KB @ 8562.00usft (H&P 330)
Project:	Garfield County, CO (UTM 12N)	MD Reference:	30' KB @ 8562.00usft (H&P 330)
Site:	S23-T6S-R97W (MESA C23)	North Reference:	True
Well:	PUCKETT 42A-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	PLAN #2		

Project	Garfield County, CO (UTM 12N)		
Map System:	Universal Transverse Mercator (US Survey Feet)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 - Western US		
Map Zone:	Zone 12N (114 W to 108 W)		

Site		S23-T6S-R97W (MESA C23)			
Site Position:		Northing:	14,361,896.90 usft	Latitude:	39.515068
From:	Map	Easting:	2,434,697.40 usft	Longitude:	-108.183912
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16"	Grid Convergence:	1.79 °

Well	PUCKETT 42A-23					
Well Position	+N/-S	0.00 usft	Northing:	14,361,844.60 usft	Latitude:	39.514923
	+E/-W	0.00 usft	Easting:	2,434,708.80 usft	Longitude:	-108.183877
Position Uncertainty		0.00 usft	Wellhead Elevation:	0.00 usft	Ground Level:	8,532.00 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
			(°)	(°)	(nT)
	HDGM	6/16/2016	9.80	65.87	51,812

Design	PLAN #2			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.00	0.00	0.00	145.53

Plan Sections										
Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Dogleg Rate	Build Rate	Turn Rate	TFO	Target
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)	(°)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00	
871.24	14.14	145.53	866.48	-47.69	32.74	3.00	3.00	0.00	145.53	
6,766.85	14.14	145.53	6,583.52	-1,234.88	847.67	0.00	0.00	0.00	0.00	
7,238.09	0.00	0.00	7,050.00	-1,282.57	880.41	3.00	-3.00	0.00	180.00	
9,410.09	0.00	0.00	9,222.00	-1,282.57	880.41	0.00	0.00	0.00	0.00	PUCKETT 42A-23 PE

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well PUCKETT 42A-23
Company:	Caerus Oil & Gas	TVD Reference:	30' KB @ 8562.00usft (H&P 330)
Project:	Garfield County, CO (UTM 12N)	MD Reference:	30' KB @ 8562.00usft (H&P 330)
Site:	S23-T6S-R97W (MESA C23)	North Reference:	True
Well:	PUCKETT 42A-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	PLAN #2		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	
500.00	3.00	145.53	499.95	-2.16	1.48	2.62	3.00	3.00	
600.00	6.00	145.53	599.63	-8.63	5.92	10.46	3.00	3.00	
700.00	9.00	145.53	698.77	-19.39	13.31	23.51	3.00	3.00	
800.00	12.00	145.53	797.08	-34.41	23.62	41.74	3.00	3.00	
871.24	14.14	145.53	866.48	-47.69	32.74	57.84	3.00	3.00	
900.00	14.14	145.53	894.36	-53.48	36.71	64.87	0.00	0.00	
1,000.00	14.14	145.53	991.33	-73.62	50.53	89.29	0.00	0.00	
1,100.00	14.14	145.53	1,088.30	-93.75	64.36	113.72	0.00	0.00	
1,200.00	14.14	145.53	1,185.28	-113.89	78.18	138.14	0.00	0.00	
1,300.00	14.14	145.53	1,282.25	-134.03	92.00	162.57	0.00	0.00	
1,400.00	14.14	145.53	1,379.22	-154.16	105.82	186.99	0.00	0.00	
1,500.00	14.14	145.53	1,476.19	-174.30	119.65	211.42	0.00	0.00	
1,600.00	14.14	145.53	1,573.16	-194.44	133.47	235.84	0.00	0.00	
1,700.00	14.14	145.53	1,670.13	-214.58	147.29	260.26	0.00	0.00	
1,800.00	14.14	145.53	1,767.10	-234.71	161.12	284.69	0.00	0.00	
1,900.00	14.14	145.53	1,864.08	-254.85	174.94	309.11	0.00	0.00	
2,000.00	14.14	145.53	1,961.05	-274.99	188.76	333.54	0.00	0.00	
2,100.00	14.14	145.53	2,058.02	-295.12	202.58	357.96	0.00	0.00	
2,200.00	14.14	145.53	2,154.99	-315.26	216.41	382.39	0.00	0.00	
2,300.00	14.14	145.53	2,251.96	-335.40	230.23	406.81	0.00	0.00	
2,400.00	14.14	145.53	2,348.93	-355.53	244.05	431.24	0.00	0.00	
2,500.00	14.14	145.53	2,445.90	-375.67	257.87	455.66	0.00	0.00	
2,600.00	14.14	145.53	2,542.87	-395.81	271.70	480.09	0.00	0.00	
2,700.00	14.14	145.53	2,639.85	-415.94	285.52	504.51	0.00	0.00	
2,800.00	14.14	145.53	2,736.82	-436.08	299.34	528.94	0.00	0.00	
2,900.00	14.14	145.53	2,833.79	-456.22	313.17	553.36	0.00	0.00	
3,000.00	14.14	145.53	2,930.76	-476.36	326.99	577.78	0.00	0.00	
3,100.00	14.14	145.53	3,027.73	-496.49	340.81	602.21	0.00	0.00	
3,200.00	14.14	145.53	3,124.70	-516.63	354.63	626.63	0.00	0.00	
3,300.00	14.14	145.53	3,221.67	-536.77	368.46	651.06	0.00	0.00	
3,400.00	14.14	145.53	3,318.64	-556.90	382.28	675.48	0.00	0.00	
3,500.00	14.14	145.53	3,415.62	-577.04	396.10	699.91	0.00	0.00	
3,600.00	14.14	145.53	3,512.59	-597.18	409.92	724.33	0.00	0.00	
3,700.00	14.14	145.53	3,609.56	-617.31	423.75	748.76	0.00	0.00	
3,800.00	14.14	145.53	3,706.53	-637.45	437.57	773.18	0.00	0.00	
3,900.00	14.14	145.53	3,803.50	-657.59	451.39	797.61	0.00	0.00	
4,000.00	14.14	145.53	3,900.47	-677.72	465.22	822.03	0.00	0.00	
4,100.00	14.14	145.53	3,997.44	-697.86	479.04	846.46	0.00	0.00	
4,200.00	14.14	145.53	4,094.42	-718.00	492.86	870.88	0.00	0.00	
4,300.00	14.14	145.53	4,191.39	-738.14	506.68	895.31	0.00	0.00	
4,400.00	14.14	145.53	4,288.36	-758.27	520.51	919.73	0.00	0.00	
4,500.00	14.14	145.53	4,385.33	-778.41	534.33	944.15	0.00	0.00	
4,600.00	14.14	145.53	4,482.30	-798.55	548.15	968.58	0.00	0.00	
4,700.00	14.14	145.53	4,579.27	-818.68	561.97	993.00	0.00	0.00	
4,800.00	14.14	145.53	4,676.24	-838.82	575.80	1,017.43	0.00	0.00	
4,900.00	14.14	145.53	4,773.21	-858.96	589.62	1,041.85	0.00	0.00	
5,000.00	14.14	145.53	4,870.19	-879.09	603.44	1,066.28	0.00	0.00	

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well PUCKETT 42A-23
Company:	Caerus Oil & Gas	TVD Reference:	30' KB @ 8562.00usft (H&P 330)
Project:	Garfield County, CO (UTM 12N)	MD Reference:	30' KB @ 8562.00usft (H&P 330)
Site:	S23-T6S-R97W (MESA C23)	North Reference:	True
Well:	PUCKETT 42A-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	PLAN #2		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100u)	Comments / Formations
5,100.00	14.14	145.53	4,967.16	-899.23	617.27	1,090.70	0.00	0.00	
5,200.00	14.14	145.53	5,064.13	-919.37	631.09	1,115.13	0.00	0.00	
5,300.00	14.14	145.53	5,161.10	-939.50	644.91	1,139.55	0.00	0.00	
5,400.00	14.14	145.53	5,258.07	-959.64	658.73	1,163.98	0.00	0.00	
5,500.00	14.14	145.53	5,355.04	-979.78	672.56	1,188.40	0.00	0.00	
5,600.00	14.14	145.53	5,452.01	-999.91	686.38	1,212.83	0.00	0.00	
5,700.00	14.14	145.53	5,548.99	-1,020.05	700.20	1,237.25	0.00	0.00	
5,800.00	14.14	145.53	5,645.96	-1,040.19	714.02	1,261.67	0.00	0.00	
5,900.00	14.14	145.53	5,742.93	-1,060.33	727.85	1,286.10	0.00	0.00	
6,000.00	14.14	145.53	5,839.90	-1,080.46	741.67	1,310.52	0.00	0.00	
6,100.00	14.14	145.53	5,936.87	-1,100.60	755.49	1,334.95	0.00	0.00	
6,200.00	14.14	145.53	6,033.84	-1,120.74	769.32	1,359.37	0.00	0.00	
6,300.00	14.14	145.53	6,130.81	-1,140.87	783.14	1,383.80	0.00	0.00	
6,361.04	14.14	145.53	6,190.00	-1,153.16	791.57	1,398.71	0.00	0.00	OHIO_CREEK.MBL (TVD)
6,400.00	14.14	145.53	6,227.78	-1,161.01	796.96	1,408.22	0.00	0.00	
6,500.00	14.14	145.53	6,324.76	-1,181.15	810.78	1,432.65	0.00	0.00	
6,591.00	14.14	145.53	6,413.00	-1,199.47	823.36	1,454.87	0.00	0.00	WILLIAMS_FORK.MBL (TVD)
6,600.00	14.14	145.53	6,421.73	-1,201.28	824.61	1,457.07	0.00	0.00	
6,700.00	14.14	145.53	6,518.70	-1,221.42	838.43	1,481.50	0.00	0.00	
6,766.85	14.14	145.53	6,583.52	-1,234.88	847.67	1,497.82	0.00	0.00	
6,800.00	13.14	145.53	6,615.74	-1,241.33	852.09	1,505.64	3.00	-3.00	
6,900.00	10.14	145.53	6,713.67	-1,257.96	863.51	1,525.82	3.00	-3.00	
7,000.00	7.14	145.53	6,812.52	-1,270.35	872.02	1,540.85	3.00	-3.00	
7,100.00	4.14	145.53	6,912.03	-1,278.46	877.58	1,550.68	3.00	-3.00	
7,200.00	1.14	145.53	7,011.91	-1,282.26	880.19	1,555.29	3.00	-3.00	
7,238.09	0.00	0.00	7,050.00	-1,282.57	880.41	1,555.67	3.00	-3.00	
7,300.00	0.00	0.00	7,111.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,338.09	0.00	0.00	7,150.00	-1,282.57	880.41	1,555.67	0.00	0.00	TOP_GAS.MBL (TVD)
7,400.00	0.00	0.00	7,211.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,500.00	0.00	0.00	7,311.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,600.00	0.00	0.00	7,411.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,700.00	0.00	0.00	7,511.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,800.00	0.00	0.00	7,611.91	-1,282.57	880.41	1,555.67	0.00	0.00	
7,900.00	0.00	0.00	7,711.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,000.00	0.00	0.00	7,811.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,100.00	0.00	0.00	7,911.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,200.00	0.00	0.00	8,011.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,300.00	0.00	0.00	8,111.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,400.00	0.00	0.00	8,211.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,500.00	0.00	0.00	8,311.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,600.00	0.00	0.00	8,411.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,700.00	0.00	0.00	8,511.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,800.00	0.00	0.00	8,611.91	-1,282.57	880.41	1,555.67	0.00	0.00	
8,900.00	0.00	0.00	8,711.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,000.00	0.00	0.00	8,811.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,100.00	0.00	0.00	8,911.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,200.00	0.00	0.00	9,011.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,260.09	0.00	0.00	9,072.00	-1,282.57	880.41	1,555.67	0.00	0.00	ROLLINS.MBL (TVD)
9,300.00	0.00	0.00	9,111.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,400.00	0.00	0.00	9,211.91	-1,282.57	880.41	1,555.67	0.00	0.00	
9,410.09	0.00	0.00	9,222.00	-1,282.57	880.41	1,555.67	0.00	0.00	TD.MBL (TVD)

Cathedral Energy Services

Planning Report

Database:	USA EDM 5000 Multi Users DB	Local Co-ordinate Reference:	Well PUCKETT 42A-23
Company:	Caerus Oil & Gas	TVD Reference:	30' KB @ 8562.00usft (H&P 330)
Project:	Garfield County, CO (UTM 12N)	MD Reference:	30' KB @ 8562.00usft (H&P 330)
Site:	S23-T6S-R97W (MESA C23)	North Reference:	True
Well:	PUCKETT 42A-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	PLAN #2		

Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
PUCKETT 42A-23 PBHL	0.00	0.00	9,222.00	-1,282.57	880.41	14,360,590.20	2,435,628.90	39.511403	-108.180758
- plan hits target center									
- Circle (radius 50.00)									

Formations						
Measured Depth	Vertical Depth	Name	Lithology	Dip	Dip Direction	
(usft)	(usft)			(°)	(°)	
6,361.04	6,190.00	OHIO_CREEK.MBL (TVD)				
6,591.00	6,413.00	WILLIAMS_FORK.MBL (TVD)				
7,338.09	7,150.00	TOP_GAS.MBL (TVD)				
9,260.09	9,072.00	ROLLINS.MBL (TVD)				
9,410.09	9,222.00	TD.MBL (TVD)				