

Grynberg Petroleum, Schulte #1-13, Reentry **Plugging Subsequent**

Objective: **Re-enter** Davis Oil well drilled and abandoned Sept. 1958

Deepen to Granite Wash. Set 5 1/2" casing.
SWSW Sec 3, T6S, R52W, Lincoln County, CO
API 05-073-05055

Lat/Long: 39.550423/-103.207815 OR

39, 33' 01.524" +/-103, 12' 28.1357"

238' of 8 5/8" 24# Casing, Cemented to surface

From Food Store in Anton CO turn South on blacktop road.

Go approx. 10 miles and turn left at the fork.

Go approx. 300 yards and take the first right (south).

In 1/2 mile look left and see new dirt mounds with caution tape
about 800' off the road.

Continue south 1/4 mile and see white plastic storage tubes.

Turn thru fence at white plastic and follow fence 1/4 mile north to well.

Use your GPS.

Reenter 7 7/8" hole to 7547'. Drill new hole to 8200'.

Set 5 1/2" 17# J or K55 or higher LTC Casing

Cement: TD to top of Marmaton + 50% excess.

DV 100 below Cheyenne. Cement to 200' above Dakota.

13 Centralizers, 2 Cnt Bskts, DV tool

15 sks top off

90 sks Type A Cement
15.8 ppg and 1.18 ft.³/sk

CIBP at 240 feet

Re-enter hole drilled in 1958

7 7/8" Hole Drilled to 7547'

TD' ed at 7547' in 1958

GL: 4915

Spud approx 6/1/2016

Run 7" surface to 500' and test to 500PSI in
truck prior to drillout.

Niobrara	3045
Ft. Hayes	3560
Graneros	3600
D Sand	4002
J Sand	4050
Dakota/ Cheyenne	4352
Morrison	4600
Day Ck	4936
Blaine	5140
Cedar Hills Sltly Sd C	5250
Stone Corral	5382
Wolfcamp	5564
Virgil	6171
Missouri	6430
Lansing K.C.	6173
Des Moines	6754
Cherokee	
Atoka	
Morrow Shale	7305
Morrow Sand	7414
Spargen	7515
Arbuckle	7595
Granite Wash	7850
TD	8000

Plugging information added

Randy Edelen September 16, 2016

Richard Miller 303-850-7490

Rev 4/3/2016

r.miller@Grynberg.com