

## Rangely Weber Sand Unit

Well Details:	
STATE & CO	CO - Rio Blanco
TWNS & RNG	TN002 & RW102W
SECTION	(NE NW) 32
API	51030556700
CHEVNO	DE5629

Casing Details:	
Type	Depth
KB	5247
16in. UNKNOWN #/ft, 62.5	0 - 60,' 77 sxs cmt
10.75in. UNKNOWN #/ft, 40.5	0 - 1481,' 600 sxs cmt
7in. J-55 #/ft, 23	0 - 5584,' 1300 sxs cmt
N/Ain. N/A #/ft, N/A	5584 - 6210,' N/A sxs cmt
in. #/ft.	-,' sxs cmt
in. #/ft.	-,' sxs cmt
in. #/ft.	-,' sxs cmt
in. #/ft.	-,' sxs cmt
TOP OH	5584
BTM OH	6210
PBTD	6210
TD	6210

Formation	Depth
Niobrara	1700
Frontier	2595
Frontier Snd	2681
Mowry	
Dakota	2945
Morrison	3709
Curtis	3809
Entrada	3962
Carmel	4017
Navajo	4620
Chinle	4742
Shinarump	4810
Moenkopi	5034
Weber	5473

Isolation PKR @	5368
-----------------	------

COGCC Regulations: Set Isolation Packer within 100' of perfs

GOC_CALC	5587	HCPV
----------	------	------

Weber 1a	5473	22%
Weber 2	5629	
Weber 3a	5636	17%
Weber 4	5720	
Weber 5a	5746	31%
Weber 6	5876	
Weber 7a	5880	11%
Weber 8	5983	
Weber 9a	5996	16%
Weber 10	6100	
Weber 11a	6126	4%

OWC_CALC	6407
----------	------

## UNION PACIFIC 1-32

### Current Wellbore

KB 5247

16in. UNKNOWN #/ft, 62.5  
0 - 60,' 77 sxs cmt

10.75in. UNKNOWN #/ft, 40.5  
0 - 1481,' 600 sxs cmt

7in. J-55 #/ft, 23  
0 - 5584,' 1300 sxs cmt

TOP OH 5584  
BTM OH 6210  
PBTD 6210  
TD 6210

2-7/8" FL tubing

Hydroseal PKR 5368

Baker FH Slick Skirt w/ 1.875F 5404

47B4 Loc-Set PKR 5410

EOT 6180

\*\*\*\*DOUBLE CHECK TUBING LANDING DETAIL IN WELL/TOUR FILE\*\*\*\*

#### Notes:

- 1- Tight spot noted @ 5433'
- 2- All injection exits perfs in FG tbg
- 3-
- 4.-